

CONVEY-ALL
INDUSTRIES INC.



INDUSTRIAL CAPACITY
COMMERCIAL SEED TENDER
INNOVATIVE DESIGN

INNOVATIVE QUALITY SOLUTIONS

CST-C COMMERCIAL SEED TENDER



- Unload over 1,000 bu. in just 20 minutes
- 16 function wireless remote option with conveyor raise, lower, swing, fold, gate open/close
- Use the CST-C year round for seed in spring, and to receive grain from combine or grain cart and haul to storage or market
- Optional camera and monitor for easier unloading position
- Self contained power pack with diesel or electric start gas engine
- Over 20 ft. of conveyor swing to fill all tanks quickly without moving the truck
- Manufactured in 4 sizes from 20' (600 bu.) to 40' (1190 bu.)
- High quality electric roll tarp features smooth operation
- Epoxy coated interior
- 10' hopper height on CST models; easily fits under most bulk systems



WHAT FARMERS SAY ABOUT THEIR CST TENDER:

"Excellent unit, No Complaints. Upped our seeding input 50 plus acres per day, everything is on one unit and also cut our fill time from 30 minutes to 8 minutes."

BARRY, INSINGER, SK

"We run two John Deere 1910 air carts. We've cut our fill time from 35 minutes to 12 minutes and basically eliminated one truck."

DEREK, FAHLER, AB

"With five compartments we service our air seeder and floater at the same time. Our fill time is a third of what it was and now we do it all with one truck."

PAUL, MIAMI, MB

CST-16' TO 20' MODELS



- Available with 2 or 3 compartments allowing for flexibility of field needs
- Manufactured for a 34" rail mount
- Manufactured in 3 sizes from 16' (490 bu.) to 20' (610 bu.)
- Available with a self-contained hydraulic pack
- Available with stainless steel conveyor and stainless steel hopper bottoms
- Full length catwalks (on truck mount only)
- High quality electric roll tarp
- 10" tube, 16" belt



CST SPECIFICATIONS

Model	Length in Feet	Total Cubic Feet (Bu.)	Total* Tons (Tonnes)	Number, Size of Compartments	Cubic Feet Per Compartment	Tons Per Compartment	Conveyor Length	Discharge Height	Body Width	Overall Height	Conveyor Swing
CST-16	16	608 (490)	18.24 (16.55)	2-8'	8'=304	9.12	20'	10'-12'	8'	9'10"	25'7"
CST-18	18	684 (550)	20.52 (18.62)	3-6'	6'=228	6.84	20'	10'-12'	8'	9'10"	25'7"
CST-20	20	760 (610)	22.80 (20.68)	2-6' & 1-8'	6'=228 8'=304	6.84 9.12	20'	10'-12'	8'	9'10"	25'7"
CST-20-C	20	750 (600)	20.5 (18.5)	2-6' & 1-8"	6'=205 8'=275	6.15 8.25	30'3"	5' to 17'	8'	13'5"	22'10"
CST-26-C	26	975 (780)	26.7 (24.0)	3-6' & 1-8'	6'=205 8'=275	6.15 8.25	30'3"	5' to 17'	8'	13'5"	22'10"
CST-32-C	32	1195 (955)	33.0 (29.7)	4-8'	8'=275	8.25	30'3"	5' to 17'	8'	13'5"	22'10"
CST-40-C	40	1495 (1190)	41.25 (37.1)	5-8'	8'=275	8.25	30'3"	5' to 17'	8'	13'5"	22'10"

* Based on 60 lbs./cu.ft.

FEATURES AND OPTIONS



Conveyor swings out to load rear compartments.



16 Function Wireless Remote



L.E.D. Gate indicators



Self contained power pack.
Gas or Diesel



All aluminum anodized
control valves



Positioning Camera. Equipped with
microphone and in-cab monitor
with speaker

OTHER OPTIONS

- Stainless steel conveyor and/or various components
- LED work lights
- Gas or Diesel option available for self-contained power pack
- Self contained hydraulics
- Rear conveyor may be removed for elevator unloading

CONVEY-ALL INDUSTRIES INC.

Box 2008, 130 Canada St., Winkler, MB R6W 4B7

1-800-418-9461

(204) 325-4195 FAX: (204) 325-8116

WWW.CONVEY-ALL.COM