

# SHREDDER RE



Steep and deep  
+ Mountain / Deep Snow

Bright White / Evo Red  
Black

## ROTAX® ENGINE

	850 E-TEC	850 E-TEC Turbo R
<b>Engine details</b>	Liquid-cooled, two-stroke, 3-D R.A.V.E.™	Liquid-cooled, two-stroke, turbocharged, 3-D R.A.V.E.™
<b>Cylinders</b>	2	
<b>Displacement</b>	849 cc	
<b>Bore</b>	82 mm	
<b>Stroke</b>	80.4 mm	
<b>Maximum engine speed</b>	7900 RPM	
<b>Carburation</b>	Electronic Direct Injection with additional booster injectors	
<b>Recommended fuel type</b>	Unleaded	
<b>Minimum octane</b>	95	
<b>Fuel tank</b>	37 liters	
<b>Oil tank capacity (2-stroke)</b>	3.4 liters	

## POWERTRAIN

<b>Drive clutch type</b>	pDrive with clickers
<b>Driven clutch type</b>	QRS
<b>Brake system</b>	Hydraulic brake with braided steel brake line, adjustable brake lever, aluminium master cylinder

## DRY WEIGHT

<b>Dry weight</b>	3700: 215 kg	3700: 221 kg 3900: 224 kg
	3900 x 2.5: 217 kg	
	3900 x 3.0: 218 kg	

## FEATURES

<b>Frame</b>	Radien <sup>2</sup>
<b>Skis</b>	Blade DS+
<b>Seating</b>	Shredder DS, 1-up
<b>Handlebar</b>	U-type aluminium with hooks, low grab handle
<b>Riser block height</b>	145 mm
<b>Starter</b>	Manual with SHOT
<b>Reverse</b>	RER

## COLOUR

## DIMENSIONS

<b>Vehicle overall length*</b>	3060 mm (3700) 3190 mm (3900)
<b>Vehicle overall width</b>	1120 mm
<b>Vehicle overall height</b>	1280 mm
<b>Ski stance</b>	921 mm
<b>Track nominal width</b>	381 mm
<b>Track nominal length</b>	3705 mm 3923 mm (64 mm) 3912 mm (76 mm)
<b>Track profile height</b>	64 mm PowderMax 76 mm PowderMax X-Light (only 3900)

## SUSPENSION

<b>Front suspension</b>	LFS
<b>Front shock</b>	KYB PRO 36 EA-3 R Kashima
<b>Rear suspension</b>	PPS <sup>2</sup> -DS+
<b>Center shock</b>	KYB 46 Plus Kashima
<b>Rear shock</b>	KYB PRO 46 HLCR Kashima

\*Overall vehicle length without snow flap.

©2023 Bombardier Recreational Products Inc., (BRP). All rights reserved. TM, ® and the BRP logo are trademarks of BRP or its affiliates.  
\*All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation.