

2025 OUTLANDER MAX DPS 850 / 1000R



■ Granite Grey / 850 / 1000R

ENGINE	850	1000R
Type	82 hp / 66 lb-ft, Rotax 999 cc V-twin, DOHC, liquid-cooled	101 hp / 69 lb-ft, Rotax 999 cc V-twin, DOHC, liquid-cooled
Fuel Delivery System	Intelligent Throttle Control (ITC™) with Electronic Fuel Injection (EFI)	
Transmission	pDrive primary CVT L / H / N / R / P	
Drive Train	Selectable 2WD / 4WD with Visco-Lok ¹ QE auto-locking front differential	
Driving Assistance	Work / Standard / Sport modes Intelligent Engine Braking (iEB™)	
Power Steering	Tri-Mode Dynamic Power Steering (DPS™)	

SUSPENSIONS

Front Suspension	Arched Double A-arm 10.8 in. (27.4 cm) travel	
Front Shocks	Twin-tube	
Rear Suspension	Arched Double A-arm 12 in. (30.5 cm) travel	
Rear Shocks	Twin-tube	

TIRES & WHEELS

Front / Rear Tires	26 x 8/10 x 12 in.	26 x 8/10 x 14 in.
Wheels	12 in. aluminum	14 in. aluminum

BRAKES

Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers	
Rear	Single 214 mm disc brake with hydraulic twin-piston caliper	

PACKAGE HIGHLIGHTS

850	1000R
<ul style="list-style-type: none"> • Tri-Mode Dynamic Power Steering (DPS™) • Intelligent Engine Braking (iEB™) and driving modes • Visco-Lok¹ QE auto-locking front differential • 26 in. tires with 12 in. aluminum wheels • 7.6 in. wide digital display • Full skid plate • Front dropdown storage • Rear removable storage • Phone storage 	<ul style="list-style-type: none"> • Tri-Mode Dynamic Power Steering (DPS™) • Intelligent Engine Braking (iEB™) and driving modes • Visco-Lok¹ QE auto-locking front differential • 26 in. tires with 14 in. aluminum wheels • 4-disc brake system • 7.6 in. wide digital display • Full skid plate • Front dropdown storage • Rear removable storage • Phone storage • LED signature lights

DIMENSIONS & CAPACITIES

	850	1000R
Estimated Dry Weight*	992 lb (451 kg)	
L x W x H	94.8 x 48.5 x 56.4 in. (240.8 x 123.2 x 143.2 cm)	
Wheelbase	60.8 in. (154.4 cm)	
Ground Clearance	11.5 in. (29.2 cm)	
Seat Height	37.8 in. (96 cm)	
Rack Capacity	Front: 120 lb (54.4 kg) Rear: 240 lb (109 kg)	
Storage Capacity	10.6 gal (40 L)	
Towing Capacity	1,830 lb (830 kg)	
Fuel Capacity	5.1 gal (19.5 L)	

FEATURES

Gauge	7.6 in. wide digital display	
Instrumentation	Phone storage	
Ignition	RF Digitally Encoded Security System (D.E.S.S.™)	
Lighting	LED headlights and taillights	LED headlights and taillights LED signature
Winch	N/A	
Seat	Standard	
Handlebar	Standard	
Protection	Full skid plate	

WARRANTY & EXTENDED SERVICE

Factory Warranty	6-month BRP limited warranty	
Extended Service Terms	B.E.S.T. term available up to 36 months	

can-am®

© 2024 Bombardier Recreational Products Inc. (BRP). All rights reserved. ®, TM and the BRP logo are registered trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. *Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners. For other jurisdictions, see your local dealer. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at any time to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in the U.S.A. call the ATV Safety Institute at 1-800-887-2887. In Canada, call the Canadian Safety Council at 1-613-739-1535, ext 227. ATVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding, alcohol and drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90 cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.

