Engine	Transversal 90° V-twin, two valves per cylinder.
Displacement	853 cc
Cooling	Air
Bore x Stroke	84 x 77 mm
Maximum power	65 hp - 6.800 rpm
Maximum torque	53.8 ft-lb - 5.000 rpm
Gearbox	6 speed
Front suspension	Hydraulic telescopic fork Ø 40 mm.
Rear suspension	Swingarm Twin-sided with two spring preload adjustable shock absorbers.
Front Brakes	Stainless steel floating disk Ø 320 mm, Brembo caliper with 4 differentiated and opposed pistons.
Pear Brakes	Stainless steel disk Ø 260 mm floating 2 nistons caliner

- 7

	seu pisiolis.
Rear Brakes	Stainless steel disk Ø 260 mm, floating 2 pistons caliper.
Front wheel	Spoked, 18" 100/90.
Rear wheel	Spoked, 17" 150/70.
Seat height	30.7 in
Dry weight	447.5 lbs
Kerb weight	491.6 lbs (According to guideline VO (EU) 168/2013 with all fluids, with standard equip- ment and fuelled with at least 90% of usable tank volume).
Fuel tank	5.5 gal (1.05 gal reserve)
Compliance	Euro 5.
CO2 Emissions	119 g/km (CO²)
Consumption	48 mpg
Electronics	LED brake light (LED indicators not included), MGCT Moto Guzzi Traction Control, Stan- dard double channel ABS.





RED STRIPE MONOCHROME

SILVER STRIPE MONOCHROME