



160 Otter



Specifications

10 Degree Deadrise
16' 6" LOA
72" Beam
66" Bottom Width
24" Side Height
.190" 5086 Keel
.125" 5052 Sides
.190" 5086 Transom
Approximate Dry Weight 1,130lbs
Maximum Horsepower 40hp
45L Fuel Capacity

Standard Features

Engine & Pump

Mercury JET 40ELPT
Stainless Steel Impeller

Hull

Coyote Exclusive Full Radius Pre-Formed Sides
Exclusive HR Tunnel Upgrade

Full Reverse Chines
Full Length Box Stringers

Centre Console or Tiller

Level Flotation Kit

Interior

Raised Front Deck
Vinyl Covered Floor Boards
Driver Seat / Pedestal
2 Cup Holders

Electrical Features

Auto Bilge Pump
Dual Battery Ready

Trailer

1,650lb Galvanized Trailer

Available Options

Engine & Pump

Smartcraft Engine Monitoring Gauge

Hull

4'x10' .375" UHMW Hull Protection w/ Stainless Fastners
Intake Protection Bars
Glass Windshield Kit

Interior

32" Storage Box/Seat for Centre Console
UltraDeck Premium Gunnel & Flooring Options

Paint & Exterior

Interior & 1/2 Side Paint (Charcoal Zolatone)

Trailer Options

Spare Tire / Carrier

