



165 Otter



Specifications

- 10 Degree Deadrise
- 16' 10" LOA
- 72" Beam
- 66" Bottom Width
- 24" Side Height
- .190" 5086 Keel
- .125" 5052 Sides
- .190" 5086 Transom
- Approximate Dry Weight 1,300lbs
- Maximum Horsepower 65hp
- 90L Fuel Capacity

Standard Features

Engine & Pump

- Mercury JET 65ELPT
- Stainless Steel Impeller

Hull

- Coyote Exclusive Full Radius Pre-Formed Sides
- Exclusive HR Tunnel Upgrade

- Full Reverse Chines

- Full Length Box Stringers

Centre Console or Tiller

- Level Flotation Kit

Interior

- Raised Front Deck
- Single Hatch for Semi-Dry Bow Storage
- Vinyl Covered Floor Boards
- Driver Seat / Pedestal
- 2 Cup Holders
- 4 Scotty Rod Holder Bases

Electrical Features

- Auto Bilge Pump
- Dual Battery Ready

Trailer

- 1,650lb Galvanized Trailer

Available Options

Engine & Pump

- Smartcraft Engine Monitoring Gauge

Hull

- 4'x12.5' .375" UHMW Hull Protection w/ Stainless Fastners
- Intake Protection Bars
- Glass Windshield Kit

Interior

- 32" Storage Box/Seat for Centre Console
- UltraDeck Premium Gunnel & Flooring Options

Paint & Exterior

- Interior & Full Side Paint (Coyote Coat)

Trailer Options

- Spare Tire / Carrier

