

CARGO TRAILERS 5'/6'/7' WIDE ALUMINUM

A Rainbow Trailers Aluminum Cargo Trailer is built with quality and designed to help you get your cargo or equipment from point A to point B in an environment protected from dust and weather.



EXPRESS

STANDARD FEATURES

- › 3/8" Plywood interior wall
- › Ramp transition flap
- › Easy lube spring axle
- › 4 Leaf spring suspension
- › 0.030 Aluminum skin (black, white or pewter)
- › 3M VHB Taped exterior sidewalls (screwless)
- › Aluminum checker plate stone guard protection
- › Galvanized roof
- › Jeep style single aluminum fenders (teardrop on all tandem axle models)
- › Aerodynamic V-nose
- › 32" RV style side door (6' & 7' wide)
- › Rear barn doors with lockable cam lock
- › All exterior wiring enclosed in poly conduit
- › DOT Compliant safety chains
- › DOT Compliant electric breakaway kit on all 5,000 lb. GVW trailers
- › DOT Compliant lights

AVAILABLE OPTIONS - ALL

- Spare tire
- Spare tire holder
- Rear ramp door
- Extra height (6" increments)
- HD Scissor jacks
- E-track tie down system
- Interior light
- LED Lights
- Jack foot
- Bar lock on RV side door
- 3 1/2" round wall vents
- Exterior loading lights
- Recessed floor mounted D-rings

Excursion

STANDARD FEATURES INCLUDES ALL EXPRESS STANDARD FEATURES, PLUS:

- › One piece translucent roof
- › LED Lights
- › Wall mounted interior light w/ switch
- › Jack foot
- › One 3 1/2" round wall vent

AVAILABLE OPTIONS ALL EXPRESS OPTIONS ARE AVAILABLE ON EXCURSION

- Torflex axle upgrade
- Aluminum wheel upgrade
- Aluminum wall vent
- Upgrade to 7K jack (7,000 lb. GVWR)
- Motorcycle wheel chalk
- Extended V-nose with front ramp door
- Beavertail
- Roof rack
- Dome light with switch
- Quad flooring
- Two tone colour
- Upgrade to 5,200 lb. axles (7' wide only)

summit

STANDARD FEATURES INCLUDES ALL EXCURSION STANDARD FEATURES, PLUS:

- › 3/8" Luaun with white vinyl finish
- › E-track tie down system
- › Easy lube torflex axles
- › Dome light with switch
- › 16" o/c wall uprights & roof bows
- › Chrome centre caps
- › Ramp transition flap
- › Roof vent (adds 4" to overall height)

AVAILABLE OPTIONS ALL EXCURSION OPTIONS ARE AVAILABLE ON SUMMIT

- Insulation package

**Photos may contain options not included in the base trailer.*



ALUMINUM 1 x 3,500	CA5X8A13	CA5X10A13	CA6X10A13	CA6X12A13	CA6X14A13
Overall Length	11' 6"	13' 6"	14'	16'	18'
Overall Height	77.5" *	77.5" *	90"	90"	90"
Overall Width	81"	81"	93"	93"	93"
Interior Height	60" *	60" *	72"	72"	72"
Interior Length	8' + V-nose	10' + V-nose	10' + V-nose	12' + V-nose	14' + V-nose
Interior Width	57"	57"	69"	69"	69"
Deck Height	16"	16"	16"	16"	16"
Hitch Height	11"	11"	13" to 14"	13" to 14"	13" to 14"
Rear Opening - Height	54.5" (Barn) *	54.5" (Barn) *	66.5" (Barn) 68" (Ramp)	66.5" (Barn) 68" (Ramp)	66.5" (Barn) 68" (Ramp)
Rear Opening - Width	50" (Barn)	50" (Barn)	62" (Barn) 63.75" (Ramp)	62" (Barn) 63.75" (Ramp)	62" (Barn) 63.75" (Ramp)
Side Opening - Height	N/A	N/A	66.5"	66.5"	66.5"
Side Opening - Width	N/A	N/A	30"	30"	30"
Ball Size	2"	2"	2"	2"	2"
Axles	1 x 3,500 lb.	1 x 3,500 lb.	1 x 3,500 lb.	1 x 3,500 lb.	1 x 3,500 lb.
GAWR	3,500 lbs.	3,500 lbs.	3,500 lbs.	3,500 lbs.	3,500 lbs.
GVWR	2,990 lbs.	2,990 lbs.	2,990 lbs.	2,990 lbs.	2,990 lbs.
Curb Weight	coming soon ***	coming soon ***	coming soon ***	coming soon ***	coming soon ***
Payload Capacity	coming soon ***	coming soon ***	coming soon ***	coming soon ***	coming soon ***
Brakes	Option	Option	Option	Option	Option
Tires - Radial	205/75R15C	205/75R15C	205/75R15C	205/75R15C	205/75R15C
Ply	6 Ply	6 Ply	6 Ply	6 Ply	6 Ply
Bolt Pattern	5-45 Bolt	5-45 Bolt	5-45 Bolt	5-45 Bolt	5-45 Bolt
Frame & Hitch	3" x 2" tube	3" x 2" tube	3" x 2" tube	3" x 2" tube	3" x 2" tube
Crossmembers	2" x 1 1/2" tube	2" x 1 1/2" tube	2" x 1 1/2" tube	2" x 1 1/2" tube	2" x 1 1/2" tube
Crossmembers spacing	24" o/c	24" o/c	24" o/c	24" o/c	24" o/c
Jack	2,000 lb. A-Frame	2,000 lb. A-Frame	2,000 lb. A-Frame	2,000 lb. A-Frame	2,000 lb. A-Frame
Electrical Hook-up	7 Prong RV Plug	7 Prong RV Plug	7 Prong RV Plug	7 Prong RV Plug	7 Prong RV Plug
Floor	3/4" Plywood	3/4" Plywood	3/4" Plywood	3/4" Plywood	3/4" Plywood

ALUMINUM 2 x 3,500	CA6X10A23	CA6X12A23	CA6X14A23	CA7X12A23	CA7X14A23	CA7X16A23	CA7X18A23
Overall Length	14'	16'	18'	16' 6"	18' 6"	20' 6"	22' 6"
Overall Height	91"	91"	91"	91" *	91" *	91" *	91" *
Overall Width	93"	93"	93"	102"	102"	102"	102"
Interior Height	72"	72"	72"	72" *	72" *	72" *	72" *
Interior Length	10' + V-nose	12' + V-nose	14' + V-nose	12' + V-nose	14' + V-nose	16' + V-nose	18' + V-nose
Interior Width	69"	69"	69"	78"	78"	78"	78"
Deck Height	17"	17"	17"	17"	17"	17"	17"
Hitch Height	13" to 14"	13" to 14"	13" to 14"	14" to 15"	14" to 15"	14" to 15"	14" to 15"
Rear Opening - Height	66.5" (Barn) 68" (Ramp)	66.5" (Barn) 68" (Ramp)	66.5" (Barn) 68" (Ramp)	66.5" (Barn) 68" (Ramp) *	66.5" (Barn) 68" (Ramp) *	66.5" (Barn) 68" (Ramp) *	66.5" (Barn) 68" (Ramp) *
Rear Opening - Width	62" (Barn) 63.75" (Ramp)	62" (Barn) 63.75" (Ramp)	62" (Barn) 63.75" (Ramp)	71.25" (Barn) 72.75" (Ramp)	71.25" (Barn) 72.75" (Ramp)	71.25" (Barn) 72.75" (Ramp)	71.25" (Barn) 72.75" (Ramp)
Side Opening - Height	N/A	66.5"	66.5"	66.5" *	66.5" *	66.5" *	66.5" *
Side Opening - Width	N/A	30"	30"	30"	30"	30"	30"
Ball Size	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"
Axles	2 x 3,500 lb.	2 x 3,500 lb.	2 x 3,500 lb.	2 x 3,500 lb.	2 x 3,500 lb.	2 x 3,500 lb.	2 x 3,500 lb.
GAWR	7,000 lbs.	7,000 lbs.	7,000 lbs.	7,000 lbs.	7,000 lbs.	7,000 lbs.	7,000 lbs.
GVWR	7,000 lbs.	7,000 lbs.	7,000 lbs.	7,000 lbs.	7,000 lbs.	7,000 lbs.	7,000 lbs.
Curb Weight	1,180 lbs.	1,323 lbs.	1,466 lbs.	1,455 lbs.	1,609 lbs.	1,764 lbs.	1,918 lbs.
Payload Capacity	6,520 lbs.	6,377 lbs.	6,234 lbs.	6,245 lbs.	6,091 lbs.	5,936 lbs.	5,782 lbs.
Brakes	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Tires - Radial	205/75R15C	205/75R15C	205/75R15C	205/75R15C	205/75R15C	205/75R15C	205/75R15C
Ply	6 Ply	6 Ply	6 Ply	6 Ply	6 Ply	6 Ply	6 Ply
Bolt Pattern	5-45 Bolt	5-45 Bolt	5-45 Bolt	5-45 Bolt	5-45 Bolt	5-45 Bolt	5-45 Bolt
Frame & Hitch	4" x 2" tube	4" x 2" tube	4" x 2" tube	Hitch 5" x 2" tube **	Hitch 5" x 2" tube **	Hitch 5" x 2" tube **	Hitch 5" x 2" tube **
Crossmembers	3" x 1 1/2" tube	3" x 1 1/2" tube	3" x 1 1/2" tube	3" x 1 1/2" tube	3" x 1 1/2" tube	3" x 1 1/2" tube	3" x 1 1/2" tube
Crossmembers spacing	24" o/c	24" o/c	24" o/c	24" o/c	24" o/c	24" o/c	24" o/c
Jack	2,000 lb. A-Frame	2,000 lb. A-Frame	2,000 lb. A-Frame	2,000 lb. A-Frame	2,000 lb. A-Frame	2,000 lb. A-Frame	2,000 lb. A-Frame
Electrical Hook-up	7 Prong RV Plug	7 Prong RV Plug	7 Prong RV Plug	7 Prong RV Plug	7 Prong RV Plug	7 Prong RV Plug	7 Prong RV Plug
Floor	3/4" Plywood	3/4" Plywood	3/4" Plywood	3/4" Plywood	3/4" Plywood	3/4" Plywood	3/4" Plywood

*Summit Class - all 5' & 7' will have 6" higher heights. **Frame is 4" x 2" tube. *** Visit our website for up to date information. Measurements are approximate and subject to change.

RAINBOW TRAILERS ARE THE BEST CHOICE FOR:

- > EASIER AND STRAIGHTER PULLING
- > DURABILITY AND LONGEVITY
- > SAFETY AND SECURITY

PLUS WE OFFER A 100% CANADIAN WARRANTY



RAINBOW TRAILERS

335 Broadway Street, Box 189 | Cartwright, MB, Canada R0K 0L0
 P (204) 529 2581 | F (204) 529 2583 | E info@rainbowtrailers.net

CONTACT YOUR LOCAL RAINBOW TRAILER
 DEALER FOR MORE INFORMATION