

HEAVY DECK ABOVE TRAILERS

EXPRESS | EXCURSION

Rainbow
Trailers
Trailers That Mean Business

HEAVY DECK ABOVE TRAILERS

Backed by an industry leading warranty, our Heavy Deck Above trailers are built to last and deliver performance under even the harshest hauling conditions. With a wide variety of sizes and options, including both Gooseneck or Bumper Hitch, and tandem or tridem axles, the Rainbow Trailers Heavy Deck Above will be perfect for your heavy hauling needs.

EXPRESS

GREAT VALUE, QUALITY COMPONENTS & WORKMANSHIP

STANDARD FEATURES

- › 2' Painted spruce floor
- › Metal preparation by sand blasting
- › 2-Part epoxy primer
- › High quality black top coat paint
- › Heavy duty stake pockets
- › Wiring enclosed in poly conduit

AVAILABLE OPTIONS - ALL

- Spare tire
- Spare tire holder
- RV King pin
- Upgrade to 2 speed jacks
- 15" x 96" Slide in ramps (not available on dovetail trailers)
- Under deck side toolbox
- Rubrail
- Tie down winch
- D-Rings
- LED Lights
- Bumper hitch (pintle ring or 2 5/16" coupler)

AVAILABLE OPTIONS - 2 x 7,000 lb Axle

- Upgrade to 7,000 lb. torflex axles
- Upgrade to tandem 8,000 lb. spring axles (16,000 lb. GVW)
- Aluminum wheels
- 5' Dovetail with 2-20" or 2-44" spring assisted flip over ramps

AVAILABLE OPTIONS - 3 x 7,000 lb Axle

- Upgrade to torflex axles
- Upgrade to tridem 8,000 lb. spring axles (24,000 lb. GVW)
- Aluminum wheels
- 5' Dovetail with 2-20" or 2-44" spring assisted flip over ramps

AVAILABLE OPTIONS - 2 x 10,000 lb Axle

- Upgrade to 12,000 lb. axles
- 5' Dovetail with 20" or 44" spring assisted flip over ramps

Excursion

PREMIUM COMPONENTS & QUALITY WORKMANSHIP

STANDARD FEATURES

INCLUDES ALL EXPRESS STANDARD FEATURES, PLUS:

- › LED Lights
- › Stone guard
- › Silver graphics
- › Steel primed under deck

AVAILABLE OPTIONS

ALL EXPRESS OPTIONS ARE AVAILABLE ON EXCURSION



**Photos may contain options not included in the base trailer.*



HEAVY DECK ABOVE TRAILERS SPECIFICATIONS



	2-7,000 lb. Axles			3-7,000 lb. Axles					2-10,000 lb. Axles				
	OG720	OG725	OG730	OG7320	OG7325	OG7330	OG7335	OG7340	OG1020	OG1025	OG1030	OG1035	OG1040
Overall Length	29'	34'	39'	29'	34'	39'	44'	49'	29'	34'	39'	44'	49'
Deck Length	20'	25'	30'	20'	25'	30'	35'	40'	20'	25'	30'	35'	40'
Overall Width	102"	102"	102"	102"	102"	102"	102"	102"	102"	102"	102"	102"	102"
Deck Width	97"	97"	97"	97"	97"	97"	97"	97"	97"	97"	97"	97"	97"
Deck Height	36"	36"	36"	36"	36"	36"	36"	36"	38"	38"	38"	38"	38"
Hitch Height	29"-37"	29"-37"	29"-37"	29"-37"	29"-37"	29"-37"	29"-37"	29"-37"	31"-39"	31"-39"	31"-39"	31"-39"	31"-39"
Hitch Weight (Empty)	1,078 lbs.	1,159 lbs.	1,235 lbs.	1,441 lbs.	1,613 lbs.	1,780 lbs.	1,947 lbs.	2,114 lbs.	1,323 lbs.	1,521 lbs.	1,719 lbs.	1,917 lbs.	2,115 lbs.
Ball Size	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"
Axles	2-7,000 lb.	2-7,000 lb.	2-7,000 lb.	3-7,000 lb.	3-7,000 lb.	3-7,000 lb.	3-7,000 lb.	3-7,000 lb.	2-10,000 lb.	2-10,000 lb.	2-10,000 lb.	2-10,000 lb.	2-10,000 lb.
GAWR	14,000 lbs.	14,000 lbs.	14,000 lbs.	21,000 lbs.	21,000 lbs.	21,000 lbs.	21,000 lbs.	21,000 lbs.	20,000 lbs.	20,000 lbs.	20,000 lbs.	20,000 lbs.	20,000 lbs.
GVWR	14,000 lbs.	14,000 lbs.	14,000 lbs.	21,000 lbs.	21,000 lbs.	21,000 lbs.	21,000 lbs.	21,000 lbs.	20,000 lbs.	20,000 lbs.	20,000 lbs.	20,000 lbs.	20,000 lbs.
Curb Weight	3,555 lbs.	3,840 lbs.	4,125 lbs.	4,478 lbs.	4,994 lbs.	5,510 lbs.	6,026 lbs.	6,542 lbs.	4,710 lbs.	5,323 lbs.	5,936 lbs.	6,549 lbs.	7,162 lbs.
Payload Capacity	12,545 lbs.	12,260 lbs.	11,975 lbs.	19,672 lbs.	19,156 lbs.	18,640 lbs.	18,124 lbs.	17,608 lbs.	18,290 lbs.	17,677 lbs.	17,064 lbs.	16,451 lbs.	15,838 lbs.
Brakes	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric
Tires	235/80/R16E	235/80/R16E	235/80/R16E	235/80/R16E	235/80/R16E	235/80/R16E	235/80/R16E	235/80/R16E	235/80/R16E	235/80/R16E	235/80/R16E	235/80/R16E	235/80/R16E
Ply	10	10	10	10	10	10	10	10	10	10	10	10	10
Bolt Pattern	8-6.5 Bolt	8-6.5 Bolt	8-6.5 Bolt	8-6.5 Bolt	8-6.5 Bolt	8-6.5 Bolt	8-6.5 Bolt	8-6.5 Bolt	8-6.5 Bolt	8-6.5 Bolt	8-6.5 Bolt	8-6.5 Bolt	8-6.5 Bolt
Frame & Hitch	12" x 14 lb. I-Beam	12" x 14 lb. I-Beam	12" x 14 lb. I-Beam	12" x 19 lb. I-Beam	12" x 19 lb. I-Beam	12" x 19 lb. I-Beam	12" x 19 lb. I-Beam	12" x 19 lb. I-Beam	12" x 19 lb. I-Beam	12" x 19 lb. I-Beam	12" x 19 lb. I-Beam	12" x 19 lb. I-Beam	12" x 19 lb. I-Beam
Cross-members	3" Channel	3" Channel	3" Channel	3" Channel	3" Channel	3" Channel	3" Channel	3" Channel	3" Channel	3" Channel	3" Channel	3" Channel	3" Channel
Cross-members Spacing	16"	16"	16"	16"	16"	16"	16"	16"	16"	16"	16"	16"	16"
Jack	2-12K	2-12K	2-12K	2-12K	2-12K	2-12K	2-12K	2-12K	2-12K	2-12K	2-12K	2-12K	2-12K
Electrical Hook-up	RV	RV	RV	RV	RV	RV	RV	RV	RV	RV	RV	RV	RV
Ramps	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
Floor	2" Spruce	2" Spruce	2" Spruce	2" Spruce	2" Spruce	2" Spruce	2" Spruce	2" Spruce	2" Spruce	2" Spruce	2" Spruce	2" Spruce	2" Spruce

Measurements are approximate and subject to change.

RAINBOW TRAILERS ARE THE BEST CHOICE FOR:

- > EASIER AND STRAIGHTER PULLING
- > DURABILITY AND LONGEVITY
- > SAFETY AND SECURITY

PLUS WE OFFER A 100% CANADIAN WARRANTY



RAINBOW TRAILERS

335 Broadway Street, Box 189 | Cartwright, MB, Canada R0K 0L0
 P (204) 529 2581 | F (204) 529 2583 | E info@rainbowtrailers.net

CONTACT YOUR LOCAL RAINBOW TRAILER DEALER FOR MORE INFORMATION