

# ANGLE IRON SIDE UTILITY TRAILER

From hauling lawn & garden equipment, to ATVs, to a broad range of other applications, the Rainbow Trailers Angle Iron Side Utility is built to last and backed by an industry leading warranty. Available in a wide variety of sizes and options, our Angle Iron Side Utility will be perfect for your light hauling needs.



## EXPRESS

GREAT VALUE, QUALITY  
COMPONENTS & WORKMANSHIP

### STANDARD FEATURES

- › 2" Painted spruce floor
- › Easy lube spring axles
- › Radial tires
- › Metal preparation by sandblasting
- › 2-Part epoxy primer
- › High quality black topcoat paint
- › Enclosed wiring in poly conduit
- › Welded on fenders
- › 7 Prong RV plug
- › Sealed lights DOT rated
- › Spring assisted lawn & garden ramp
- › DOT Compliant safety chains

### AVAILABLE OPTIONS

- LED Lights
- Aluminum wheels
- Upgrade to brake axle
- Upgrade to torflex idler
- Spare tire holder (weld on)
- Spare tire & rim

*\*Photos may contain  
options not included  
in the base trailer.*



# ANGLE IRON SIDE UTILITY TRAILER SPECIFICATIONS



EXPRESS 60"-72"	5X8ASE	5X10ASE	5X12ASE	6X10ASE	6X12ASE	6X14ASE
Overall Length	11' 7"	13' 7"	15' 7"	13' 7"	15' 7"	17' 7"
Deck Length	8'	10'	12'	10'	12'	14'
Overall Width	79"	79"	79"	91"	91"	91"
Between Fenders	60"	60"	60"	72"	72"	72"
Deck Height	19"	19"	19"	19"	19"	19"
Rail Height from Deck	12"	12"	12"	12"	12"	12"
Hitch Height	14"	14"	14"	14"	14"	14"
Hitch Weight (Empty)	66 lbs.	88 lbs.	101 lbs.	99 lbs.	110 lbs.	117 lbs.
Ball Size	2"	2"	2"	2"	2"	2"
Axle	3,500 lbs.	3,500 lbs.	3,500 lbs.	3,500 lbs.	3,500 lbs.	3,500 lbs.
GAWR	3,500 lbs.	3,500 lbs.	3,500 lbs.	3,500 lbs.	3,500 lbs.	3,500 lbs.
GVWR	2,990 lbs.	2,990 lbs.	2,990 lbs.	2,990 lbs.	2,990 lbs.	2,990 lbs.
Curb Weight	683 lbs.	772 lbs.	849 lbs.	838 lbs.	904 lbs.	988 lbs.
Payload Capacity	2,606 lbs.	2,517 lbs.	2,440 lbs.	2,451 lbs.	2,385 lbs.	2,301 lbs.
Brakes	Option	Option	Option	Option	Option	Option
Tires	205/75R15C	205/75R15C	205/75R15C	205/75R15C	205/75R15C	205/75R15C
Ply	6	6	6	6	6	6
Bolt Pattern	5-4.5 bolt	5-4.5 bolt	5-4.5 bolt	5-4.5 bolt	5-4.5 bolt	5-4.5 bolt
Hitch	3" Channel	3" Channel	3" Channel	3" Channel	3" Channel	3" Channel
Crossmembers	2" x 2" Angle	2" x 2" Angle	2" x 2" Angle	2" x 2" Angle	2" x 2" Angle	2" x 2" Angle
Crossmembers spacing	24"	24"	24"	24"	24"	24"
Jack	2,000 lb. A-frame	2,000 lb. A-frame	2,000 lb. A-frame	2,000 lb. A-frame	2,000 lb. A-frame	2,000 lb. A-frame
Electrical Hook-up	RV Plug	RV Plug	RV Plug	RV Plug	RV Plug	RV Plug
Ramp	4' L&G	4' L&G	4' L&G	4' L&G	4' L&G	4' L&G
Floor	2" Spruce	2" Spruce	2" Spruce	2" Spruce	2" Spruce	2" Spruce

EXPRESS 76"-82"	65X10ASE	65X12ASE	65X14ASE	7X10ASE	7X12ASE	7X14ASE
Overall Length	13' 7"	15' 7"	17' 7"	13' 7"	15' 7"	17' 7"
Deck Length	10'	12'	14'	10'	12'	14'
Overall Width	95"	95"	95"	101"	101"	101"
Between Fenders	76"	76"	76"	82"	82"	82"
Deck Height	19"	19"	19"	19"	19"	19"
Rail Height from Deck	12"	12"	12"	12"	12"	12"
Hitch Height	14"	14"	14"	14"	14"	14"
Hitch Weight (Empty)	104 lbs.	112 lbs.	117 lbs.	119 lbs.	126 lbs.	132 lbs.
Ball Size	2"	2"	2"	2"	2"	2"
Axle	3,500 lbs.	3,500 lbs.	3,500 lbs.	3,500 lbs.	3,500 lbs.	3,500 lbs.
GAWR	3,500 lbs.	3,500 lbs.	3,500 lbs.	3,500 lbs.	3,500 lbs.	3,500 lbs.
GVWR	2,990 lbs.	2,990 lbs.	2,990 lbs.	2,990 lbs.	2,990 lbs.	2,990 lbs.
Curb Weight	860 lbs.	937 lbs.	1,036 lbs.	893 lbs.	996 lbs.	1,080 lbs.
Payload Capacity	2,429 lbs.	2,352 lbs.	2,253 lbs.	2,396 lbs.	2,293 lbs.	2,209 lbs.
Brakes	Option	Option	Option	Option	Option	Option
Tires	205/75R15C	205/75R15C	205/75R15C	205/75R15C	205/75R15C	205/75R15C
Ply	6	6	6	6	6	6
Bolt Pattern	5-4.5 bolt	5-4.5 bolt	5-4.5 bolt	5-4.5 bolt	5-4.5 bolt	5-4.5 bolt
Hitch	3" Channel	3" Channel	3" Channel	3" Channel	3" Channel	3" Channel
Crossmembers	2" x 2" Angle	2" x 2" Angle	2" x 2" Angle	2" x 2" Angle	2" x 2" Angle	2" x 2" Angle
Crossmembers spacing	24"	24"	24"	24"	24"	24"
Jack	2,000 lb. A-frame	2,000 lb. A-frame	2,000 lb. A-frame	2,000 lb. A-frame	2,000 lb. A-frame	2,000 lb. A-frame
Electrical Hook-up	RV Plug	RV Plug	RV Plug	RV Plug	RV Plug	RV Plug
Ramp	4' L&G	4' L&G	4' L&G	4' L&G	4' L&G	4' L&G
Floor	2" Spruce	2" Spruce	2" Spruce	2" Spruce	2" Spruce	2" Spruce

Measurements are approximate and subject to change.

## RAINBOW TRAILERS ARE THE BEST CHOICE FOR:

- > EASIER AND STRAIGHTER PULLING
- > DURABILITY AND LONGEVITY
- > SAFETY AND SECURITY

## PLUS WE OFFER A 100% CANADIAN WARRANTY



### RAINBOW TRAILERS

335 Broadway Street, Box 189 | Cartwright, MB, Canada R0K 0L0  
P (204) 529 2581 | F (204) 529 2583 | E info@rainbowtrailers.net

CONTACT YOUR LOCAL RAINBOW TRAILER DEALER FOR MORE INFORMATION