

SOLID SIDE UTILITY TRAILER

From landscaping, to hauling light aggregate, to a broad range of other applications, the Rainbow Trailers Solid Side Utility is built to last and backed by an industry leading warranty. Available in a wide variety of sizes and options, our Solid Side Utility will be perfect for your light hauling needs.



- > 2" painted spruce floor
- > Easy lube spring axles
- › Radial tires
- > Metal preparation by sandblasting
- > 2-Part epoxy primer
- > High quality black topcoat paint
- > Enclosed wiring in poly conduit
- > Welded on fenders
- > 7 Prong RV plug
- > Sealed lights DOT rated
- > Spring assisted lawn & garden ramp
- > DOT Compliant safety chains

AVAILABLE OPTIONS

- ☐ LED Lights
- ☐ Aluminum wheels
- ☐ Upgrade to brake axle
- \square Upgrade to torflex idler
- ☐ Spare tire holder (weld on)
- $\hfill\Box$ Spare tire & rim
- □ 24" Tall side walls (5x8, 5x10, 6x10 only)



^{*}Photos may contain options not included in the base trailer.

SOLID SIDE UTILITY TRAILER SPECIFICATIONS



EXPRESS 60"-72"	5X8SSE	5X10SSE	5X12SSE	6X10SSE	6X12SSE	6X14SSE
Overall Length	11' 8"	13' 8"	15' 8"	13' 8"	15' 8"	17' 8"
Deck Length	8'	10'	12'	10'	12'	14'
Overall Width	79"	79"	79"	91"	91"	91"
Between Fenders	60"	60"	60"	72"	72"	72"
Deck Height	18"	18"	18"	18"	18"	18"
Wall Height	13"	13"	13"	13"	13"	13"
Hitch Height	14"	14"	14"	14"	14"	14"
Hitch Weight (Empty)	66 lbs.	73 lbs.	84 lbs.	79 lbs.	97 lbs.	119 lbs.
Ball Size	2"	2"	2"	2"	2"	2"
Axle	3,500 lbs.	3,500 lbs.	3,500 lbs.	3,500 lbs.	3,500 lbs.	3,500 lbs.
GAWR	3,500 lbs.	3,500 lbs.	3,500 lbs.	3,500 lbs.	3,500 lbs.	3,500 lbs.
GVWR	2,990 lbs.	2,990 lbs.	2,990 lbs.	2,990 lbs.	2,990 lbs.	2.990 lbs.
Curb Weight	705 lbs.	798 lbs.	893 lbs.	882 lbs.	970 lbs.	1,058 lbs.
· ·						
Payload Capacity	2,584 lbs.	2,491 lbs.	2,396 lbs.	2,407 lbs.	2,319 lbs.	2,231 lbs.
Brakes	Option	Option	Option	Option	Option	Option
Tires	205/75R15C	205/75R15C	205/75R15C	205/75R15C	205/75R15C	205/75R15C
Ply	6	6	6	6	6	6
Bolt Pattern	5-4.5 bolt	5-4.5 bolt	5-4.5 bolt	5-4.5 bolt	5-4.5 bolt	5-4.5 bolt
Hitch	3" Channel	3" Channel	3" Channel	3" Channel	3" Channel	3" Channel
Crossmembers	2" x 2" Angle	2" x 2" Angle	2" x 2" Angle	2" x 2" Angle	2" x 2" Angle	2" x 2" Angle
Crossmembers spacing	24"	24"	24"	24"	24"	24"
Jack	2,000 lb. A-frame	2,000 lb. A-frame	2,000 lb. A-frame	2,000 lb. A-frame	2,000 lb. A-frame	2,000 lb. A-frame
Electrical Hook-up	RV Plug	RV Plug	RV Plug	RV Plug	RV Plug	RV Plug
Ramp	4' L&G	4' L&G	4' L&G	4' L&G	4' L&G	4' L&G
Floor	2" Spruce	2" Spruce	2" Spruce	2" Spruce	2" Spruce	2" Spruce
EXPRESS 76"-82"	65X10SSE	65X12SSE	65X14SSE	7X10SSE	7X12SSE	7X14SSE
Overall Length	65X10SSE 13' 8"	65X12SSE 15' 8"	65X14SSE 17' 8"	7X10SSE 13' 8"	7X12SSE 15' 8"	7X14SSE 17' 8"
Overall Length	13' 8"	15' 8"	17' 8"	13' 8"	15' 8"	17' 8"
Overall Length Deck Length	13' 8" 10'	15' 8" 12'	17' 8" 14'	13' 8" 10'	15' 8" 12'	17' 8" 14'
Overall Length Deck Length Overall Width	13' 8" 10' 95"	15' 8" 12' 95"	17' 8" 14' 95"	13' 8" 10' 101"	15' 8" 12' 101"	17' 8" 14' 101"
Overall Length Deck Length Overall Width Between Fenders	13' 8" 10' 95" 76"	15' 8" 12' 95" 76"	17' 8" 14' 95" 76"	13' 8" 10' 101" 82"	15' 8" 12' 101" 82"	17' 8" 14' 101" 82"
Overall Length Deck Length Overall Width Between Fenders Deck Height Wall Height	13' 8" 10' 95" 76" 18"	15' 8" 12' 95" 76" 18"	17' 8" 14' 95" 76" 18"	13' 8" 10' 101" 82" 18"	15' 8" 12' 101" 82" 18"	17' 8" 14' 101" 82" 18"
Overall Length Deck Length Overall Width Between Fenders Deck Height Wall Height Hitch Height	13' 8" 10' 95" 76" 18" 13"	15' 8" 12' 95" 76" 18" 13"	17' 8" 14' 95" 76" 18" 13"	13' 8" 10' 101" 82" 18" 13"	15' 8" 12' 101" 82" 18" 13"	17' 8" 14' 101" 82" 18" 13"
Overall Length Deck Length Overall Width Between Fenders Deck Height Wall Height	13' 8" 10' 95" 76" 18" 13" 14"	15' 8" 12' 95" 76" 18" 13"	17' 8" 14' 95" 76" 18" 13" 14"	13' 8" 10' 101" 82" 18" 13" 14"	15' 8" 12' 101" 82" 18" 13" 14"	17' 8" 14' 101" 82" 18" 13" 14"
Overall Length Deck Length Overall Width Between Fenders Deck Height Wall Height Hitch Height Hitch Weight (Empty)	13' 8" 10' 95" 76" 18" 13" 14" 88 lbs.	15' 8" 12' 95" 76" 18" 13" 14"	17' 8" 14' 95" 76" 18" 13" 14"	13' 8" 10' 101" 82" 18" 13" 14" 95 lbs.	15' 8" 12' 101" 82" 18" 13" 14" 117 lbs.	17' 8" 14' 101" 82" 18" 13" 14"
Overall Length Deck Length Overall Width Between Fenders Deck Height Wall Height Hitch Height Hitch Weight (Empty) Ball Size	13' 8" 10' 95" 76" 18" 13" 14" 88 lbs. 2"	15' 8" 12' 95" 76" 18" 13" 14" 110 lbs. 2"	17' 8" 14' 95" 76" 18" 13" 14" 132 lbs. 2" 3,500 lbs.	13' 8" 10' 101" 82" 18" 13" 14" 95 lbs. 2"	15' 8" 12' 101" 82" 18" 13" 14" 117 lbs. 2" 3,500 lbs.	17' 8" 14' 101" 82" 18" 13" 14" 139 lbs. 2" 3,500 lbs.
Overall Length Deck Length Overall Width Between Fenders Deck Height Wall Height Hitch Height Hitch Weight (Empty) Ball Size Axle	13' 8" 10' 95" 76" 18" 13" 14" 88 lbs. 2" 3,500 lbs.	15' 8" 12' 95" 76" 18" 13" 14" 110 lbs. 2" 3,500 lbs. 3,500 lbs.	17' 8" 14' 95" 76" 18" 13" 14" 132 lbs. 2" 3,500 lbs. 3,500 lbs.	13' 8" 10' 101" 82" 18" 13" 14" 95 lbs. 2" 3,500 lbs. 3,500 lbs.	15' 8" 12' 101" 82" 18" 13" 14" 117 lbs. 2" 3,500 lbs.	17' 8" 14' 101" 82" 18" 13" 14" 139 lbs. 2" 3,500 lbs.
Overall Length Deck Length Overall Width Between Fenders Deck Height Wall Height Hitch Height Hitch Weight (Empty) Ball Size Axle GAWR GVWR	13' 8" 10' 95" 76" 18" 13" 14" 88 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs.	15' 8" 12' 95" 76" 18" 13" 14" 110 lbs. 2" 3,500 lbs. 3,500 lbs.	17' 8" 14' 95" 76" 18" 13" 14" 132 lbs. 2" 3,500 lbs. 3,500 lbs.	13' 8" 10' 101" 82" 18" 13" 14" 95 lbs. 2" 3,500 lbs. 3,500 lbs.	15' 8" 12' 101" 82" 18" 13" 14" 117 lbs. 2" 3,500 lbs. 3,500 lbs.	17' 8" 14' 101" 82" 18" 13" 14" 139 lbs. 2" 3,500 lbs. 2,990 lbs.
Overall Length Deck Length Overall Width Between Fenders Deck Height Wall Height Hitch Height Hitch Weight (Empty) Ball Size Axle GAWR GVWR Curb Weight	13' 8" 10' 95" 76" 18" 13" 14" 88 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs.	15' 8" 12' 95" 76" 18" 13" 14" 110 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs.	17' 8" 14' 95" 76" 18" 13" 14" 132 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs.	13' 8" 10' 101" 82" 18" 13" 14" 95 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs.	15' 8" 12' 101" 82" 18" 13" 14" 117 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs.	17' 8" 14' 101" 82" 18" 13" 14" 139 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs.
Overall Length Deck Length Overall Width Between Fenders Deck Height Wall Height Hitch Height Hitch Weight (Empty) Ball Size Axle GAWR GVWR Curb Weight Payload Capacity	13' 8" 10' 95" 76" 18" 13" 14" 88 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 915 2,374 lbs.	15' 8" 12' 95" 76" 18" 13" 14" 110 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 992 2,297 lbs.	17' 8" 14' 95" 76" 18" 13" 14" 132 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 1080 2,209 lbs.	13' 8" 10' 101" 82" 18" 13" 14" 95 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 948 2,341 lbs.	15' 8" 12' 101" 82" 18" 13" 14" 117 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 1036 2,253 lbs.	17' 8" 14' 101" 82" 18" 13" 14" 139 lbs. 2" 3,500 lbs. 2,990 lbs. 1102 2,187 lbs.
Overall Length Deck Length Overall Width Between Fenders Deck Height Wall Height Hitch Height Hitch Weight (Empty) Ball Size Axle GAWR GVWR Curb Weight Payload Capacity Brakes	13' 8" 10' 95" 76" 18" 13" 14" 88 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 915 2,374 lbs. Option	15' 8" 12' 95" 76" 18" 13" 14" 110 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 992 2,297 lbs. Option	17' 8" 14' 95" 76" 18" 13" 14" 132 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 1080 2,209 lbs. Option	13' 8" 10' 101" 82" 18" 13" 14" 95 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 948 2,341 lbs. Option	15' 8"	17' 8" 14' 101" 82" 18" 13" 14" 139 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 1102 2,187 lbs. Option
Overall Length Deck Length Overall Width Between Fenders Deck Height Wall Height Hitch Height Hitch Weight (Empty) Ball Size Axle GAWR GVWR Curb Weight Payload Capacity Brakes Tires	13' 8" 10' 95" 76" 18" 13" 14" 88 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 915 2,374 lbs. Option 205/75R15C	15' 8" 12' 95" 76" 18" 13" 14" 110 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 992 2,297 lbs. Option 205/75R15C	17' 8" 14' 95" 76" 18" 13" 14" 132 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 1080 2,209 lbs. Option 205/75R15C	13' 8" 10' 101" 82" 18" 13" 14" 95 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 948 2,341 lbs. Option 205/75R15C	15' 8" 12' 101" 82" 18" 13" 14" 117 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 1036 2,253 lbs. Option 205/75R15C	17' 8" 14' 101" 82" 18" 13" 14" 139 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 1102 2,187 lbs. Option 205/75R15C
Overall Length Deck Length Overall Width Between Fenders Deck Height Wall Height Hitch Height Hitch Weight (Empty) Ball Size Axle GAWR GVWR Curb Weight Payload Capacity Brakes Tires Ply	13' 8" 10' 95" 76" 18" 13" 14" 88 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 915 2,374 lbs. Option 205/75R15C 6	15' 8" 12' 95" 76" 18" 13" 14" 110 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 992 2,297 lbs. Option 205/75R15C 6	17' 8" 14' 95" 76" 18" 13" 14" 132 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 1080 2,209 lbs. Option 205/75R15C 6	13' 8" 10' 101" 82" 18" 13" 14" 95 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 948 2,341 lbs. Option 205/75R15C 6	15' 8" 12' 101" 82" 18" 13" 14" 117 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 1036 2,253 lbs. Option 205/75R15C 6	17' 8" 14' 101" 82" 18" 13" 14" 139 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 1102 2,187 lbs. Option 205/75R15C 6
Overall Length Deck Length Overall Width Between Fenders Deck Height Wall Height Hitch Height Hitch Weight (Empty) Ball Size Axle GAWR GVWR Curb Weight Payload Capacity Brakes Tires Ply Bolt Pattern	13' 8" 10' 95" 76" 18" 13" 14" 88 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 915 2,374 lbs. Option 205/75R15C 6 5-4.5 bolt	15' 8" 12' 95" 76" 18" 13" 14" 110 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 992 2,297 lbs. Option 205/75R15C 6 5-4.5 bolt	17' 8" 14' 95" 76" 18" 13" 14" 132 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 1080 2,209 lbs. Option 205/75R15C 6 5-4.5 bolt	13' 8" 10' 101" 82" 18" 13" 14" 95 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 948 2,341 lbs. Option 205/75R15C 6 5-4.5 bolt	15' 8"	17' 8" 14' 101" 82" 18" 13" 14" 139 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 1102 2,187 lbs. Option 205/75R15C 6 5-4.5 bolt
Overall Length Deck Length Overall Width Between Fenders Deck Height Wall Height Hitch Height (Empty) Ball Size Axle GAWR GVWR Curb Weight Payload Capacity Brakes Tires Ply Bolt Pattern Hitch	13' 8" 10' 95" 76" 18" 13" 14" 88 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 915 2,374 lbs. Option 205/75R15C 6 5-4.5 bolt 3" Channel	15' 8" 12' 95" 76" 18" 13" 14" 110 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 992 2,297 lbs. Option 205/75R15C 6 5-4.5 bolt 3" Channel	17' 8" 14' 95" 76" 18" 13" 14" 132 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 1080 2,209 lbs. Option 205/75R15C 6 5-4.5 bolt 3" Channel	13' 8" 10' 101" 82" 18" 13" 14" 95 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 948 2,341 lbs. Option 205/75R15C 6 5-4.5 bolt 3" Channel	15' 8" 12' 101" 82" 18" 13" 14" 117 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 1036 2,253 lbs. Option 205/75R15C 6 5-4.5 bolt 3" Channel	17' 8" 14' 101" 82" 18" 13" 14" 139 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 1102 2,187 lbs. Option 205/75R15C 6 5-4.5 bolt 3" Channel
Overall Length Deck Length Overall Width Between Fenders Deck Height Wall Height Hitch Height (Empty) Ball Size Axle GAWR GVWR Curb Weight Payload Capacity Brakes Tires Ply Bolt Pattern Hitch Crossmembers	13' 8" 10' 95" 76" 18" 13" 14" 88 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 915 2,374 lbs. Option 205/75R15C 6 5-4.5 bolt 3" Channel 2" x 2" Angle	15' 8" 12' 95" 76" 18" 13" 14" 110 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 992 2,297 lbs. Option 205/75R15C 6 5-4.5 bolt 3" Channel 2" x 2" Angle	17' 8" 14' 95" 76" 18" 13" 14" 132 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 1080 2,209 lbs. Option 205/75R15C 6 5-4.5 bolt 3" Channel 2" x 2" Angle	13' 8" 10' 101" 82" 18" 13" 14" 95 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 948 2,341 lbs. Option 205/75R15C 6 5-4.5 bolt 3" Channel 2" x 2" Angle	15' 8" 12' 101" 82" 18" 13" 14" 117 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 1036 2,253 lbs. Option 205/75R15C 6 5-4.5 bolt 3" Channel 2" x 2" Angle	17' 8" 14' 101" 82" 18" 13" 14" 139 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 1102 2,187 lbs. Option 205/75R15C 6 5-4.5 bolt 3" Channel 2" x 2" Angle
Overall Length Deck Length Overall Width Between Fenders Deck Height Wall Height Hitch Height (Empty) Ball Size Axle GAWR GVWR Curb Weight Payload Capacity Brakes Tires Ply Bolt Pattern Hitch Crossmembers Crossmembers spacing	13' 8" 10' 95" 76" 18" 13" 14" 88 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 915 2,374 lbs. Option 205/75R15C 6 5-4.5 bolt 3" Channel 2" x 2" Angle 24"	15' 8" 12' 95" 76" 18" 13" 14" 110 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 992 2,297 lbs. Option 205/75R15C 6 5-4.5 bolt 3" Channel 2" x 2" Angle 24"	17' 8" 14' 95" 76" 18" 13" 14" 132 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 1080 2,209 lbs. Option 205/75R15C 6 5-4.5 bolt 3" Channel 2" x 2" Angle 24"	13' 8" 10' 101" 82" 18" 13" 14" 95 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 948 2,341 lbs. Option 205/75R15C 6 5-4.5 bolt 3" Channel 2" x 2" Angle 24"	15' 8" 12' 101" 82" 18" 13" 14" 117 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 1036 2,253 lbs. Option 205/75R15C 6 5-4.5 bolt 3" Channel 2" x 2" Angle 24"	17' 8" 14' 101" 82" 18" 13" 14" 139 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 1102 2,187 lbs. Option 205/75R15C 6 5-4.5 bolt 3" Channel 2" x 2" Angle 24"
Overall Length Deck Length Overall Width Between Fenders Deck Height Wall Height Hitch Height (Empty) Ball Size Axle GAWR GVWR Curb Weight Payload Capacity Brakes Tires Ply Bolt Pattern Hitch Crossmembers Crossmembers spacing Jack	13' 8" 10' 95" 76" 18" 13" 14" 88 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 915 2,374 lbs. Option 205/75R15C 6 5-4.5 bolt 3" Channel 2" x 2" Angle 24" 2,000 lb. A-frame	15' 8" 12' 95" 76" 18" 13" 14" 110 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 992 2,297 lbs. Option 205/75R15C 6 5-4.5 bolt 3" Channel 2" x 2" Angle 24" 2,000 lb. A-frame	17' 8" 14' 95" 76" 18" 13" 14" 132 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 1080 2,209 lbs. Option 205/75R15C 6 5-4.5 bolt 3" Channel 2" x 2" Angle 24" 2,000 lb. A-frame	13' 8" 10' 101" 82" 18" 13" 14" 95 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 948 2,341 lbs. Option 205/75R15C 6 5-4.5 bolt 3" Channel 2" x 2" Angle 24" 2,000 lb. A-frame	15' 8" 12' 101" 82" 18" 13" 14" 117 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 1036 2,253 lbs. Option 205/75R15C 6 5-4.5 bolt 3" Channel 2" x 2" Angle 24" 2,000 lb. A-frame	17' 8" 14' 101" 82" 18" 13" 14" 139 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 1102 2,187 lbs. Option 205/75R15C 6 5-4.5 bolt 3" Channel 2" x 2" Angle 24" 2,000 lb. A-frame
Overall Length Deck Length Overall Width Between Fenders Deck Height Wall Height Hitch Height (Empty) Ball Size Axle GAWR GVWR Curb Weight Payload Capacity Brakes Tires Ply Bolt Pattern Hitch Crossmembers Crossmembers spacing Jack Electrical Hook-up	13' 8" 10' 95" 76" 18" 13" 14" 88 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 915 2,374 lbs. Option 205/75R15C 6 5-4.5 bolt 3" Channel 2" x 2" Angle 24" 2,000 lb. A-frame RV Plug	15' 8" 12' 95" 76" 18" 13" 14" 110 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 992 2,297 lbs. Option 205/75R15C 6 5-4.5 bolt 3" Channel 2" x 2" Angle 24" 2,000 lb. A-frame RV Plug	17' 8" 14' 95" 76" 18" 13" 14" 132 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 1080 2,209 lbs. Option 205/75R15C 6 5-4.5 bolt 3" Channel 2" x 2" Angle 24" 2,000 lb. A-frame RV Plug	13' 8" 10' 101" 82" 18" 13" 14" 95 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 948 2,341 lbs. Option 205/75R15C 6 5-4.5 bolt 3" Channel 2" x 2" Angle 24" 2,000 lb. A-frame RV Plug	15' 8" 12' 101" 82" 18" 13" 14" 117 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 1036 2,253 lbs. Option 205/75R15C 6 5-4.5 bolt 3" Channel 2" x 2" Angle 24" 2,000 lb. A-frame RV Plug	17' 8" 14' 101" 82" 18" 13" 14" 139 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 1102 2,187 lbs. Option 205/75R15C 6 5-4.5 bolt 3" Channel 2" x 2" Angle 24" 2,000 lb. A-frame RV Plug
Overall Length Deck Length Overall Width Between Fenders Deck Height Wall Height Hitch Height (Empty) Ball Size Axle GAWR GVWR Curb Weight Payload Capacity Brakes Tires Ply Bolt Pattern Hitch Crossmembers Crossmembers spacing Jack	13' 8" 10' 95" 76" 18" 13" 14" 88 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 915 2,374 lbs. Option 205/75R15C 6 5-4.5 bolt 3" Channel 2" x 2" Angle 24" 2,000 lb. A-frame	15' 8" 12' 95" 76" 18" 13" 14" 110 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 992 2,297 lbs. Option 205/75R15C 6 5-4.5 bolt 3" Channel 2" x 2" Angle 24" 2,000 lb. A-frame	17' 8" 14' 95" 76" 18" 13" 14" 132 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 1080 2,209 lbs. Option 205/75R15C 6 5-4.5 bolt 3" Channel 2" x 2" Angle 24" 2,000 lb. A-frame	13' 8" 10' 101" 82" 18" 13" 14" 95 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 948 2,341 lbs. Option 205/75R15C 6 5-4.5 bolt 3" Channel 2" x 2" Angle 24" 2,000 lb. A-frame	15' 8" 12' 101" 82" 18" 13" 14" 117 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 1036 2,253 lbs. Option 205/75R15C 6 5-4.5 bolt 3" Channel 2" x 2" Angle 24" 2,000 lb. A-frame	17' 8" 14' 101" 82" 18" 13" 14" 139 lbs. 2" 3,500 lbs. 3,500 lbs. 2,990 lbs. 1102 2,187 lbs. Option 205/75R15C 6 5-4.5 bolt 3" Channel 2" x 2" Angle 24" 2,000 lb. A-frame

Measurements are approximate and subject to change.

RAINBOW TRAILERS ARE THE BEST CHOICE FOR:

- > EASIER AND STRAIGHTER PULLING
- > DURABILITY AND LONGEVITY
- > SAFETY AND SECURITY

PLUS WE OFFER A 100% CANADIAN WARRANTY



RAINBOW TRAILERS

335 Broadway Street, Box 189 | Cartwright, MB, Canada ROK 0L0 P (204) 529 2581 | F (204) 529 2583 | E info@rainbowtrailers.net

CONTACT YOUR LOCAL RAINBOW TRAILER DEALER FOR MORE INFORMATION