

# WOODS

## BATWING® PRO SERIES ROTARY CUTTERS

15-foot heavy-duty  
flex-wing rotary cutters

### Models

BW180XHD PRO

BW126XHD PRO

For tractors 55-235 hp



Choose a rugged, reliable Woods Batwing® PRO to tame the most unruly waterways, roadsides and pastures. Higher torque capacity, a deep 7-gauge deck, and innovative wing design ensure you'll mow more material in less time.

- High-strength 7-gauge steel deck *New*
- Smooth, sloped design sheds debris
- Cuts brush up to 4 inches in diameter
- Fully baffled deck for even distribution (standard)
- Thirteen-inch deep side frame offers maximum cut capacity *WOODS Exclusive*
- Full-length, 1-inch pin makes the wing hinge more durable
- Quick-Change blade pins for easy maintenance *WOODS Exclusive*
- Dual wheels available on wings and center for extra flotation, smoother cut
- Free link on wing cylinders allows wing movement without wearing cylinder; extends life
- Optional shredding kit for shredding crop residue
- Fully-welded deck rings (optional) for added deck protection
- Limited six-year gearbox warranty *WOODS Exclusive*

### Proven Durability

- Hours of testing in extreme conditions
- Rugged sub-structure
- Industry-leading welding and paint standards

10.5-foot  
single wing  
**BW126XHD PRO**  
is ideal for state, county  
and contract cutting  
of roadsides

# WOODS

# Woods Batwing® PRO Series Rotary Cutters

Specifications	BW180XHD PRO	BW126XHD PRO
Tractor PTO HP Range	55-235 hp	
Side Frame Depth	13"	
Cutting Swath	180" (15-ft.)	126" (10.5 ft.)
Cutting Height	2" – 15"	
Cutting Capacity Diameter	4"	
Hitch Choices	swivel clevis; optional pintel ring	
Transport Width	96"	93"
Overall Width	190"	136"
Overall Length	205"	
Deck Thickness	.179" (7-gauge)	
Side Frame Thickness	.25"	
Weight	4,900 lbs	4,500 lbs
Tongue Weight	1,715 lbs	1,575 lbs
Main Driveline Rating	Cat 6 CV	
Output Shaft Diameter	2.38"	
Splitter/Spindle Gearbox	235 / 205 hp	
Blade Size	.5" x 4"	
Blade Overlap	6"	
Blade Tip Speed 540 RPM	16,000 fpm	
Blade Tip Speed 1,000 RPM	16,000 fpm	
Suspension Choices	single spring on center deck wheel yoke; spring-loaded at each axle arm; walking tandem (center), spring-loaded (wing) axle	
Wheel Choices	15" rims; 21" laminated; 29" used aircraft or foam-filled used aircraft; 25" severe-duty ag or foam-filled ag	
Wing Leveling Adjustment	easy adjust turnbuckle	
Deck Shielding Choices	single or double chain	
Gearbox Warranty (limited)	6-year	
<b>Heavy-duty</b>		

Woods attachments are sold and backed by a network of authorized Woods dealers throughout North America. To find the dealer near you visit [woodsequipment.com](http://woodsequipment.com).



Woods is an approved supplier of the National Joint Powers Alliance®.



To maintain the quality and peak performance of your Woods equipment ask for Woods Genuine Parts.



**WOODS®** | A Blount International Brand

2606 South Illinois Route 2, Oregon, Illinois 61061 tel 800-319-6637 [woodsequipment.com](http://woodsequipment.com)

Warning! Some images may show safety shields removed to provide a better view. Equipment should never be operated with any safety shield removed. Some machines in this brochure may be shown with optional equipment. Always operate machines in accordance with supplied operator's manuals. ©2016 Woods Equipment Company. All rights reserved. WOODS and Woods logo are trademarks of Woods Equipment Company. All other trademarks, trade names, or service marks not owned by Woods Equipment Company that appear in this brochure are the property of their respective companies or mark holders. Specifications subject to change without notice.