

BATWING®

THE LEGACY CONTINUES

WITH A NEW LINE OF BATWING CUTTERS



THE BEST JUST GOT BETTER!

Introducing our most durable Batwing yet!

- More options for hitches and tail wheels allow you to configure the perfect Batwing for your application
- Full length welds on top seams improve paint quality and reduce corrosion from water seepage
- Rigid stump jumper reduces bending and vibration for smoother operation
- Cleaner design ensures your Batwing looks good while performing great

And, the Woods Batwing is still the only fully baffled deck as a standard feature, ensuring better distribution of cut material.

Plus, we continue to bring you higher torque capacities, deeper decks, and our innovative wing design to ensure you'll cut more in less time.



Optional Shredding Kit

An optional shredding kit allows you to shred stalks to better manage crop residue in corn, cotton, milo and specialty crops.

WOODS
Woods Equipment Company

Introducing Six New Batwing® Cutters

Specifications	BW180X / BW126X	BW180XHD / BW126XHD	BW1800X / BW1260X
Tractor PTO Horsepower	45–160 hp	55–235 hp	65–250 hp
Cutting Width	180" / 120"		
Transport Width	96"		
Blade Tip Speed	14,900 at 540 rpm and 15,450 at 1,000 rpm	16,000 at 540 and 1,000 rpm	
Cutting Height	2"–15"		
Cut Capacity	2"	3.5"	4"
Weight	4,245 / 3,920 lbs	4,910 / 4,510 lbs	5,700 / 5,288 lbs
Tongue Weight	1,320 lbs	1,430 / 1,540 lbs	1,970 lbs
Deck Thickness	10 gauge		7 gauge
Side Skirt Thickness	.25"		
Side Skirt Depth	13"		
Blade Carrier	round		
Wing Flex Up / Down	90° / 22°		
Hinge Rod Diameter	1" full length		
Main Driveline Rating	Cat 6 CV or 5 EA		
Wing Driveline Rating	Cat 4	Cat 4 or 5	Cat 5
Splitter Gearbox Horsepower	160 hp	250 hp	
Wing Gearbox Horsepower	120 hp	210 hp	
Output Shaft Diameter	2"	2.375"	
Gearbox Warranty – Limited	6 years	6 years	6 years
	Standard-Duty	Heavy-Duty	Extreme-Duty

Woods Equipment A Blount International Company
 2606 South Illinois Route 2, Oregon, Illinois 61061 tel 800-319-6637 woodsequipment.com

Warning! Some images may show safety shields removed to provide a better view. Equipment should never be operated with any safety shield removed. Some machines in this brochure may be shown with optional equipment. Always operate machines in accordance with supplied operator's manuals. ©2012 Woods Equipment Company. All rights reserved. WOODS, Batwing® and the Woods logo are trademarks of Woods Equipment Company. All other trademarks, trade names, or service marks not owned by Woods Equipment Company that appear in this brochure are the property of their respective companies or mark holders. Specifications subject to change without notice.



B011202 Revised April 2012



Printed in the USA with soy ink on paper using recycled content