

**H&S**

**WIDE BODY  
FORAGE BOXES**



# ALUMINIZED WIDE BODY™ BOX

**Customer  
Farm Name -  
NO CHARGE**

**Available in either  
truck mount, chassis mount,  
or running gear mount**



- Shown with the optional front-to-rear electric roll tarp. An optional forage hood is also available.

Wide Body Aluminized Boxes is available in 18', 20', and 22' lengths.



- A tie down kit is standard on all Wide Body boxes.

• 5" side welded pocket strength also used for return

- All Wide Body Forage Boxes feature **Cross Z-iron**. Cross Z's are welded to the side channels in-line with stakes for added strength.



- The patented hydraulic center mount drive on all Wide Body Boxes provides smooth trouble-free operation.
- Wide Body forage boxes have spring-loaded tighteners on the main apron drive for less stress on the main aprons upon engagement.

**18'-26' MODELS ARE S**

# FIBERGLASS REINFORCED PLYWOOD WIDE BODY™ BOX



- All Wide Body Boxes have **Poly Bond** plywood floors.
- Four formed steel channel supports run lengthwise under the floor for added strength.



Side channels are attached to the stake posts for added strength and are used as a chain slide.

- Side stakes on all Wide Body boxes are 2½" x 2½" tubular steel with a 15½" spacing between them.

- Transport lights are standard on all Wide Body boxes



- Rear latches and center drive.

## DOOR OPTIONS

The H&S Wide Body Box offers a choice of **double barn doors** with air closure or a **top hinged door** with optional air or hydraulic delay system.



Fiberglass reinforced plywood (FRP) side Wide Body boxes are available in 22', 24' and 26' lengths.



**STANDARD WITH THE H&S PATENTED CENTER DRIVE SYSTEM**

# WIDE BODY OPTIONS

**Running Gear or Chassis Mounting is available on most models.**



• An optional **gravity unload grain hopper** for grain is available for wide body boxes with a top hinged gate.



## Wide Body Forage Box Specifications

MODEL -FLOOR/LOAD LENGTH →	18'	20'	22'	24'	26'
INSIDE WIDTH	96"	96"	96"	96"	96"
INSIDE HEIGHT (floor to top of side)	86"	86"	86"	86"	86"
INSIDE LENGTH	18'	20'	22'	24'	26'
OVERALL LENGTH	18'9"	20'9"	22'9"	24'9"	26'9"
OVERALL WIDTH	102"	102"	102"	102"	102"
STANDARD BOX OVERALL HEIGHT	101"	101"	101"	101"	101"
STANDARD BOX CAPACITY STRUCK LEVEL	1011 cu. ft.	1126 cu. ft.	1241 cu. ft.	1355 cu. ft.	1470 cu. ft.
WEIGHT - STANDARD BOX	6300#	6750#	7100#/7350#	7958#	8550#
BOX MATERIAL	ALUMINUM	ALUMINUM	ALUMINUM/POLY BOND	POLY BOND	POLY BOND
MAIN APRON CHAIN	T-ROD IS STANDARD/667XH OR 667X - OPTIONAL		667XH - STANDARD		
MAIN APRON DRIVE	HYDRAULIC DRIVE				
UNLOAD SPEED	UNLOAD TIME IS DEPENDENT ON TRACTOR R.P.M., HYDRAULIC PRESSURE AND G.P.M.				
REAR ENDGATE	AUTOMATIC LOCK AND UNLOCK AN AIR OR HYDRAULIC GATE DELAY IS OPTIONAL				

Warranty: See operators manual for warranty details and limitations. H&S reserves the right to change its products or the description at any time without notice or obligation.

*Buy the BEST* **H&S**  
BUY



Manufactured in U.S.A.



NEED A QR CODE READER?  
DOWNLOAD THE FREE APP  
TO YOUR SMARTPHONE!

Models and specifications are to change without prior notice.

2/17 4M

# H & S MANUFACTURING CO. INC.

2608 S. Hume Avenue  
P.O. Box 768 • Telephone (715) 387-3414  
FAX (715) 384-5463 • Website [www.hsmfgco.com](http://www.hsmfgco.com)  
**MARSHFIELD, WI 54449**



H&S WAREHOUSE 10145 Lakeshore Road  
P.O. Box 1260 • Telephone (716) 736-7595  
FAX (716) 736-7596 • Website [www.hsmfgco.com](http://www.hsmfgco.com)  
**RIPLEY, NY 14775**