

| Model | Style | Suspension | Capacity (Trailer & Load) | Tread Width | Axle Configuration | Heavy Duty Hubs | Max Speed (Depends on Tires) | Frame Design | Bed Width | Stake Spacing | Bed Height | Overall Width w/600/50x22.5 | Overall Length | Bed Length | Hitch and Hitch Supports | Articulating Implement Hitch | Weight- Approx. | Options | Tires | Brakes | Safety Chair |
|--------------|-----------------------------|-------------|---------------------------|-----------------------|--|-------------------------|------------------------------|--------------|-----------|---------------|-------------------|-----------------------------|----------------|------------|--------------------------|--|-----------------------|---------|--|---|--------------|
| XTSS2700+264 | Tandem Suspension Steerable | Leaf Spring | 54,000# | 88 1/2" w/600/50x22.5 | Tandem - steerable 33,000# x 2 - High Speed | 10 Bolt - Grease Filled | 40 mph | 4x8 Tubular | 42" | 33.5" std | 50" w/600/50x22.5 | 110" | 29' 9" | 22' 1/2" | Extra Heavy Duty | Standard- Requires 1.5 or 2" pin Hammerstrap style hitch | 7,960# w/600/50x22.5 | | 600/50x22.5 High Float 700/40x22.5 High Float | Hydraulic Manual Hydraulic Foot Pedal Air | Optional |
| XTSS2700+280 | Tandem Suspension Steerable | Leaf Spring | 54,000# | 88 1/2" w/600/50x22.5 | Tandem - steerable 33,000# x 2 - High Speed | 10 Bolt - Grease Filled | 40 mph | 4x8 Tubular | 42" | 33.5" std | 50" w/600/50x22.5 | 110" | 29' 9" | 22' 1/2" | Extra Heavy Duty | Standard- Requires 1.5 or 2" pin Hammerstrap style hitch | 7,960# w/600/50x22.5 | | 600/50x22.5 High Float 700/40x22.5 High Float | Hydraulic Manual Hydraulic Foot Pedal Air | Optional |
| XTSS4500+315 | Tridem Suspension Steerable | Leaf Spring | 90,000# | 88 1/2" w/600/50x22.5 | Tridem - steerable 33,000# x 3 - High Speed | 10 Bolt - Grease Filled | 40 mph | 4x8 Tubular | 42" | 33.5" std | 50" w/600/50x22.5 | 110" | 34' | 26' 9" | Extra Heavy Duty | Standard- Requires 1.5 or 2" pin Hammerstrap style hitch | 12,660# W/600/50x22.5 | | 600/50x22.5 High Float 700/40x22.5 High Float | Hydraulic Manual Hydraulic Foot Pedal | Optional |
| | | | | | | | | | | | | | | | | | | | | | |
| XTSS4500+390 | Tridem Suspension Steerable | Leaf Spring | 90,000# | 88 1/2" w/600/50x22.5 | Tridem - steerable 33,000# x 3 - High Speed | 10 Bolt - Grease Filled | 40 mph | 4x8 Tubular | 42" | 33.5" std | 50" w/600/50x22.5 | 110" | 40' 3" | 32' 9" | Extra Heavy Duty | Standard- Requires 1.5 or 2" pin Hammerstrap style hitch | 13,100# w/600/50x22.5 | | 600/50x22.5 High Float 700/40x22.5 High Float | Hydraulic Manual Hydraulic Foot Pedal | Optional |