## Farm King

## Offset Disc - 1225 / 1275 / 1375 / 8550

Model	1225		1275	
Blade Spacing	9" (230 mm)	10.5" (267 mm)	10.5" (267 mm)	12" (305 mm)
Width, working	10' to 15' (3 to 4.6 m)	6' to 20' (1.8 to 6.1 m)	6' to 20' (1.8 to 6.1 m)	6' to 20' (1.8 to 6.1 m)
Width, transport	2.5' (762 mm) wider than working width		2.5' (762 mm) wider than working width	
Weight, per foot	603 lb (274 kg)	565 lb (256 kg)	630 lb (286 kg)	651 lb (295 kg)
Weight, per blade	242 lb (110 kg)	266 lb (121 kg)	297 lb (135 kg)	340 lb (154 kg)
Horsepower required*	5 to 6 DBHP/ft	7 to 8 DBHP/ft	7 to 9 DBHP/ft	7 to 9 DBHP/ft
Structure				
Frame	6" x 4" x 3/8" (152 x 102 x 8 mm)	6" x 4" x 3/8" (152 x 102 x 8 mm)	8" x 4" x 3/8" (203 x 102 x 8 mm)	8" x 4" x 3/8" (203 x 102 x 8 mm)
Gang beam size	6" x 4" x 3/8" (152 x 102 x 8 mm)	6" x 4" x 3/8" (152 x 102 x 8 mm)	6" x 4" x 3/8" (152 x 102 x 8 mm)	6" x 4" x 3/8" (152 x 102 x 8 mm)
Hitch, length	92" (2.33 m)	92" (2.33 m)	92" (2.33 m)	92" (2.33 m)
Hanger, opt. stone flex	1.25" x 2.5" (32 x 64 mm)	1.25" x 2.5" (32 x 64 mm)	1.25" x 2.5" (32 x 64 mm)	1.25" x 2.5" (32 x 64 mm)
Gang shaft	1-15/16" (49 mm)	1-15/16" (49 mm)	1-15/16" (49 mm)	1-15/16" (49 mm)
Spools, steel fabricated	5-1/2" (140 mm) Dia. O.D.	5-1/2" (140 mm) Dia. O.D.	5-1/2" (140 mm) Dia. O.D.	5-1/2" (140 mm) Dia. O.D.
Bearings	410 WSS series	410 WSS / T2-215 series	T2-215 series trunnion mounted, regreaseable, 22,800 lb radial load rating	
Gang angle	25°, 22°, 19° F & R	25°, 22°, 19° F & R	25°, 22°, 19° F & R	25°, 22°, 19° F & R
Blades				
Blade sizes, notched/smooth	24" x 5/16" (610 x 8 mm)	24" x 5/16" (610 x 8 mm)	26" x 5/16" (660 x 8 mm)	26" x 5/16" (660 x 8 mm)
Blade sizes, optional, smooth	24" x 5/16" (610 x 8 mm) 26" x 5/16" (660 x 8 mm)	-	-	-
Blade sizes, optional notched/smooth	26" x 5/16" (660 x 8 mm)	26" x 5/16" (660 x 8 mm) 26" x 3/8" (660 x 9 mm) 28" x 3/8" (711 x 9 mm)	26" x 3/8" (660 x 9 mm) 28" x 3/8" (711 x 9 mm) 30" x 3/8" (762 x 9 mm)	26" x 3/8" (660 x 9 mm) 28" x 3/8" (711 x 9 mm) 30" x 3/8" (762 x 9 mm)
Features				
Adjustable rigid scrapers	4" High Carbon Steel	4" High Carbon Steel	4" High Carbon Steel	4" High Carbon Steel
Tires	11L x 15 Fl	11L x 15 FI	11L x 15 Fl	11L x 15 Fl
Depth control	Single 4" x 12" (102 x 305 mm) hydraulic cylinder c/w depth control segments			

\*Depends on working depth, soil type, field speed, etc.

Model	1375		
Blade Spacing	12" (305 mm)		
Width, working	10' to 20' (3 to 6.1 m)		
Width, transport	2.5' (762 mm) wider than working width		
Weight class	750 lb/ft (1,116 kg/m)		
Weight, per blade	361 lb (164 kg)		
Horsepower required*	8 to 9 DBHP/ft		
Structure			
Frame	8" x 4" x 3/8", ballasted (203 x 102 mm)		
Gang beam size	6" x 4" x 3/8" (152 x 102 x 9 mm)		
Hitch, length	92" (2.33 m)		
Hanger, std.	Rigid, U-Bolt Mounted		
Gang shaft	1-15/16" (49 mm)		
Spools, steel fabricated	6-5/8" (159 mm) Dia. O.D.		
Bearings	T2-215 series trunnion mounted, regreaseable, 22,800 lb (10342 kg) radial load rating		
Gang angle	25°, 22°, 19° F & R		
Blades			
Blade sizes, notched	28" x 3/8" (711 x 9 mm)		
Blade sizes, optional, notched/smooth	30" x 3/8" (762 x 9 mm)		
Features			
Adjustable rigid scrapers	4" High Carbon Steel		
Tires	11L x 15 FI		
Depth control	Single 4" x 12" (102 x 305 mm) hydraulic cylinder c/w depth control segments		

\*Depends on working depth, soil type, field speed, etc.

Model	8550		
Blade Spacing	14" (356 mm)		
Width, working	9.5' to 15.5' (2.9 to 4.7 m)		
Width, transport	2.5' (762 mm) wider than working width		
Weight, per foot	1050 lb (476 kg)		
Weight, per blade	636 lb (288 kg)		
Horsepower required*	20 to 25 DBHP/ft		
Structure			
Frame	10" x 4" x 0.5" (254 x 102 x 13 mm)		
Gang beam size	10" x 4" x 0.5" (254 x 102 x 13 mm)		
Hitch, length	92" (2.33 m), floating hitch		
Hanger, standard	Rigid, U-Bolt Mounted		
Gang shaft	1-15/16" (49 mm)		
Spools	Steel fabricated c/w locking drive lug half spools		
Bearings	T2-215 series trunnion mounted, regreaseable, 22,800 lb (10342 kg) radial load rating		
Gang angle	25°, 22° F & R		
Blades			
Blade sizes, notched	32" x 1/2" (813 x 12 mm)		
Features			
Adjustable rigid scrapers	4" x 3/4" (102 x 19 mm) steel		
Tires	12.5 L x 15 Fl		
Depth control	Single 4" x 12" (102 x 305 mm) hydraulic cylinder c/w depth control segments		

\*Depends on working depth, soil type, field speed, etc.