

# BP 660

# SPECIFICATIONS

	Base 660 Bale Pro®	Base 660 Bale Pro® with Feed Chopper™	Base 660 Bale Pro® with Grain Tank	Base 660 Bale Pro® with FC* & GT**
<b>PTO Minimum HP</b>	85 hp (64 kW)	125 hp (94 kW)	100 hp (75 kW)	125 hp (94 kW)
<b>PTO Recommended HP</b>	100 hp (75 kW)	140 hp (105 kW)	125 hp (94 kW)	140 hp (105 kW)
<b>Transport Width</b>	112" (2.84 m)	112" (2.84 m)	141 ½" (3.59 m)	141 ½" (3.59 m)
<b>Transport Height</b>	130 ½" (3.31 m)	130 ½" (3.31 m)	130 ½" (3.31 m)	130 ½" (3.31 m)
<b>Working Height Maximum</b>	152" (3.86 m)	152" (3.86 m)	152" (3.86 m)	152" (3.86 m)
<b>Length to End of Tires</b>	174" (4.42 m)	174" (4.42 m)	174" (4.42 m)	174" (4.42 m)
<b>Length to End of Forks Down</b>	223 ½" (5.68 m)	223 ½" (5.68 m)	223 ½" (5.68 m)	223 ½" (5.68 m)
<b>Discharge***</b>	Right Hand	Right Hand	Right Hand	Right Hand
<b>Weight</b>	5050 lb (2291 kg)	5820 lb (2640 kg)	6090 lb (2762 kg)	6860 lb (3112 kg)
<b>Tongue Weight (Unloaded)</b>	1610 lb (730 kg)	1890 lb (857 kg)	1975 lb (896 kg)	2225 lb (1009 kg)
<b>Hydraulics</b>	3 Remote	3 Remote	3 Remote	3 Remote
<b>Driveline</b>	1000 rpm PTO 1 ¾" 21 Spline	1000 rpm PTO 1 ¾" 21 Spline	1000 rpm PTO 1 ¾" 21 Spline	1000 rpm PTO 1 ¾" 21 Spline
<b>Tires</b>	16.5L x 16.1	16.5L x 16.1	16.5L x 16.1	16.5L x 16.1
<b>Size of Bales</b>	Up to 6' (1.83 m) diameter	Up to 6' (1.83 m) diameter	Up to 6' (1.83 m) diameter	Up to 6' (1.83 m) diameter
<b>Discharge End Curtains, Top and Rear Deflectors</b>	Standard	Standard	Standard	Standard
<b>2 Hydraulic Remote</b>	Option	Option	Option	Option

\* FC - Feed Chopper

\*\* Grain Tank capacity - 45 bushels (1587 L)

\*\*\* Right/left hand is determined by sitting in the tractor seat looking forward.

All weights and transport dimensions are estimates and are subject to change.

While every effort has been made to ensure that the information is accurate/current at the time of production, all specifications are subject to change.

If livestock is being fed, it is the operator's responsibility to ensure that the materials in the processed feed mix are suitable. Some of the wrapping material (twine, net wrap or other materials) may be discharged with the feed if the wrapping materials are not removed prior to processing.

For the latest product information, please visit: [www.highlinemfg.com](http://www.highlinemfg.com).