

BP 661

SPECIFICATIONS

	Base 661 Bale Pro®	Base 661 Bale Pro® with Feed Chopper™	Base 661 Bale Pro® with Grain Tank	Base 661 Bale Pro® with FC* & GT**
PTO Minimum HP	85 hp (64 kW)	125 hp (94 kW)	100 hp (75 kW)	125 hp (94 kW)
PTO Recommended HP	100 hp (75 kW)	140 hp (105 kW)	125 hp (94 kW)	140 hp (105 kW)
Transport Width	112" (2.84 m)	112" (2.84 m)	148 ½" (3.77 m)	148 ½" (3.77 m)
Transport Height	130 ½" (3.31 m)	130 ½" (3.31 m)	130 ½" (3.31 m)	130 ½" (3.31 m)
Working Height Maximum	152" (3.86 m)	152" (3.86 m)	152" (3.86 m)	152" (3.86 m)
Length to End of Tires	181" (4.60 m)	181" (4.60 m)	181" (4.60 m)	181" (4.60 m)
Length to End of Forks Down	230" (5.84 m)	230" (5.84 m)	230" (5.84 m)	230" (5.84 m)
Discharge***	Right Hand	Right Hand	Right Hand	Right Hand
Weight	5685 lb (2579 kg)	6430 lb (2917 kg)	6710 lb (3044 kg)	7465 lb (3386 kg)
Tongue Weight (Unloaded)	1935 lb (878 kg)	2175 lb (987 kg)	2280 lb (1034 kg)	2480 lb (1125 kg)
Hydraulics	3 Remote	3 Remote	3 Remote	3 Remote
Driveline	1000 rpm PTO 1 ¾" 21 Spline	1000 rpm PTO 1 ¾" 21 Spline	1000 rpm PTO 1 ¾" 21 Spline	1000 rpm PTO 1 ¾" 21 Spline
Tires	16.5L x 16.1	16.5L x 16.1	16.5L x 16.1	16.5L x 16.1
Size of Bales	Up to 6' (1.83 m) diameter	Up to 6' (1.83 m) diameter	Up to 6' (1.83 m) diameter	Up to 6' (1.83 m) diameter
Discharge End Curtains, Top and Rear Deflectors	Standard	Standard	Standard	Standard
2 Hydraulic Remote	Option	Option	Option	Option

* FC - Feed Chopper

** Grain Tank capacity - 45 bushels (1587 L)

*** Right/left hand is determined by sitting in the tractor seat looking forward.

All weights and transport dimensions are estimates and are subject to change.

While every effort has been made to ensure that the information is accurate/current at the time of production, all specifications are subject to change.

If livestock is being fed, it is the operator's responsibility to ensure that the materials in the processed feed mix are suitable. Some of the wrapping material (twine, net wrap or other materials) may be discharged with the feed if the wrapping materials are not removed prior to processing.

For the latest product information, please visit: www.highlinemfg.com.