

# TOP GUN® SPECIFICATIONS

<b>PTO Recommended HP</b>	165 hp (124 kW)
<b>Transport Width</b>	108 ½" (2.75 m)
<b>Transport Height</b>	139 ½" (3.54 m)
<b>Working Height Maximum (Forks Extended)</b>	152" (3.86 m)
<b>Length to End of Tires</b>	253" (6.42 m)
<b>Length to End of Forks Down (Extended)</b>	306" (7.77 m)
<b>Weight</b>	7820 lb (3547 kg)
<b>Tongue Weight (Unloaded)</b>	2815 lb (1277 kg)
<b>Discharge</b>	Left/Center/Right
<b>Hydraulics</b>	3 Remote
<b>Driveline</b>	1000 PTO 1 ⅜" 21 Spline with over-running clutch

<b>Tires</b>	16.5L x 16.1
<b>Max. Size of Bales</b>	
<b>Round</b>	6' x 6' (1.83 x 1.83 m)
<b>Square (model dependent)</b>	4' x 3' x 8' (1.2 x 0.9 x 2.4 m)
<b>Top Deflectors</b>	Standard
<b>Rear Deflector</b>	Model Dependent
<b>Rear Facing Lights</b>	Option
<b>1 Remote Joystick</b>	Option
<b>Twine Sickle™</b>	Model Dependent
<b>Hydraulic Aggression Control</b>	Option

All weights and transport dimensions are estimates and are subject to change.

While every effort has been made to ensure that the information is accurate/current at the time of production, all specifications are subject to change.

If livestock is being fed, it is the operator's responsibility to ensure that the materials in the processed feed mix are suitable. Some of the wrapping material (twine, net wrap or other materials) may be discharged with the feed if the wrapping materials are not removed prior to processing.

For the latest product information, please visit: [www.highlinemfg.com](http://www.highlinemfg.com).