

BP 965

SPECIFICATIONS

	Base 965 Bale Pro®	Base 965 Bale Pro® with Feed Chopper™	Base 965 Bale Pro® with Grain Tank	Base 965 Bale Pro® with FC* & GT**
PTO Minimum HP	100 hp (75 kW)	140 hp (105 kW)	100 hp (75 kW)	140 hp (105 kW)
PTO Recommended HP	115 hp (86 kW)	165 hp (122 kW)	125 hp (94 kW)	165 hp (122 kW)
Transport Width	112" (2.84 m)	112" (2.84 m)	141 ½" (3.59 m)	141 ½" (3.59 m)
Transport Height	136" (3.45 m)	136" (3.45 m)	136" (3.45 m)	136" (3.45 m)
Working Height Maximum	189 ½" (4.81 m)	189 ½" (4.81 m)	189 ½" (4.81 m)	189 ½" (4.81 m)
Length to End of Tires	210" (5.33 m)	210" (5.33 m)	210" (5.33 m)	210" (5.33 m)
Length to End of Forks Down	302" (7.67 m)	302" (7.67 m)	302" (7.67 m)	302" (7.67 m)
Discharge***	Right Hand	Right Hand	Right Hand	Right Hand
Hydraulics	3 Remote	3 Remote	3 Remote	3 Remote
Driveline	1000 rpm PTO 1 3/8" 21 Spline	1000 rpm PTO 1 3/8" 21 Spline	1000 rpm PTO 1 3/8" 21 Spline	1000 rpm PTO 1 3/8" 21 Spline
Weight	7375 lb (3345 kg)	8390 lb (3806 kg)	8480 lb (3847 kg)	9495 lb (4307 kg)
Tongue Weight (Unloaded)	2400 lb (1088 kg)	2760 lb (1252 kg)	2715 lb (1232 kg)	3070 lb (1393 kg)
Tires	16.5L x 16.1	16.5L x 16.1	16.5L x 16.1	16.5L x 16.1
Max. Size of Bales				
Round	6' (1.83 m)	6' (1.83 m)	6' (1.83 m)	6' (1.83 m)
Square	4' x 4' x 9' (1.2 x 1.2 x 2.7 m)	4' x 4' x 9' (1.2 x 1.2 x 2.7 m)	4' x 4' x 9' (1.2 x 1.2 x 2.7 m)	4' x 4' x 9' (1.2 x 1.2 x 2.7 m)
Twine Sickle™, Discharge End Curtains, Top and Rear Deflectors	Standard	Standard	Standard	Standard
2 Hydraulic Remote	Option	Option	Option	Option

* FC - Feed Chopper
** Grain Tank capacity - 45 bushels (1587 L)

*** Right/left hand is determined by sitting in the tractor seat looking forward.

All weights and transport dimensions are estimates and are subject to change.

While every effort has been made to ensure that the information is accurate/current at the time of production, all specifications are subject to change.

If livestock is being fed, it is the operator's responsibility to ensure that the materials in the processed feed mix are suitable. Some of the wrapping material (twine, net wrap or other materials) may be discharged with the feed if the wrapping materials are not removed prior to processing.

For the latest product information, please visit: www.highlinemfg.com.