


PRODUCT CATALOGUE





FEB 2025

CONTENTS

Fixed Frame Packer	3
Superflex Packer	4
Superflex-Magnum Series Packer	6
Lawn Rollers	8
Single Gang Drum Rollers	9
Vertical Fold Drum Rollers	10
Municipal Park Roller	11
FW8800 Forestry Winch	12
Liquid Fertilizer Applicator	13
Multi-Purpose Grapple	15
Top Soil Screener	16
Post Drivers	17

Big Jim Products are proudly designed and manufactured in-house for the past 20 years.



5808 Highway 9 Harriston, Ontario N0G 1Z0

Ph: 519-338-2923 • Fax: 519-338-2756

sales@harcoag.ca



FIXED FRAME PACKER



Match tillage or planting equipment with adjustable frame width ranging 9' to 15', and rigid frame on 3' to 6' and 16' models. Big Jim Packers are available in Red, Green, Blue & Orange frame colours. They are available in a colour of your choice to match the other equipment on your farm. Big Jim wheels are designed with heavy hubs and spokes, up to 12% heavier than competitive units.

1 ³/₄" grade C1045 cold rolled gang shafts, greasable flangette style bearings and heavy-duty ductile iron end clamps.

Wheel Options:

- 15" Smooth/Sprocket combination, Ductile Iron suited for clay based soils.
- 18" Smooth/Sprocket combination, Ductile Iron suited for clay based soils.
- 19" Notched wheel, Ductile Iron suited for loamier soils.
- 20" Crow Foot, Ductile Iron suited for sandy soils.

Ductile wheels carry a 3-year limited warranty.

The Optional Transport Package is available in single or dual wheel versions and include:

- Complete hydraulic package with 3000 PSI Cylinders
- DOT tagged safety chain
- 5000 lb tongue jack
- 4000 lb hub assemblies
- 15" rims



Tongue Jack Safety Chain



Cylinder Lock



Shown with Dual Wheel Transport Kit



Made in Canada Fabrique au Canada

Sold & serviced by:

Distributed in Canada by:

Harco Ag Equipment Harriston, Ontario

Ph: 519-338-2923 • Fax: 519-338-2756

Email: sales@harcoag.ca



SUPERFLEX PACKER





Flex packers are available in a 3-section configuration for widths of 21' to 32' (shown on left). Packers 33' to 50' are built on a 5-section frame (shown right). The balanced frame design minimizes tongue weight.

Each wing gang is independently suspended in the middle allowing **MAXIMUM FLEXIBILITY** on contoured ground. This feature also assures even weight distribution.



Standard Equipment:

- Complete hydraulic package 3000 PSI Cylinders
- Forged Adjustable Pintle/Clevis Hitch
- 7000lb drop leg tongue jack
- DOT tagged safety chains
- Tail and turn signal light package
- Dual 11L-15 8-ply tires 21-40 ft 12 ply on 41-50ft models
- Greasable flange style bearings
- Main frame material 6" x 6" x 1/4" wall tube
- Wing material 6" x 4" x ¼" wall tube
- Pivot pins and gang shafts 1 ¾" C.R. (C1045)

Big Jim Flex Wing packers are available with 18" Smooth / Sprocket combination Ductile, 19" notched Ductile or 20" Crowfoot Ductile Wheels. Ductile Wheels carry a 3-year limited warranty.

Available in Red, Green, Blue & Orange frame colours.

Working	Transport	Transport	Overall	Approximate Weight (lbs)		
Width	Width	Height	Length	18"	19"	20"
21'	12'-8"	10'	212"	6624	5994	5150
22'	12'-8"	10'-6"	212"	6772	6202	5289
23'	12'-8"	11'	212"	7020	6330	5427
24'	12'-8"	11'-6"	212"	7168	6538	5565
25'	12'-8"	12'	212"	7416	6666	5703
26'	12'-8"	12'-6"	272"	7776	6874	6043
27'	12'-8"	13'	272"	8024	7002	6181
28'	14'-8"	12'-6"	272"	8172	7210	6319
29'	14'-8"	13'	272"	8420	7338	6457
30'	16'-8"	12'-6"	272"	8648	7626	6675
31'	16'-8"	13'	272"	8896	7754	6813
32'	16'-8"	13'-6"	272"	9044	7962	6951
33'	14'-8"	10'-9"	272"	9544	8564	7614
34'	14'-8"	10'-9"	272"	9692	8772	7752
35'	14'-8"	11'-3"	320"	9940	8900	7890
36'	14'-8"	11'-3"	320"	10188	9108	8028
37'	14'-8"	11'-9"	320"	10336	9236	8166
38'	14'-8"	11'-9"	320"	10584	9444	8304
39'	14'-8"	12'-3"	320"	10732	9572	8442
40'	14'-8"	12'-3"	320"	10980	9780	8580
42'	14'-8"	12'-9"	320"	11270	10040	8740
45'	16'-8"	13'-3"	392"	See Magnum Series 9470		9020
48'	16'-8"	13'-9"	392"			9470
50'	16'-8"	14'-3"	392"			9770





Distributed in Canada by:

Harco Ag Equipment Harriston, Ontario

Ph: 519-338-2923 • Fax: 519-338-2756

Email: sales@harcoag.ca

www.harcoag.ca





SUPERFLEX MAGNUM SERIES PACKER



The Superflex concept has proven to be the most revolutionary design in packers for years. The independent floating design lets each section follow the contour of the soil giving more effective wheel to soil contact. The design also allows each section to independently float over obstacles such as stones without placing excessive weight on the gang causing wheel, shaft or bearing damage.

Construction of the "Magnum Series" allows us to produce 40 to 50 foot packers with 19" wheels and scrapers and still maintain sufficient capacity to incorporate heavier larger diameter wheels in the future should the demand arise.

Standard Features:

- Forged Pintle / Clevis Adjustable Hitch
- 7000lb Tongue Jack
- Grade 70 20,000 lb 3/8" DOT approved for agricultural use safety chains x 2
- Tandem 4" x 24" Inner Wing Cylinders
- Tandem 3 ½" x 24" Outer Wing Cylinders
- 2 LED Road Light Boxes
- 14/7 Heavy Jacket Wiring
- 7 Pin Aluminum Light Plug
- Reflective Tape

Options

- 18" Ductile Smooth Sprocket Combination Wheel
- 19" Ductile Notched Wheel
- Scrapers for 19" Notched Wheels
- 20" Ductile Crowfoot Wheels

Ductile Wheels carry a 3 year limited warranty.



All plumbing neatly arranged and tied in place



Rugged 1 ¾" hinge pins, securely fastened



3 beam outerwing section w/ two cylinders, each packer gang oscillates on centre pin and plastic wear plates



Adjustable clevis hitch, safety chains, 7000 lb tongue jack, steel hydraulic lines



5 bearing main frame section, lights & reflectors standard



Rugged 4 beam main with section with two cylinders

15' (50' Model)

SpecificationsTransport Height

Transport reight	13 (30 Model)
Transport Width	16' 8" (all)
Total Weight (46' w/ 19" Wheels)	15058 Ìbs
Drawbar Weight (Transport Position)	1100 lbs (46' Model)
Tongue Material	7" x 5" x 3/8" Wall
Tongue Brace Material	3" x 3" x ¼" Wall
Main Frame Material	6" x 6" x 3/8" Wall
Inner Wing Front Tubes (2)	6" x 4" x 3/8" Wall
Inner Wing Rear Tubes (2)	6" x 4" x ¼" Wall
Outer Wing Tubes	6" x 4" x ¼" Wall
Wheel Gang Tubes	6" x 4" x ¼" Wall
Pivot Pins and Gang Shafts	1 ¾" C.R. (C1045)
Tires (4)	11L-15 12-Ply
Wheels (4)	6 Bolt Solid Centre
Hubs (4)	6 Bolt 5000 lb
Gang Shaft Bearings	1 ¾" NTN Triple Seal
Hydraulic Cylinders	3000 PSI (CDN Made)
Hydraulic Connections	JIC and ORB

Distributed in Canada by:

Harco Ag Equipment Harriston, Ontario

Ph: 519-338-2923 • Fax: 519-338-2756

Email: sales@harcoag.ca

www.harcoag.ca

1

Made in Canada Fabrique au Canada



LAWN ROLLERS

The new Big Jim lawn roller is a natural extension of the field roller currently manufactured in Harriston, Ontario! The same ruggedness is built right in.

The roller is offered in 4', 5' and 6' sizes. They are a heavy-duty design. An Extra Heavy-Duty version is available with sizes up to 8'.

The dry weight of these rollers is serious!



	Heavy Duty
4'	606 lbs
5'	733 lbs
6'	864 lbs
7'	
8'	

720 lbs 857 lbs 998 lbs 1135 lbs 1272 lbs

Additional weight can be achieved by filling the drum with water. This will add up to **290** lbs per foot.



The drum is made from tubular steel 30" in diameter and 3/8" thick. The end plates are 10-gauge steel with 1" bearing on the standard roller. The Extra Heavy-Duty version uses ½" steel with 1 ¾" pillow block bearings.



The Extra Heavy-Duty frame is made of 2" square tubing that is 3/16" thick. It has mitered corners and surrounds the drum for added strength.

The drum is painted black, and the frame is available in a variety of colours to match your tractor.



A standard hitch clevis is used.



Made in Canada Fabrique au Canada

Distributed in Canada by:

Harco Ag Equipment Harriston, Ontario

Ph: 519-338-2923 • Fax: 519-338-2756

Email: sales@harcoag.ca

www.harcoag.ca

8



SINGLE GANG DRUM ROLLERS









Single Gang Features:

- 30" Diameter x 3/8" Wall Drum
- 4" x 3" x 3/16" Wall Tongue
- 4" x 4" x 1/4" Wall Main Frame
- ½" Thick Inner End Plates
- 3/8" Thick Outer End Plates
- 1 ¾" Drum Shafts
- 1 ¾" Greasable Bearings
- Drum Scrapers
- Models from 9'-6" to 16'-6"

*Available in Red, Green, Blue & Orange Frames

Distributed in Canada by:

Harco Ag Equipment Harriston, Ontario


Ph: 519-338-2923 • Fax: 519-338-2756

Email: sales@harcoag.ca

www.harcoag.ca

Single or Dual Transport Kits Include:

- 5000 lb Tongue Jack
- Complete Hydraulic Package
- 3000 PSI Hydraulic Cylinders
- 11,000 lb Safety Chain
- Rims
- Tires Optional





VERTICAL FOLD DRUM ROLLERS









Standard Features:

- 30" Diameter x 3/8" Wall Drum
- 3/8" Thick Inner End Plates
- ½" Thick Outer End Plates
- 2-7/16" Drum Shafts
- 2-7/17" Greaseable Ductile Pillow Block Bearings
- 6" x 6" x ½" Wall Main Frame
- 6" x 4" x 3/8" Wall Tongue
- 6" x 4" x 1/4" Wall Wing Frames
- Height Adjustable Pintle / Clevis Hitch
- 7000 lb Drop Leg Tongue Jack
- Double Safety Chains 21000 lbs each
- Dual Wheels w/ 11L-15 8-Ply Tubed Tires
- 3000 PSI Hydraulic Cylinders
- Drum Scrapers
- Implement Safety Lights & Reflectors
- Balanced Frame Design for minimum torque weight
- Models from 20'-6" to 34'-6"

Available in Red, Green, Blue & Orange Frames





MUNICIPAL PARK ROLLERS



Approximate Weights (7' Model)

Roller (Dry) 1637 lbs Light Package 20 lbs Single Wheel Transport Kit 390 lbs Dual Wheel Transport Kit 470 lbs

Standard Features

- 4" x 4" x ½" Wall Main Frame
- 4" x 3" x ¼" Wall x 6' Long Tongue
- Non-adjustable Clevis Style Hitch
- Reflective Safety Tape on Outer Front and Rear Corners

Options

 4 Lamp Stop/Turn Tail Light Package with 7-pin Round Plug (Agricultural Wire Schematic)

30" x 3/8" Wall Roller Tube

1/4" Thick Roller End Plates

1 3/4" Roller Centre Shaft

1 3/4" Greaseable Bearings Ballast Fill and Vent Plugs

Adjustable Drum Scraper

- Various Tire Options
- Swivel Clevis Hitch

Single or Dual Wheel Transport Kits Include:

- DOT approved 11,000 lb Safety Chain
- Tongue Jack
- Hydraulic Cylinders
- Hoses & Quick Couplers
- Cylinder Transport Locks
- 4000 lb Hubs and Spindles
- 15" x 6 Bolt Agricultural Wheels
- SMV Sign



Sold & serviced by:

Distributed in Canada by:

Harco Ag Equipment Harriston, Ontario

Ph: 519-338-2923 • Fax: 519-338-2756

Email: sales@harcoag.ca



FW8800 FORESTRY WINCH



Features:

- 1 ½" Diameter Drum Shaft
- Single Nut Clutch Adjustment
- 7/16" Diameter Cable
- Upper Support on top pulley allows easier pulley swivel
- Removable front shaft support
- Single upper and lower safety shields allow quick and easy access to complete drive
- #50 Chain Drive
- Adjustable Idler Sprocket
- #4 PTO Shaft

- 3/8" Thick Blade with Chain Slots
- 8800 lb Pulling Force (at first wrap of drum)
- Upper Pulley Bearings Sealed One Side and Greaseable
- Lower Pulley has Greaseable Bushing
- Twin Storage Stands
- 40 to 80 HP Tractor Range
- Choker Chain Storage Boxes on Both Sides
- Optional Safety Screen



Sold & serviced by:

Distributed in Canada by:

Harco Ag Equipment Harriston, Ontario

Ph: 519-338-2923 • Fax: 519-338-2756

Email: sales@harcoag.ca



LIQUID FERTILIZER APPLICATOR





Features:

- Tubular Steel Frame Construction
- Convertible Hitch Clevis
- Transverse Mounted Tank
- LED Implement Lights
- Tire-to-Tire Pump Drive
- 2" Bottom Fill Plumbing
- Rockshaft Lift System
- Safety Chain
- 12/4 x 24 Tires
- Blu-Jet® Coulters
- John Blue Piston Pump
- 300 or 500 Gallon Tank Capacity
- Knife or Stream Injection
- Fixed 60" or 90" Axles
- Adjustable Axle or 60"-90"



To build a Big Jim Liquid Fertilizer Applicator, Select One Item from Each Section:

Section 1	
Model	Description
BJLA00100	Base Unit

Section 2	
Model	Description
BJLA00105	300 Gallon Tank
BJLA00106	500 Gallon Tank

Section 3			
Model	Description		
BJLA00102	60" Fixed Axle		
BJLA00104	80" Fixed Axle		
BJLA00111	90" Fixed Axle		
BJLA00103	60"-90" Adjustable Axle		

Section 4	
Model	Description
BJLA00107	5R30 Fixed Tool Bar
BJLA00110	7R30 Fixed Tool Bar
BJLA00108	5R30 Folding Tool Bar
BJLA00109	7R30 Folding Tool Bar

For Different Row Spacing Configurations contact Harco Ag

Section 5	
Model	Description
LA0134	Coulter / Stream Injection
LA0133	Coulter / Knife Injection

Section 6	
Model	Description
BJLA00101	Single Piston Pump, Drive, Plumbing
BJLA00112	Double Piston Pump, Drive, Plumbing

Distributed in Canada by:

Harco Ag Equipment Harriston, Ontario

Ph: 519-338-2923 • Fax: 519-338-2756

Email: sales@harcoag.ca

www.harcoag.ca





Big im MULTIPURPOSE GRAPPLE



Quick Change Claw Options:





- Brush Raking or Piling
- Log lifting, Piling or Loading
- Orchard Pruning, etc.
- Round and Square Bale Grabbing
- Moving Loose Hay and Straw
- Moving Scrap Metal and **Tires**
- Bind and Dirt-Free Trimming and Blocking of Tree Tops

The Big Jim Multipurpose Grapple is available with Frey, Alo and Skid Steer quick attach brackets and universal pin brackets (1" diameter pin). The Grapple consists of 3/4" thick x 5" deep teeth. Teeth are tied together with 1 3/4" and 1" diameter round bar and reinforced with 4" x 2" x 1/4" wall tubing on back side of grapple. Teeth are spaced 12" centres to allow dirt to pass through, but still pick up branches, roots, and many other objects. Several different claw options are available to suit the customers' specific requirements.



Logs & Slabs



Bales



Scrap



Brush

Made in Canada Fabrique au Canada

Sold & serviced by:

Distributed in Canada by:

Harco Ag Equipment Harriston, Ontario

Ph: 519-338-2923 • Fax: 519-338-2756

Email: sales@harcoag.ca



TOP SOIL SCREENER



Dimensions:

- > Depth 5 foot (6' 4" with loading forks.)
- ➤ Height to top of screen approximately 6' (varies with spring adjustments.)
- ➤ Width 9' inside, approximately 9' 7" outside.
- Mound height of screened material approximately 4'.
- ➤ Back wall of screener is 39"
- > Option: 16" flat belt skirt on screener discharge.



Fast, convenient moving, insert loader bucket into twin forks on discharge side. Also twin loops for chain lifting at approximate balance point.

Oli vibrator 110V standard, purchaser to complete electrical wiring for their requirements and local codes. Can be operated with 110 extension cord, generator or inverter.





Vibrator frame and tension springs mounted in rubber blocks. Tension springs have six adjustments to set angle of screen and tension on the screen assembly.

Screen hinge pins mounted in rubber blocks, use of isolating rubber mounts reduces vibration loss through mainframe keeping as much vibration on the screen area as possible.





Screen with $\frac{3}{4}$ " openings has two center flat bar hold-downs and two angle iron hold-downs on each side to prevent run-off. Screenings drop into ample holding area approximately 9 feet wide x 4 feet high for easy access with buckets up to 8 feet wide.

Distributed in Canada by: Harco Ag Equipment Harriston, Ontario

Ph: 519-338-2923 • Fax: 519-338-2756

Email: sales@harcoag.ca

www.harcoag.ca







Proudly Made in Canada

Features & Benefits

- The Mast tilts in and out and forward and back for post leveling on uneven ground
- The Mast travels out 16 inches and the tongue travels out 24 inches. This enables the operator to accurately place posts without moving the entire machine.
- The Mast lifts hydraulically 24 inches. This allows a fast change from 8 to 10 foot posts. This feature also allows a longer hammer stroke for starting 8 foot posts.
- The Hammer and Mast in fully raised position reaches a height of 11' 6" from the hammer to the ground.
- The BJ740-T and BJ740-T Plus model can be ordered with an optional round/square combination hugger. Both the round and square hugger are made of steel. The hugger swings out of the way for working on existing fence lines.

All Big Jim Post Drivers come with built in safety features to prevent injury in the event of a sudden hydraulic failure.
All units come complete with a DOT approved safety chain on tongue.



Specifications

pecinications		T	T
Model	BJ740- 3PH/SS	BJ740-T	BJ740-T PLUS
Hammer Weight	740 lbs.	740 lbs.	740 lbs.
Counter Weight	N/A	979 lbs.	1,306 lbs.
Total Weight	1,697 lbs.	3,748 lbs.	4,440 lbs.
Hammer Maximum Height Lower Mount	9' 6"	9' 6"	9' 6" – 11' 6"
Hammer Maximum Height Upper Mount	11' 6"	11' 6"	11' 6" – 13' 6"
Hammer Minimum Height Lower Mount	4' 2"	4' 2"	4' 2" - 6' 2"
Hammer Minimum Height Upper Mount	6' 2"	6' 2"	6' 2" – 8' 2"
Hammer Stroke	64"	64"	64"
Overall Width	42"	96"	100"
Overall Length	48"	118"	118"
Transport Height	100"	100"	104"
Mast Tilt Forward/Backward	18°	18°	18°
Mass Tilt In/Out	12°	12°	12°
Mast Vertical Lift	N/A	N/A	24"
Mast Horizontal Travel	N/A	16"	16"
Tongue Travel	N/A	16"	24"
Tires	N/A	9.5L-15 8PR	9.5L-15 8PR
Wheels	N/A	6 Bolt Ag	6 Bolt Ag
Spindles and Hubs	N/A	5000 lb.	5000 lb.
Reservoir	N/A	15 Gallon	15 Gallon
Drive System	N/A	13HP Honda	13HP Honda
Frame	6" x 3" 1/4"	6" x 3" 1/4"	6" x 3" x ¼"
Max Post Hugger Diameter	8"	8"	8"

Distributed in Canada by:

Harco Ag Equipment Harriston, Ontario

Ph: 519-338-2923 • Fax: 519-338-2756

Email: sales@harcoag.ca

www.harcoag.ca