

RCH 415

SPECIFICATIONS

Cutting Swath	180" (4.57 m)
Cutting Capacity	3 1/2" (89 mm)
Cutting Height	2" to 15" (51 mm to 381 mm)
Overall Width (to outside of wings lowered)	196" (4.98 m)
Overall Length	392" (10 m)
Transport Width	120" (3.05 m)
Weight	9735 lb (4416 kg)
Blade Size	1/2" x 4" (13 mm x 102 mm)
Wing Working Range	25° Down, 55° Up
Double Safety Chains All Round	Standard
Minimum Recommended HP	140 hp (104 kW)

Deck Thickness	3/16" High Impact Resistant
Blade Tip Speed	15250 FPM (4650 mpm)
Standard Front Tires	32 x 11.5 x 15 22 Ply
Rear Tires (Wing)	27 x 10.5, 15" Skid Steer (Standard)
Rear Tires (Center)	27 x 10.5, 15" Skid Steer (Standard)
Hydraulic Fluid	AW68
Oil Capacity	20 Imp Gal (94 L)
Deck to Blade Clearance	11" (279 mm)
Tongue Weight	1275 lb (578 kg)
Driveline	Cat 4 1000 PTO -1 3/8" 21 Spine

While every effort has been made to ensure that the information is accurate/current at the time of production, all specifications are subject to change.

For the latest product information, please visit:
www.highlinemfg.com.