

# RR 4300

# SPECIFICATIONS

Raking Width (at 20 degrees working position)	160" (4.07 m)
Rotor Length	171" (4.34 m)
Rake Angle	10 degrees minimum 30 degrees maximum
Max. Rotor rpm	154
Transport Width	97" (2.48 m)
Working Width - 20 degrees	160" (4.06 m)
Transport Length	239" (6.07 m)
Operating Length - 20 degrees	252" (6.42 m)
Height	72" (1.84 m)
Weight	3990 lb (1810 kg)
Tongue Weight	Transport - 1256 lb (570 kg) Working - 1036 lb (470 kg)
Tire Size	11L - 15F

Tire Pressure (max.)	60 psi (413.7 kPa)
Hydraulic Drive	Yes
Minimum Horsepower	65 hp (49 kW)
Maximum Horsepower	75 hp (56 kW)
Hydraulic Outlets Required	3
Hydraulic Pressure (max. relieved)	3000 psi (20,684 kPa)
Hydraulic Flow Required	20 gpm (76 l/min)
Hydraulic Hitch	Yes
Hydraulic Drive	Yes
Raking Style	Rotor
Number of Replaceable Teeth	100
Replaceable and Reversible Teeth	Yes
Hard Surfacing	Rotor Teeth

Note: Right/left hand is determined by sitting in the tractor seat looking forward

While every effort has been made to ensure that the information is accurate/current at the time of production, all specifications are subject to change.

For the latest product information, please visit: [www.highlinemfg.com](http://www.highlinemfg.com).