

ROTO GRIND

BY

BURROWS ENTERPRISES LLC.
 2024, EAST 8th STREET
 GREELEY, COLORADO 80631
 (970) 353-3769 - PHONE
 (970) 353-0839 - FAX

Web Page: www.rotogrind.com
 E-Mail: sales@rotogrind.com

MODEL 760

ROTO GRIND SPECIFICATIONS

GRINDER WEIGHT	3500 pounds.	MILL	Six sets of hammers with 18 standard hammers and 6 hard surfaced lead hammers, 13 inches long with 11-inch swing. Reversible, can be used on all four corners. 1000 R.P.M. required (Option) Six special alfalfa hammers (38 lbs. ea.) To be run at 540 R.P.M. (can be used in combination with standard hammers, for certain conditions.)
HITCH WEIGHT	660 pounds.	SHEAR	5 adjustable shear plates to control the fineness of grind. Individually adjustable from 0 to 2 1/2 Inches of movement per shear plate.
HEIGHT	8 feet, 6 inches -Standard 7 feet, 6 inches -Low Profile	CAPACITY	Depends on the type of material, condition of material (wet or dry), how fine it is being ground, and the size of the tractor, e.g. 80 to 90 horsepower on reasonably dry material should produce 15 tons per hour. H.P. Range from 70 to 200. Because of the variables, capacity can vary from 5 to 45 tons per hour.
TUB DIMENSIONS	9 feet at the top of the tub 8 feet at the bottom of the tub. 51 inches deep. Low Profile tub is 39 inches deep.		
TUB SPEED	0 to 9 R.P.M., depending on tractor hydraulic volume.		
TUB GOVERNOR	To stop tub if the tractor R.P.M. pulls down. Standard equipment. Works only in the clockwise rotation of the tub.		

MODEL 1090

ROTO GRIND SPECIFICATIONS

GRINDER WEIGHT	4000 pounds.	MILL	Six sets of hammers with 24 standard hammers and 12 hard surfaced lead hammers, Reversible, can be used on all four corners. 1000 R.P.M. required. Total of 36 Hammers.
HITCH WEIGHT	710 pounds.	SHEAR	5 adjustable shear plates to control the fineness of grind. Individually adjustable from 0 to 2 1/2 Inches of movement per shear plate.
HEIGHT	8 feet, 6 inches -Standard tub	CAPACITY	Depends on the type of material, condition of material (wet or dry), how fine it is being ground, and the size of the tractor, e.g. 150 to 200 horsepower on reasonably dry material should produce 35 tons per hour. Because of the variables, capacity can vary from 20 to 60 tons per hour.
TUB DIMENSIONS	9 feet at the top of the tub 7-1/2 feet at the bottom of the tub. 51 inches deep.		
TUB SPEED	0 to 9 R.P.M., depending on tractor hydraulic volume.		
TUB GOVERNOR	To stop tub if the tractor R.P.M. pulls down. Standard equipment. Works only in the clockwise rotation of the tub.		

ROTO GRIND



Model 760 Standard



Model 1090 Standard

**THE
 MOST
 VERSATILE
 TUB
 GRINDER
 ON THE
 MARKET!!**