# COMMANDER MAX DPS 1000R

## **HIGHLIGHTS**

PERFORMANCE	Proven Rotax engine
	Dependable drivetrain
	<ul> <li>Sport segment-worthy suspension</li> </ul>
WORKABILITY	Rugged taskmaster
	<ul> <li>Work-oriented functionality</li> </ul>
	<ul> <li>Vehicle protection and rigidity</li> </ul>
DESIGN &	Interior focused on comfort
ERGONOMICS	<ul> <li>Superior fit and finish</li> </ul>
	<ul> <li>Low cost of ownership</li> </ul>
PLATFORM	■ 120.6 in. wheelbase
FEATURES	<ul> <li>12.5 in. ground clearance</li> </ul>
	<ul> <li>Up to 13 in. suspension travel</li> </ul>
	<ul><li>2,000 lb towing capacity</li></ul>
	<ul> <li>Dynamic Power Steering (DPS™)</li> </ul>
	<ul> <li>Visco-Lok<sup>†</sup> QE front differential</li> </ul>
	<ul> <li>SPORT/ECO™ modes</li> </ul>
	<ul> <li>D.E.S.S. key with Start/Stop button</li> </ul>
	<ul> <li>4.5 in. digital display</li> </ul>
	<ul> <li>Premium half doors</li> </ul>
	<ul> <li>Mudguards</li> </ul>
	<ul> <li>Rear differential with Turf mode</li> </ul>

ENGINE	1000R
Туре	100 hp, Rotax® 976 cc, V-twin, liquid-cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System (QRS) CVT with high-airflow ventilation and Electronic Drive Belt Protection Extra-L/H/N/R/P
Drive Train	Selectable Turf Mode/2WD/4WD with Visco-Lok† QE auto-locking front differential
Driving Assistance	Electronic Hill Descent Control SPORT/ECO™ modes
Power Steering	Dynamic Power Steering (DPS)

# SUSPENSIONS

Front Suspension	Double A-arm with sway bar/12.5 in. (31.8 cm) travel
Front Shocks	Twin-tube gas-charged shocks
Rear Suspension	TTA with sway bar/13 in. (33 cm) travel
Rear Shocks	Twin-tube gas-charged shocks

## **TIRES & WHEELS**

Front Tires	XPS Trail Force 27 x 9 x 14 in.
Rear Tires	XPS Trail Force 27 x 11 x 14 in.
Wheels	14 in. steel

# BRAKES

Front	Dual 220 mm disc brakes with hydraulic twin-piston calipers
Rear	Dual 220 mm disc brakes with hydraulic twin-piston calipers



Tundra Green / 1000R

#### **DIMENSIONS & CAPACITIES**

DIVILIVOIONO & CALAC	JIIIE3
Estimated Dry Weight	1,855 lb (841.4 kg)
Chassis/Cage	Profiled cage ROPS approved
LxWxH	158.3 x 62 x 73 in. (402.2 x 157.5 x 185.8 cm)
Wheelbase	120.6 in. (306.3 cm)
Ground Clearance	12.5 in. (31.8 cm)
Cargo Box Dimensions	29.5 x 45.2 x 10.6 in. (75.1 x 114.7 x 27 cm)
Cargo Box Capacity	600 lb (272.2 kg)
Towing Capacity	2,000 lb (907.2 kg)
Payload Capacity	1,280 lb (580.6 kg)
Storage Capacity	Total: 8.5 gal (32.1 L) Glove box: 4.1 gal (15.6 L) Driver storage: 0.4 gal (1.5 L) Center console and cup holders: 0.8 gal (3.1 L) Rear console and cup holders: 1.2 gal (4.5 L) Side cargo box storage (passenger side): 1.6 gal (5.9 L) Dual side panel storage: 0.8 gal (3.0 L)
Fuel Capacity	10 gal (38 L)

# FEATURES

Gauge	4.5 in. wide digital display:  Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT/ECO™ mode, seat belt and 4 x 4 indicator, rear diff lock indicators, diagnostics,
Instrumentation	clock, battery voltage, engine temperature  Lighter-type DC outlet in console (10 A)
Anti-Theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
Magneto	650 W
Lighting	Two 55 W reflectors headlights (low/high) and LED tail lights
Winch	
Steering Wheel	Adjustable tilt steering
Protection	Premium half doors Full skid plate Mudguards
Hitch Type	2 in. hitch receiver

### **WARRANTY & EXTENDED SERVICE**

Factory Warranty	6-month BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 30 months

