

HIGHLIGHTS

Inditio	
TOUGH	Heavy-duty Rotax* engine Smooth, durable and responsive transmission True Can-Am DNA with a strong identity
CAPABLE	Work or ride with confidence Meaningful and versatile functionality Easy handling and capabilities
CLEVER	Advanced comfort and intuitive cockpit with optimized visibility Multifunction cargo box with sturdy tailgate and smart storage 1 year maintenance-free and easy access to key maintenance components
PLATFORM FEATURES	• 115.5 in. wheelbase • 13 in. of ground clearance • Dynamic Power Steering (DPS™) • 3,000 lb towing capacity • Multifunction cargo box • 27 in. Maxxis¹ Bighorn 2.0¹ • 4.5 in. digital display
SPECIFIC TO 6X6 XT PACKAGE	64 in. wide with arched A-arm Visco-Lok¹ QE front differential 14 in. cast-aluminum wheels VERSA-PRO bolster bench seat with reinforced XT seat skin and adjustable driver seat HMWPE full skid plate 4,500 lb (2,014 kg) winch Hydraulic power-tilt bed XT front bumper Full hard roof Brake holding mechanism

ENGINE	HD10
Туре	82 hp/69 lb-ft, Rotax 976 cc, V-twin, liquid-cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	PRO-TORQ CVT Transmission with Quick Response System (QRS), high-airflow ventilation and Electronic Drive Belt Protection Extra L/H/N/R/P
Drive Train	Selectable 4WD/6WD with Visco-Lok QE auto-locking front differential
Driving Assistance	Electronic Hill Descent Control ECO™/ECO™ Off/Work modes
Power Steering	Dynamic Power Steering (DPS)

SUSPENSIONS

Arched double A-arm/11 in. (27.9 cm) travel
Twin tube gas-charged shocks
Arched TTA with external sway bar/11 in. (27.9 cm) travel
Twin tube gas-charged shocks

TIRES & WHEELS

Front Tires	Maxxis Bighorn 2.0 27 x 9 x 14 in.
Rear Tires	Maxxis Bighorn 2.0 27 x 11 x 14 in.
Wheels	14 in. cast-aluminum
BRAKES	
Front	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers
	Brake-holding mechanism



Oxford Blue / HD10

DIMENSIONS & CAPACITIES

Chassis/Cage	Profiled cage, ROPS approved
Estimated Dry Weight	2,077 lb (942 kg)
LxWxH	159.7 x 64 x 80 in. (405.7 x 162.5 x 203.3 cm)
Wheelbase	115.5 in. (294 cm)
Ground Clearance	13 in. (33 cm)
Cargo Box Dimensions	72 x 54.5 x 10 in. (180.3 x 138.4 x 25.4 cm)
Cargo Box Capacity	1,000 lb (454 kg)/California only: 600 lb (272.2 kg)
Power Tilt Bed	Hydraulic power-tilt bed
Tailgate Load Capacity	250 lb (113.4 kg)
Storage Capacity	Total: 16.9 gal (63.9 L) Under dash: 6 gal (22.8 L) Waterproof and removable box under passenger seat: 5.6 gal (21 L) Dash: 2 gal (7.7 L) Water-resistant and removable toolbox: 1.7 gal (6.3 L) Armrests and cup holders: 1.6 gal (6.1 L)
Towing Capacity	3,000 lb (1,360.8 kg)
Payload Capacity	1,570 lb (712 kg)
Fuel Capacity	10.6 gal (40 L)
Person Capacity	3

FEATURES

Gauge	4.5 in. wide digital display: speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, ECO™/ECO™ Off/Work modes, seat belt and 4 x 4 indicator, front and rear diff. lock indicators, diagnostics, clock, battery voltage, engine temperature
Battery	12 V (30 amp/h)
Magneto	650 W
Instrumentation	Lighter-type DC outlet in console (20 A)
Lighting	140 W lighting output from four 35 W reflectors ensuring wide visibility and premium LED tail lights
Winch	4,500 lb (2,041 kg) winch with roller fairlead
Seat	VERSA-PRO bolster bench seats for additional lateral support with passenger seats flipping up, adjustable driver seat, underside hooks, reinforced XT seat skin and contoured bench to improve entrance/exit of the cab
Steering Wheel	Adjustable tilt steering
Protection	XT front bumper, HMWPE full skid plate, full hard roof
Hitch Type	2 in. hitch receiver

WARRANTY & EXTENDED SERVICE

Factory Warranty	1 year BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 30 months

