Can-amDEFENDER MAX Lone Star

HIGHLIGHTS

TOUGH	 Heavy-duty Rotax® engine Smooth, durable and responsive transmission True Can-Am DNA with a strong identity
CAPABLE	Work or ride with confidence Meaningful and versatile functionality Easy handling and capabilities
CLEVER	Advanced comfort and intuitive cockpit with optimized visibility Multifunction cargo box with sturdy tailgate and smart storage 1 year maintenance-free and easy access to key maintenance components
PLATFORM FEATURES	• 115.5 in. wheelbase • 13 in. of ground clearance • Dynamic Power Steering (DPS™) • 2,500 lb towing capacity • Multifunction cargo box • Rear differential with Turf mode
SPECIFIC TO Lone Star PACKAGE	65 in. wide with arched A-arm LED Signature Visco-Lok' QE front differential 14 in. cast-aluminum wheels 28 in. with Maxxis Bighorn 2.0 Dual VERSA-PRO bolster bench seats with reinforced seat skin featuring Lone Star package trims and adjustable driver seat HMWPE full skid plate 4,500 lb (2,014 kg) winch Heavy-duty front steel bumper Aluminum rock sliders Full hard roof 7.6 in. digital display with keypad Brake holding mechanism

ENGINE	HD10
Туре	82 hp/69 lb-ft, Rotax 976 cc, V-twin, liquid-cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	PRO-TORQ CVT Transmission with Quick Response System (QRS), high-airflow ventilation and Electronic Drive Belt Protection Extra L/H/N/R/P
Drive Train	Selectable Turf Mode/2WD/4WD with Visco-Lok QE auto-locking front differential
Driving Assistance	Electronic Hill Descent Control ECO™/ECO™ Off/Work modes
Power Steering	Dynamic Power Steering (DPS)

SUSPENSIONS

Front Suspension	Arched double A-arm with sway bar/10 in. (25.4 cm) travel
Front Shocks	Twin tube gas-charged shocks
Rear Suspension	Arched TTA with external sway bar/10 in. (25.4 cm) travel
Rear Shocks	Twin tube gas-charged shocks

TIRES & WHEELS

Rear

Front Tires	Maxxis Bighorn 2.0 28 x 9 x 14 in.
Rear Tires	Maxxis Bighorn 2.0 28 x 11 x 14 in.
Wheels	14 in. cast-aluminum
BRAKES	
Front	Dual 220 mm ventilated disc brakes

Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers

Brake-holding mechanism



Night Black / HD10

DIMENSIONS & CAPACITIES

Chassis/Cage	Profiled cage, ROPS approved
Estimated Dry Weight	1,929 lb (875 kg)
LxWxH	158.9 x 65 x 79.9 in. (403.6 x 165.1 x 203.1 cm)
Wheelbase	115.5 in. (294 cm)
Ground Clearance	13 in. (33 cm)
Cargo Box Dimensions	38 x 54.5 x 12 in. (96.5 x 138.4 x 30.5 cm)
Cargo Box Capacity	1,000 lb (454 kg)
Power Tilt Bed	N/A
Tailgate Load Capacity	250 lb (113.4 kg)
Storage Capacity	Total: 16.9 gal (63.9 L) Under dash: 6 gal (22.8 L) Waterproof and removable box under passenger seat: 5.6 gal (21 L) Dash: 2 gal (7.7 L) Water-resistant and removable toolbox: 1.7 gal (6.3 L) Armrests and cup holders: 1.6 gal (6.1 L)
Towing Capacity	2,500 lb (1,134 kg)
Payload Capacity	1,730 lb (785 kg)
Fuel Capacity	10.6 gal (40 L)
Person Capacity	6

FEATURES

Gauge	7.6 in. wide digital display with keypad: speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, ECO™/ECO™ Off/Work modes, seat belt and 4 x 4 indicator, front and rear diff. lock indicators, diagnostics, clock, battery voltage, engine temperature
Battery	12 V (30 amp/h)
Magneto	650 W
Instrumentation	Lighter-type DC outlets in the console (10 A) and two lighted USB ports in the dash storage (10 A)
Lighting	140 W lighting output from four 35 W reflectors ensuring wide visibility, signature LED and LED tail lights
Winch	4,500 lb (2,041 kg) winch with roller fairlead
Seat	Dual VERSA-PRO bolster bench seats for additional lateral support with passenger seats flipping up, adjustable driver seat, underside hooks, reinforced seat skin featuring Lone Star package trims and contoured bench to improve entrance/exit of the cab
Steering Wheel	Adjustable tilt steering
Protection	Heavy-duty front steel bumper, HMWPE full skid plate, 2-piece full hard roof, aluminum rock sliders
Hitch Type	2 in. hitch receiver

WARRANTY & EXTENDED SERVICE

.E.S.T. term available up to 30 months

