2022

CON-OTT. MAVERICK X3 MAX X ds TURBO RR

HIGHLIGHTS

DEFIANT	Trademark Can-Am DNA with next-generation design Low seating position Ergo-Lok cockpit with front and rear four-way adjustable seats
POWERFUL	 Industry-leading 200 hp turbocharged and intercooled Rotax* ACE engine Advanced airflow dynamics QRS-X transmission
PRECISE	TTX suspension with industry-leading travel Ultra efficient and lightweight chassis Sharpest handling features
PLATFORM FEATURES	• 64 in. wide • 135 in. wheelbase • 14 in. of ground clearance • High-torque Dynamic Power Steering (DPS™) • 20 in. suspension travel • 30 in. Maxxis Carnivore tires • Rear tow hook
SPECIFIC TO X ds TURBO RR PACKAGE	Belt-monitoring system 200 hp Turbo RR engine Smart-Lok™* front differential FOX 2.5 PODIUM RC2 Piggyback shocks 14 in. aluminum beadlock wheels X-package graphics/seats 7.6 in. digital display with keypad Can-Am LED signature 850 W magneto Painted color options

ENGINE	TURBO RR
Туре	200 hp, Rotax ACE (Advanced Combustion Efficiency) 900 cc turbocharged triple-cylinder engine, liquid-cooled with integrated intercooler and high-perfomance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	PDrive primary and Quick Response System X (QRS-X) CVT with high airflow, L/H/N/R/P
Drive Train	Lockable front differential with exclusive Smart-Lok technology. True 4-mode traction system: 2WD/4WD with front diff. lock/4WD TRAIL ACTIV/4WD TRAIL
Power Steering	High-torque Tri-Mode Dynamic Power Steering (DPS)
SUSPENSIONS	
Front Suspension	Double A-arm with sway bar/20 in. (50.8 cm) travel
Front Shocks	FOX 2.5 PODIUM RC2 piggyback with dual speed compression and rebound adjustments
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar/20 in. (50.8 cm) travel
Rear Shocks	FOX 2.5 PODIUM RC2 piggyback with dual speed compression, rebound adjustments and bottom-out control
TIRES & WHEELS	
Front Tires	Maxxis Carnivore 30 x 10 x 14 in.
Rear Tires	Maxxis Carnivore 30 x 10 x 14 in.
Wheels	14 in. cast-aluminum beadlock
BRAKES	
Front	Dual 262 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 248 mm ventilated disc brakes



DIMENSIONS & CAPACITIES

Estimated Dry Weight	1,838 lb (833.7 kg)
Chassis/Cage	Dual-phase 980 steel
LxWxH	164 x 64 x 66 in. (416.6 x 162.5 x 167.6 cm)
Wheelbase	135 in. (342.9 cm)
Ground Clearance	13 in. (33 cm)
Rack Capacity	150 lb (68 kg) with LinQ™ quick-attach
Storage Capacity	Total: 3 gal (11.4 L) Glove box: 1.6 gal (6.2 L) Central console: 1.1 gal (4.1 L) Cup holders: 0.3 gal (1.1 L)
Fuel Capacity	10.5 gal (40 L)

FEATURES	
Gauge	7.6 in. wide digital display with keypad: speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT/ECO™ mode, seat belt and 4 x 4 indicator, front and rear diff. lock indicators, diagnostics, clock, battery voltage, engine temperature, DPS mode
Instrumentation	Lighter-type DC outlet in central console
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
Lighting	LED headlights and tail lights with unique Can-Am LED signature
Winch	N/A
Magneto	850 W
Protection	Integrated front bumper Quarter doors HMWPE full skid plate Rear tow hook

WARRANTY &

EXTENDED SERVICE	
Factory Warranty	6-month BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 30 months



with hydraulic twin-piston calipers