

HIGHLIGHTS

DEFIANT	<ul style="list-style-type: none"> • Trademark Can-Am DNA with next-generation design • Low seating position • Ergo-Lok cockpit with four-way adjustable seats
POWERFUL	<ul style="list-style-type: none"> • Industry-leading 200 hp turbocharged and intercooled Rotax[®] ACE engine • Advanced airflow dynamics • QRS-X transmission
PRECISE	<ul style="list-style-type: none"> • TTX suspension with industry-leading travel • Ultra efficient and lightweight chassis • Sharpest handling features
PLATFORM FEATURES	<ul style="list-style-type: none"> • 64 in. wide • 102 in. wheelbase • 14 in. of ground clearance • High-torque Dynamic Power Steering (DPS™) • 18 in. suspension travel • FOX 2.5 PODIUM QS3 piggyback shocks • 14 in. aluminum wheels • Rear tow hook
SPECIFIC TO X mr TURBO RR 64" PACKAGE	<ul style="list-style-type: none"> • Belt-monitoring system • 200 hp Turbo RR engine • Smart-Lok™ front differential • Snorkeled engine air intake and CVT • 30 in. ITP Cryptid tires • Front bumper, half doors • Front tow hook • HMWPE full skid plate • 4,500 lb (2,041 kg) winch with synthetic rope • X-package graphics/seats • 7.6 in. digital display with keypad • Can-Am LED signature • 850 W magneto • Painted color



■ Liquid Titanium & Magma Red / TURBO RR

ENGINE	TURBO RR
Type	200 hp, Rotax ACE (Advanced Combustion Efficiency) 900 cc turbocharged triple-cylinder engine, liquid-cooled with integrated intercooler, high-performance air filter and strategically positioned engine air intake
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	PDrive primary and Quick Response System X (QRS-X) CVT, high airflow with strategically positioned CVT air intake and exhaust, L/H/N/R/P
Drive Train	Lockable front differential with exclusive Smart-Lok technology. True 4-mode traction system: 2WD/4WD with front diff. lock/4WD MUD/4WD TRAIL
Power Steering	High-torque Tri-Mode Dynamic Power Steering (DPS)
SUSPENSIONS	
Front Suspension	Arched double A-arm with sway bar/18 in. (45.7 cm) travel
Front Shocks	FOX 2.5 PODIUM piggyback with QS3 compression adjustment
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar and arched lower links/18 in. (45.7 cm) travel
Rear Shocks	FOX 2.5 PODIUM piggyback with QS3 compression adjustment and bottom-out control
TIRES & WHEELS	
Front Tires	ITP Cryptid 30 x 9 x 14 in.
Rear Tires	ITP Cryptid 30 x 11 x 14 in.
Wheels	14 in. cast-aluminum with machined finish
BRAKES	
Front	Dual 262 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 248 mm ventilated disc brakes with hydraulic twin-piston calipers

DIMENSIONS & CAPACITIES

Estimated Dry Weight	1,705 lb (773.4 kg)
Chassis/Cage	Dual-phase 980 steel
L x W x H	133 x 66.7 x 66.1 in. (337.8 x 169.4 x 167.9 cm)
Wheelbase	102 in. (259.1 cm)
Ground Clearance	14 in. (35.6 cm)
Rack Capacity	200 lb (91 kg) with LinQ™ quick-attach
Storage Capacity	Total: 2.5 gal (9.4 L) Glove box: 1.6 gal (6.2 L) Central console: 0.8 gal (2.8 L) Cup holders: 0.1 gal (0.4 L)
Fuel Capacity	10.5 gal (40 L)

FEATURES

Gauge	7.6 in. wide digital display with keypad: speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT/ECO™ mode, seat belt and 4 x 4 indicator, front and rear diff. lock indicators, diagnostics, clock, battery voltage, engine temperature, DPS mode
Instrumentation	Lighter-type DC outlet in central console
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
Lighting	LED headlights and tail lights with unique Can-Am LED signature
Winch	4,500 lb (2,041 kg) winch with synthetic rope
Magneto	850 W
Protection	Front bumper Half doors Front and rear tow hooks HMWPE full skid plate

WARRANTY & EXTENDED SERVICE

Factory Warranty	6-month BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 30 months