2022

Can-am. MAVERICK X3 X rc TURBO RR 64"

HIGHLIGHTS

Rear

DEFIANT	Trademark Can-Am DNA with next-generation design Low seating position Ergo-Lok cockpit with four-way adjustable seats
POWERFUL	 Industry-leading 200 hp turbocharged and intercooled Rotax* ACE engine Advanced airflow dynamics QRS-X transmission
PRECISE	TTX suspension with industry-leading travelUltra efficient and lightweight chassisSharpest handling features
PLATFORM FEATURES	• 64 in. wide • 102 in. wheelbase • 14 in. of ground clearance • High-torque Dynamic Power Steering (DPS™) • 18 in. suspension travel • FOX 2.5 PODIUM QS3 piggyback shocks • 14 in. aluminum wheels • Rear tow hook
SPECIFIC TO X rc TURBO RR 64" PACKAGE	Belt-monitoring system 200 hp Turbo RR engine Smart-Lok* front differential 30 in. Maxxis Liberty tires Front bumper, quarter doors Front tow hook HMWPE differential and under-bumper skid plates HMWPE front and rear suspension arm UHMWPE rock sliders 4,500 lb (2,041 kg) winch with synthetic rope X-package graphics/seats 7.6 in. digital display with keypad Can-Am LED signature 850 W magneto Painted color

ENGINE	TURBO RR
Туре	200 hp, Rotax ACE (Advanced Combustion Efficiency) 900 cc turbocharged triple-cylinder engine, liquid-cooled with integrated intercooler and high-perfomance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	PDrive primary and Quick Response System X (QRS-X) CVT with high airflow, L/H/N/R/P
Drive Train	Lockable front differential with exclusive Smart-Lok technology. True 4-mode traction system: 2WD/4WD with front diff. lock/4WD ROCK/4WD TRAIL
Power Steering	High-torque Tri-Mode Dynamic Power Steering (DPS)
SUSPENSIONS	
Front Suspension	Double-arched A-arm with sway bar/18 in. (45.7 cm) travel
Front Shocks	FOX 2.5 PODIUM piggyback with QS3 compression adjustment
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar and arched lower links/18 in. (45.7 cm) travel
Rear Shocks	FOX 2.5 PODIUM piggyback with QS3 compression adjustment and bottom-out control
TIRES & WHEELS	
Front Tires	Maxxis Liberty 30 x 10 x 14 in.
Rear Tires	Maxxis Liberty 30 x 10 x 14 in.
Wheels	14 in. cast-aluminum
BRAKES	
Front	Dual 262 mm ventilated disc brakes with hydraulic twin-piston calipers



Chalk Gray & Magma Red / TURBO RR


DIMENSIONS & CAPACITIES

Estimated Dry Weight	1,674 lb (759.3 kg)	
Chassis/Cage	Dual-phase 980 steel	
LxWxH	133 x 65.6 x 66 in. (337.8 x 166.6 x 167.6 cm)	
Wheelbase	102 in. (259.1 cm)	
Ground Clearance	14 in. (35.6 cm)	
Rack Capacity	200 lb (91 kg) with LinQ™ quick-attach	
Storage Capacity	Total: 2.5 gal (9.4 L) Glove box: 1.6 gal (6.2 L) Central console: 0.8 gal (2.8 L) Cup holders: 0.1 gal (0.4 L)	
Fuel Capacity	10.5 gal (40 L)	

7.6 in. wide digital display with keypad: speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT/ECO™ mode, seat belt and 4 x 4 indicator, front and rear diff. lock indicators, diagnostics, clock, battery voltage, engine temperature, DPS mode
Lighter-type DC outlet in central console
RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
LED headlights and tail lights with unique Can-Am LED signature
4,500 lb (2,041 kg) winch with synthetic rope
850 W
Front bumper Quarter doors UHMWPE rock sliders HMWPE skidplates: Full heavy-duty with differential/Under bumper/Front and rear suspension arm Rear tow hook

WARRANTY & EXTENDED SERVICE

EXTENDED CENTICE	
Factory Warranty	6-month BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 30 months



Dual 248 mm ventilated disc brakes with hydraulic twin-piston calipers

