

HIGHLIGHTS

- Rotax® V-Twin engine options
- · Arched double A-arm front suspension with front sway bar
- Front and rear FOX[†] 1.5 PODIUM[†] QS3 shocks
- Visco-4Lok† front differential
- Heavy-duty front and rear bumpers
- Intelligent Throttle Control (iTC™) with riding modes
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS)
- 3,500 lb (1,588 kg) winch
- 14 in. cast-aluminum beadlock wheels
- 26 in. ITP Terracross radial tires
- Painted plastics for premium look
- Aluminum taper-profile handlebar with full-wrap handguards
- 650 W magneto
- \bullet High-strength, multifunction racks with LinQ $^{\text{\tiny{TM}}}$ quick-attach accessory system
- 5.7 gal (21.4 L) water-resistant rear compartment



Iron Gray, Black & Neo Yellow / 850 / 1000R

ENGINES	850	1000R
Туре	78 hp, Rotax 854 cc V-twin, liquid-cooled	91 hp, Rotax 976 cc V-twin, liquid-cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)	
Transmission	CVT, P/R/N/H/L, standard engine braking	
Drive Train	Selectable 2WD/4WD/Lock 4WD with Visco-4Lok front differential	
Power Steering	Tri-Mode Dynamic Power Steering (DPS)	
SUSPENSIONS		
Front Suspension	Arched double A-arm with front sway bar 9.2 in. (23.3 cm) travel	
Front Shocks	FOX 1.5 PODIUM QS3	
Rear Suspension	Torsional Trailing arm Independent (TTI) 9.9 in. (25.1 cm) travel	
Rear Shocks	FOX 1.5 PODIUM QS3	
TIRES & WHEELS		
Front Tires	ITP Terracross 26 x 8 x 14 in.	
Rear Tires	ITP Terracross 26 x 10 x 14 in.	
Wheels	14 in. cast-aluminum beadlock	
BRAKES		
Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers	
Rear	Single 214 mm disc brake with hydraulic twin-piston caliper	
		

CAPACITIES	850	1000R
Estimated Dry Weight*	800 lb (363 kg)	826 lb (375 kg)
LxWxH	86 x 48 x 49.5 in. (218.4 x 121.9 x 126 cm)	
Wheelbase	51 in. (129.5 cm)	
Ground Clearance	11 in. (27.9 cm)	
Seat Height	34.5 in. (87.7 cm)	
Rack Capacity	Front: 100 lb (45 kg)/Rear: 200 lb (90 kg)	
Storage Capacity	Rear: 5.7 gal (21.4 L)	
Towing Capacity	1,650 lb (750 kg)	
Fuel Capacity	5.4 gal (20.5 L)	
	gear position, 4 x 4 in	
Gauge	7.6 in wide digital display: speedometer, tachometer, odometer, trips and hour meters, gear position, 4 x 4 indicator, temperature,	
Instrumentation	Lighter-type DC	outlet in console,
	standard connecto	r in the back (15 A)
Anti-Theft System	RF Digitally Encoded Sec	curity System (D.E.S.S.™)
Lighting	230 W from twin 60 W projectors and dual 55 W reflectors with tail light/brake light	
Winch	3,500 lb (1,588 kg) winch	
	Standard	
Seat	Heavy-duty front and rear bumpers Aluminum taper-profile handlebar with full-wrap handguards Mudguards	

WARRANTY & EXTENDED SERVICE

Factory Warranty	6-month BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 36 months

