

OPEN UTILITY FA TILTING 2.0

12', 14', 14' 5k



12', 14', 14' 5k

STANDARD FEATURES

- > All-Aluminum Construction
- > 24" O/C Floor Crossmembers
- > 2"x3" Subframe Tubing
- > (2) 5000# Safety Chains
- > 6000# Coupler w/ 2" Ball
- > Torsion Ride Idler Axle
- > EASY Removable Aluminum Fenders
- > Extruded Aluminum Decking
- > Tilt System with Hydraulic Dampener System
- > Fixed 2"x2" Aluminum Side Rail Kit
- > Exterior LED Lights
- > Adjustable Perimeter Track for EASY INSTALL Options
- > Limited 5 Year Warranty

STANDARD SPECIFICATIONS

TRAILER MODEL	FIXED RAIL TILT 6.5X12	FIXED RAIL TILT 6.5X14	FIXED RAIL TILT 6.5X14 5K
Model Number	MU6.5x12FA-TILT-2.0	MU6.5x14FA-TILT-2.0	MU6.5X14FA-TILT-2.0-5K
Deck (WxL)	76"x146"	76"x169"	76"x169"
Overall (WxL)	102"x200"	102"x223"	102"x223"
Deck Height	17"	17"	17"
Hitch Height	14"	14"	14"
Axle(s) - Qty/Rating	1-3500#	1-3500#	1-5200# Braked
Wheels	14" Aluminum	14" Aluminum	15" Aluminum
Tires	205/75R14	205/75R14	225/75R15
Tongue	Triple - Tube	Triple - Tube	Triple - Tube
GVWR	2990#	2990#	4400#
Curb Weight	480#	560#	754#
Payload	2510#	2430#	3646#
Power Connection	4-Way Flat	4-Way Flat	4-Way Flat

OPTIONS & ACCESSORIES (Expanded list of available options can be found in MES option Section)

RAIL KIT OPTIONS (2.0) MODELS
FR Series EASY INSTALL 10" Solid Aluminum Rail Kit (6.5x12) (FA 2.0)
FR Series EASY INSTALL 10" Solid Aluminum Rail Kit (6.5x14) (FA 2.0)
FR Series EASY INSTALL 17" Slatted Aluminum Rail Kit w/ Solid Front (6.5x12) (FA 2.0)
FR Series EASY INSTALL 17" Slatted Aluminum Rail Kit w/ Solid Front (6.5x14) (FA 2.0)
TIRE/WHEEL ASSEMBLIES & ACCESSORIES
Spare 14" Aluminum Wheel w/ 205/75R14 Tire
Spare 15" Aluminum Wheel w/ 205/75R15 Tire
Spare 15" Aluminum Wheel w/ 225/75R15 Tire (6-Lug)
Downgrade to Silver Mods From Aluminum Rims
Upgrade to 15" Aluminum (Radial Ply; From 14" Aluminum Wheels; Open Trailers)

EASY INSTALL/ADJUST OPTIONS
EASY INSTALL/ADJUST SPARE TIRE MOUNT (FOR AR OR FA 2.0)
EASY INSTALL/ADJUST STAKE POCKET KIT (AR OR FA 2.0) Includes (4) Stake Pockets w/ Hardware
EASY INSTALL/ADJUST D-RING KIT (FOR AR OR FA 2.0) - Includes (4) 2,000lb D-Rings and Hardware
EASY INSTALL/ADJUST D-RING (FOR AR OR FA 2.0)
EASY INSTALL/ADJUST DROP DOWN STABILIZER JACKS (PAIR) (FOR AR OR FA 2.0)

RAMP CAPACITY BY MODEL

Ramp Type	Applicable Models	Capacity
Utility Trailer Rear Ramp (Fold-Down)	SSR (All Sizes), AR 2.0 (All Sizes), WR 2.0 (All Sizes), FA 2.0 (All Sizes), LANDSCAPE (LS) 2.0 (All Sizes)	750#
Utility Trailer Rear Ramp (Fold-Down, Bi-Fold)	SSR (Optional, All Sizes), AR 2.0 (Optional, All Sizes), WR 2.0 (Optional, All Sizes), FA 2.0 (Optional, All Sizes), LANDSCAPE (LS) 2.0 (Optional, All Sizes)	750#
Deckover Equipment Trailer Ramps (Stow)	(All Sizes)	4000# (PAIR)
Deckover Equipment Trailer Ramps -14K (Fold-Down)	(All Sizes)	5000# (PAIR)
Patriot Ramps (Fold-Down)	(All Sizes)	4000# (PAIR)
Patriot Ramps -14K (Fold-Down)	(All Sizes)	5000# (PAIR)
Dump Trailers (Side-Stow, Optional)	(All Sizes)	4000# (PAIR)
ATV (83-Wide, Side-Stow)	(All Sizes)	1200# (PAIR)
ATV (88-Wide, Side-Stow)	(All Sizes)	750# (PAIR)
Open Motorcycle (Rear-Stow)	(All Sizes)	1200#
Slingshot Rear Ramp (Fold-Down, Bi-Fold)	MU-SLINGSHOT	1500#
Open Car Hauler 2.0 (Stow)	(All Sizes)	4000# (PAIR)
Open Car Hauler 2.0-10K (Stow)	(All Sizes)	4000# (PAIR)
Open Car Hauler Standard (Stow)	(All Sizes)	4000# (PAIR)
Open Snow (Rear-Stow)	MFS	750#
Sport Deck (Rear-Stow, Telescoping)	MSD	1000#
Enclosed Cargo (4, 5, 6-Wide)	(All Sizes)	1500#
Enclosed Cargo (7, 7.5-Wide)	(All Sizes)	1500#
Enclosed Cargo (8.5-Wide, Premium)	(All Sizes)	1500#
Enclosed Motorcycle (7-Wide)	(All Sizes)	1500#
Enclosed Car Hauler (8.5-Wide)	(All Sizes)	4000#
Enclosed Gooseneck (8.5-Wide, REAR)	(All Sizes)	4000#
Enclosed Gooseneck (8.5-Wide, SIDE, Optional)	(All Sizes)	1200#
Enclosed Snowmobile (7, 7.5, 101-Wide, REAR)	(All Sizes)	1500#
Enclosed Snowmobile (7, 7.5, 101-Wide, FRONT)	(All Sizes)	1200#
Enclosed Snowmobile (Crossover REAR)	(All Sizes)	1500#