

## Specifications

Model	450	550
Cutting width	134" (11.2')	163" (13.6')
Transportation width bottom/top	84"/90"	86"/100"
Transportation height / length	80"/13"	84 1/2"/15'9"
Recommended horsepower	35 hp	40 hp
Wing flex*	30° up 17° down	35° up 16° down
Deck overlap	5"	8.5"
Gear box rating at 540 RPM	66 hp - divider box / 30 hp - wing boxes	
Hitch type	Cast clevis - standard, 25/16" ball hitch - optional	
Driveline main / wings	Series 4-80° CV / series 2	Series 6-80° CV / series 2
Deck width / thickness	4' / 10 Ga.	5' / 7 Ga.
Deck tires	8 (15" x 6" x 6")	10 (15" x 6" x 6")
Main frame tire	2 (27" x 10-1/2" x 15")	2 (27" x 10-1/2" x 15")
Blades per deck / overlap	3 blades / 1-5/8"	3 blades / 2-5/8"
Blade tip speed	15,485 ft/min	15,829 ft/min
Cutting height	1-1/2" to 4-1/2"	1-1/2" to 4-1/2"
Mower drive system	2 belt B groove	2 belt B groove
Front roller	4" x 7" UHMW Poly	4" x 7" UHMW Poly
Weight	3347 lbs	3919 lbs

\* Not recommended for operation greater than 30°, actual measurement based on mower deck flex.

Model	650	750
Cutting width	200" (16.7')	236" (19.9')
Transportation width bottom/top	86"/102"	79"/102"
Transportation height / length	103" / 16'3"	121 1/2" / 16'9"
Recommended horsepower	45 hp	50 hp
Wing flex*	30° up 11° down	30° up 11° down
Deck overlap	8"	8"
Gear box rating at 540 RPM	66 hp - divider box / 30 hp - wing boxes	
Hitch type	Cast clevis - standard, 25/16" ball hitch - optional	
Driveline main / wings	Series 6-80° CV / series 2	Series 6-80° CV / series 2
Deck width / thickness	6' / 7 Ga.	7' / 7 Ga.
Deck tires	10 (15" x 6" x 6")	12 (15" x 6" x 6")
Main frame tire	2 (27" x 10-1/2" x 15")	2 (27" x 10-1/2" x 15")
Blades per deck / overlap	3 blades / 2-5/8"	3 blades / 2-5/8"
Blade tip speed	18,737 ft/min	18,552 ft/min
Cutting height	1-1/2" to 4-1/2"	1-1/2" to 4-1/2"
Mower drive system	2 belt B groove	2 belt B groove
Front roller	4" x 7" UHMW Poly	4" x 7" UHMW Poly
Weight	4349 lbs	4633 lbs

\* Not recommended for operation greater than 30°, actual measurement based on mower deck flex.