

Snowblower

Models: 5010 / 6010 / 6610 / 7420 / 8420 / 8420G /
9620Q / 1080C / 1200C



SPECIFICATIONS									
MODEL >>	5010	6010	6610	7420	8420	8420G	9620Q	1080C	1200C
Cutting width	50"	60"	66"	74"	84"	84"	96"	108"	120"
Cutting height	24"			25"			36"	41"	
Replaceable cutting edge	N/A						Optional	Yes	Yes
Fan	4-blade								
Fan diameter	20"	22"		24"			32"	34"	
Replaceable fan housing	N/A							7 gague	
Drive fan	540 RPM open gear					540 RPM oil bath gearbox		540 RPM oil bath	1000 RPM oil bath
Auger diameter	13"	15"				15" (dual)			
Auger drive	#50 chain						#60 chain	#80 chain	
Spout rotator - manual - hydraulic	standard optional			optional standard				N/A standard	
Spout deflector - manual - hydraulic	standard optional						N/A standard		
Skid shoes	adjustable & replaceable								
Hitch category	Cat. I standard				Cat. I & II std Cat. I & II QH		Cat. II std Cat. II QH	Cat. II & III std Cat. II & III QH	
Hitch adjustment	4 position			2 position			Fixed	2 position	
Tractor requirements	15 - 30 hp	20 - 40 hp	22 - 40 hp	40 - 70 hp	60 - 90 hp		90 - 125 hp	120 - 180 hp	180 - 225 hp
Weight	422 lb	470 lb	515 lb	756 lb	848 lb	878 lb	1243 lb	2398 lb	2600 lb

* Capacity rating dependent on grain type, moisture, density, % F.M. and elevation of main auger.