

Unverferth® Header Transports

Fieldrunner, Fieldrunner AWS and Roadrunner



Farm to Farm **Field to Field**

Roadrunner



Fieldrunner HT



Fieldrunner AWS



Fieldrunner, Fieldrunner AWS and Roadrunner Header Transports

For timely, safe and efficient combine header movement from field to field, or farm to farm, look to Unverferth – the industry innovator. From pioneering the first true header transport in the '70s for a 6-row head to today's 12-, 16- and even 24-row, there's an Unverferth header transport to perfectly fit your needs.

All three styles feature patented tool-free adjustability for matching virtually every make and model platform and draper head. Standard transport and safety equipment includes a lightbar, tie-down straps, reflective striping and transport chains.

Fieldrunner HT header transport



Fieldrunner HT

Unverferth Fieldrunner header transports are perfect for shorter road trips and moving from field to field. The exclusive rear oscillating axle keeps all four wheels in full contact with the ground, even through ditches and valleys for optimum trailing.

- 100% tool-free adjustability and models available in 42', 36', 30' and 25' lengths
- Steel upper rest bar resists flexing and is fully adjustable, both vertically and horizontally, without tools, to fit any brand grain platform or row-crop header
- The sturdy 6"x4" lower rest bar resists bowing and flexing
- Patented rest brackets allow quick, easy and tool-free adjustment for holding and transporting grain platform or corn head
- Steel tie-back loops are included for secure fastening of the tie-down straps
- Heavy-duty 8-ton hubs, spindles, steering components and 6-bolt wheels with new tires dependably carry all brands of corn heads and grain platforms
- The tongue's extendable clevis and spring-lift assist make hitching to pickup, combine or tractor easy and convenient
- Extra-height clearance between axle and ground allows for easy field entry and exit
- Optional 12.5" bracket specifically for draper and corn heads for greater versatility
- HT-42, HT-36 and HT-30 feature a trussed lower rest bar for even greater strength and stability
- Transport chain, rear-mounted LED lighting package, tie downs and reflective striping are standard equipment for optimum road travel safety
- Units equipped with 12"-diameter tires feature 180° steering
- Available large-diameter 11Lx15 F-range tires provide 14,000-pound carrying capacity with greater flotation and feature 150° steering
- A storage slot in the upper rest bar is specifically designed for holding an extra cutter knife
- Highly durable powder-coat finish in choice of red, green or black helps resist corrosion



Spring-lift assist tongue



Standard tool-free 4-way adjustable rest bracket



180° steering

Unverferth Fieldrunner HT Specifications

Model Number	HT-42 Auto-Type Steering	HT-36 Auto-Type Steering	HT-30 Auto-Type Steering	HT-25 Auto-Type Steering
Fits Conventional Grain Platforms	42' and smaller	35' and smaller	30' and smaller	25' and smaller
Fits Draper Platforms	42' and smaller	36' and smaller	30'	25'
Fits Corn Heads	16-row & specialty corn heads	12-row & smaller	12-row & smaller	12-row & smaller
Carrying Capacity* with Standard Tires	14,000 lbs.	8,500 lbs.	8,500 lbs.	8,500 lbs.
Standard Tires	11Lx15 F-Range	22.5x8.00-12 F-Range	22.5x8.00-12 F-Range	22.5x8.00-12 F-Range
Approx. Weight with Wheels and Tires	2,180 lbs.	1,776 lbs.	1,600 lbs.	1,290 lbs.
Tread Width	6'	6'	6'	6'
Height Adjustment, Maximum	3'11"	3'11"	3'11"	3'9"
Height Adjustment, Minimum	2'8"	2'8"	2'8"	2'5"
Bracket Height Adjustment, Maximum	2'8"	2'8"	2'8"	2'5"
Bracket Height Adjustment, Minimum	2'2"	2'2"	N/A	N/A
Upper Support Tube Dimensions	8"x 4"x43'	6"x 3"x37'	5"x 3"x31'	5"x 3"x26'
Hitch to Front Axle Standard Latched Position	16'	16'	12'	12'
Optional Latched Position	—	—	16'	16'
Wheelbase	20'	18'5"	18'5"	14'5"
Approx. Overall Length	52'7"	46'7"	39'1"	34'1"
Span Between Upper/Lower Bar, Maximum	4'4"	4'4"	4'4"	4'4"
Span Between Upper/Lower Bar, Minimum	2'11"	2'11"	2'11"	2'11"

*Carrying capacities are rated at agricultural speeds. U.S. Patent #6,272,824.

Due to continuing improvements in the design and manufacture of Unverferth products, all specifications contained herein are subject to change without notice.



Rear-mounted LED lights



11Lx15 F-range tires



2" tie-downs

Models HT-42, HT-36, HT-30, HT-25

Fieldrunner AWS/AWSP header transport



Fieldrunner AWSP

The patented Fieldrunner AWS (All-Wheel Steering) header transport with front-to-rear steering reduction provides the best in all-wheel steering maneuverability. AWSP models feature 4-wheel rubber-cushioned suspension for greater over-the-road stability.

- Patented, 4-wheel steering offers sharper turning, greater maneuverability and excellent trailing
- Patented convertible rest brackets for quick, easy and totally tool-free adjustment for grain platforms, corn and draper heads
- Models available in 48', 42', 36' and 30' for hauling the widest variety of corn heads, grain platforms and draper platforms
- Steel upper rest bar resists flexing and is fully adjustable both vertically and horizontally, without tools, to fit any brand grain platform or row-crop header
- Three support arms provide maximum upper bar support and tool-free adjustability
- Twin trussed lower rest bars add rigidity to the unit for full-width support
- The rear-oscillating axle keeps all four wheels in full contact with the ground, even when traveling over rough terrain
- Heavy-duty greaseable 10-ton hubs, automotive-type ball-joint steering, spindles with tapered roller bearing and 6-bolt wheels with new tires dependably carry all brands of corn heads and grain platforms
- The 12' tongue's extendable clevis and spring-lift assist makes hitching to pickup, combine or tractor easy and convenient
- 2" tiedowns with heavy-duty nylon straps, brackets and ratchets for securing the load
- Retractable lighting cord keeps excess wiring concealed in tongue for longer life
- Extra-height clearance between axle and ground allows for easy field entry and exit
- Rear LED light bar mounted on axle and one on upper rest bar for enhanced visibility and 7-pin bladed receptacle for quick attachment to towing vehicle
- Transport chain and reflective striping are standard equipment for optimum road travel safety
- A wide variety of tire choices depending on model
- A storage slot in the upper rest bar is specifically designed for holding an extra cutter knife
- A highly durable powder-coat finish in choice of red, green or black helps resist corrosion



Rear oscillating axle and standard lights



4-point rubber-cushioned suspension



Optimum maneuverability

**True trailing & towability
over any terrain**



Unverferth Fieldrunner AWS/AWSP HT Specifications

Model Number	AWS/AWSP-48	AWS/AWSP-42	AWS/AWSP-36	AWS/AWSP-30
Fits Conventional Grain Platforms	48' and smaller	42' and smaller	35' and smaller	30' and smaller
Draper Platforms	48' and smaller	42' and smaller	36' and smaller	30' and smaller
Corn Heads (30" Rows)	16-row & specialty	16-row & specialty	12-row & smaller	12-row & smaller
Carrying Capacity* with Standard Tires	14,000 lbs.	14,000 lbs.	14,000 lbs.	14,000 lbs.
Standard Tires	11Lx15 F-Range	11Lx15 F-Range	11Lx15 F-Range	11Lx15 F-Range
Approx. Weight (lbs.)	3,000 lbs.	2,800 lbs.	2,700 lbs.	2,200 lbs.
Tread Width	80"	80"	80"	80"
Approx. Overall Length – Std. Tongue	59'	51'	47'	42'
Wheelbase	30'	30'	24'	24'
Tongue Length (Std./Opt.)	16'	12'/16'	12'/16'	12'/16'
Upper Support Tube Dimensions	8"x 4"x49'	8"x 4"x43'	6"x 3"x37'	5"x 3"x31'
Maximum Height	4'3"	4'3"	4'3"	4'3"
Minimum Height	2'6"	2'6"	2'6"	2'6"
Rest Bracket Maximum Height	2'6"	2'6"	2'6"	2'6"
Rest Bracket Minimum Height	2'4"	2'4"	2'4"	2'4"
Span Between Upper/Lower Bar, Maximum	4'5"	4'5"	4'5"	4'5"
Span Between Upper/Lower Bar, Minimum	2'5"	2'5"	2'5"	2'5"

*Carrying capacities are rated at agricultural speeds. U.S. patent #8,870,210 additional foreign patents pending.

Due to continuing improvements in the design and manufacture of Unverferth products, all specifications contained herein are subject to change without notice.



180° front steering



Optional 2- or 4-wheel brakes



Tool-free, 2-way adjustable rest bracket

Models AWS, AWSP, 48, 42, 36 and 30

Road-ready for a high-speed harvest



The Unverferth Roadrunner header transport is specifically designed and constructed for longer-haul highway travel. It's the ideal hauler for your combine's grain platform, draper head, chopper or conventional corn head.

The Roadrunner's tricycle front axle allows for a tighter turning radius and greater maneuverability. The front and rear torsion-flex axles and highway speed-rated tires ensure stable tracking and towing that gets you down the road and onto the next farm as quickly as possible.

- Integrated chassis design with adjustable trussed-frame can be tailored to each head regardless of weight, while keeping full-width support
- Extended-length upper rest bar for full-width support of combine head
- Three upper bar supports for full-length header support
- 4-way, tool-free adjustable rest brackets to fit any brand header or platform
- Standard 12 ½"-wide pads to accommodate draper heads with under-frame stowage when the traditional brackets are used
- Available with 2-, 4- or 6-wheel brakes, depending on model, and includes break-away kit for added safety
- Plastic-molded full-wrap front fenders turn with wheels to protect pickup tailgates and headers from stone chips and debris
- Tandem 6,000 lb. rear axles are adjustable for accommodating various feeder-house designs
- Adjustable tongue length from 57" to 81"; telescopes to 91" for easy hookup
- Width-adjustable LED light bar attaches to rear of upper rest bar for greater visibility
- Rear brake and turn signal lights and double transport safety chains for enhanced safety
- The tongue rotates completely beneath the frame for space-efficient storage
- Industry-standard 7-pin bladed receptacle for attachment to towing vehicle is standard; electric cord routes through frame for added protection
- Choice of 15" - or 16" -diameter tires on 30', 36' and 42' models; 16" standard on 48' models
- Standard clevis hitch with pintle or ball-hitch conversion package available
- Storage slot in upper rest bar for extra cutter knife
- Durable powder-coat finish in choice of tractor red, green or black



2" tiedown and rest bracket



Rear torsion suspension



Front torsion suspension



Adjustable rear axles



Width-adjustable LED light bar



Optional spare tire

Unverferth Roadrunner Specifications

Model Number	48' Models 548 Tricycle Front Tandem Rear Axle	42' Models 542 Tricycle Front Tandem Rear Axle	36' Models 536 Tricycle Front Tandem Rear Axle		30' Models 530 Tricycle Front Tandem Rear Axle	
Fits Conventional Grain Platforms	48' and smaller	40' and smaller	35' and smaller	35' and smaller	30' and smaller	30' and smaller
Fits Draper Platforms	48' and smaller	42' and smaller	36' and smaller	36' and smaller	30' and smaller	30' and smaller
Fits Corn Heads	16-row & smaller	16-row & smaller	For specialty & narrow row heads	For specialty & narrow row heads	For specialty & narrow row heads	12-row & smaller
Carrying Capacity*	14,000 lbs.	14,000 lbs.	14,000 lbs.	11,000 lbs.	14,000 lbs.	11,000 lbs.
Tires (highway rated), Front & Rear	235/80x16	235/80x16	235/80x16	225/75x15	235/80x16	225/75x15
Approx. Weight with Wheels and Tires	4,600 lbs.	4,490 lbs.	3,910 lbs.	3,790 lbs.	3,935 lbs.	3,635 lbs.
Rear Wheel Tread Width	6'	6'	6'	6'	6'	6'
Bracket Height Adjustment, Maximum	2'8"	2'8"	2'8"	2'6"	2'8"	2'6"
Bracket Height Adjustment, Minimum	2'4"	2'4"	2'0"	1'10"	2'0"	1'10"
Span Between Upper/Lower Bar, Maximum	4'9"	4'9"	4'9"	4'9"	4'9"	4'9"
Span Between Upper/Lower Bar, Minimum	2'10"	2'10"	2'10"	2'10"	2'10"	2'10"
Overall Length (approximate)	59'5"	53'5"	47'5"	47'5"	41'5"	41'5"
Upper Support Tube Dimensions	6"x 3"x49'	6"x 3"x43'	6"x 3"x37'	6"x 3"x37'	5"x 3"x37'	5"x 3"x31'
Rest Pad Adjustment Length	27'10"-25'4"	27'10"-25'4"	23'3"-22'6"	23'3"-22'6"	23'3"-22'6"	23'6"-22'6"
Tongue Length	5'9"	5'9"	5'9"	5'9"	5'9"	5'9"
Wheelbase	32'6"-30'	32'6"-30'	28'1"-27'4"	28'1"-27'4"	28'1"-27'4"	28'1"-27'4"
Upper Bar Height Adjustment, Maximum	4'0"	4'0"	4'0"	3'10"	4'0"	3'10"
Upper Bar Height Adjustment, Minimum	3'0"	3'0"	3'0"	2'10"	3'0"	2'10"

*Carrying capacities are rated at agricultural speeds. U.S. Patent #6,272,824.

See your nearest Unverferth dealer today or visit our website at umequip.com for complete details about all Unverferth header transports.

Due to continuing improvements in the design and manufacture of Unverferth products, all specifications contained herein are subject to change without notice.

Unverferth
Manufacturing Company, Inc.

P.O. Box 357
Kalida, Ohio 45853
(419) 532-3121 • unverferth.com

Please remind all family members and others to use caution and follow recommended safety practices when around all farm equipment. Unverferth Manufacturing Co., Inc., supports the efforts of Farm Safety 4 Just Kids and all other organizations that promote farm safety.

©2015 Unverferth Manufacturing Co., Inc. Printed in U.S.A.

®™ Trademarks, registered or applied for, of Unverferth Manufacturing Co., Inc., Kalida, OH.

Additional facilities in California, Georgia, Iowa, Nebraska, North Dakota, Oregon, Ontario and Saskatchewan, Canada



HT5151800M5

Unverferth® Header Transports

Fieldrunner, Fieldrunner AWS and Roadrunner



Farm to Farm ***Field to Field***

Roadrunner



Fieldrunner AWS



Fieldrunner HT



Fieldrunner, Fieldrunner AWS and Roadrunner Header Transports