



# **UNVERFERTH RIPPER-BEDDER**

## **ONE-PASS SOIL PREP FOR BEDDED CROPS**



**SEEDBED TILLAGE**

Model 432  
[umequip.com](http://umequip.com)



## Unverferth® RIPPER-BEDDER

### **FIGHT COMPACTION AND PREPARE SEEDBEDS IN ONE PASS**

*The Unverferth Model 432 Ripper-Bedder deep tills, raises and shapes beds in one pass to optimize germination conditions and encourage vigorous early growth for peanuts, cotton, hemp and other bedded crops. Save time, save fuel and prepare your rows in one pass with this all-in-one tool.*

#### **Model 432 Main Features**

- Auto-reset trip design with 6,000 pounds of trip pressure
- Heavy-duty cast pull arm can trip upward and rearward to avoid obstacles and quickly resets without the need for shear-bolt replacement
- Shanks are steep-sloped and constructed of a special .75" thick alloy for extra durability and feature replaceable raised-center shark-fin points
- Till up to 18" deep for shattering hardpan with minimal soil surface disruption
- Patented 1.25" wide shark fin wearbars extend the shank life and reduce soil disturbance

#### **Frame Standard Features**

- Heavy-duty, double frame with 6" x 6" rear mounting bar for maximum durability
- Stabilizer wheels provide added stability and tool-free adjustment for quick and convenient setting of depth
- Rigid models are equipped with 7.6L x 15 8-ply tires, folding models up to 12-row 30" feature 9.5L x 15 8-ply tires on base and wings, and 12-row models with 36" and wider spacings feature 12.5L x 15 10-ply tires on base
- Transport lights and reflective markings for safer road transport
- Powder-coated frame in tractor red or green for a long-lasting, durable finish



**Rugged shank design**

# BEDDING ATTACHMENTS

*For finishing off your seedbed, choose from bedding disks with a fully adjustable parallel-link design or economical spring-reset or rigid listers.*

## Disk Gang

- Features 18" inner and 20" outer concave blades on 36", 38" or 40" wide spacings, 20" blades for 30" spacing
- Gangs can be positioned at 7°, 13°, 19° or 24° angles to meet individual needs
- Gangs can be staggered for rounded beds to capture and retain more moisture, or opposed for a taller peaked bed
- Disk gang arms are tool-free adjustable and can be easily changed to fully floating, limited float or rigid setting to match your field conditions
- Gauge wheel package with 20.5 x 8-10-ply tires on the bedding disk provides flotation in tilled soils when bedding disks are operated in floating position



## Listers

- 10"-wide furrow shovels for 30" spacing or 15" shovels for wider spacings provide economical bedding for a wide variety of applications
- Choose from a spring-reset lister shank design or a rigid shank design to meet individual needs



## Bed Shaper Kits

- Bolts onto the back of the bedding disk or lister toolbar for consistent bed shaping
- Tool-free spring downpressure settings to tailor beds to your needs



# ACCESSORIES

Customize your Model 432 to your exact needs with these optional accessories.

- **Scraper kits** bolt onto the bedding disk arm and require minimal adjustment when changing the disk cutting angle
- **Lead coulter** with a swivel design is equipped with 20", 13-wave blades and 1,500 pounds of downforce
- **Patented flex-frame hydraulics** on folding models with 36", 38" and 40" spacings allow the wings to float up 15 degrees and down 5 degrees to follow ground contours
- **Three-Point Implement Caddy** easily converts the Ripper-Bedder or other three-point implements into a pull-type unit
- **Plastic shank protectors** provide non-stick performance and prevent against damage in tacky and abrasive soils



Optional shatter wings and shank protectors

- **Steel shank protectors** provide added shank life in any soil type
- **7" or 9" shatter wings** can be added to the point and are angle-adjustable from zero to 14 degrees for greater soil surface disturbance
- **Row-markers** feature 16" notched blades that leave a highly visible mark and come complete with hydraulics and sequence valve
- **Lift-assist package** for 12-row models with 36", 38" and 40" spacings provides faster, easier lifting on endrows and for transport

## Auto-Reset Model 432

Model Size	Row Spacing	Approximate Weight			Transport Width	Transport Height
		With Bedding Disks	With Spring-Cushioned Lister Shovel	With Rigid Lister Shovel		
6-Row Rigid	30"	5,700 lbs.	4,620 lbs.	5,010 lbs.	16'6"	—
	36"	5,950 lbs.	4,840 lbs.	5,240 lbs.	21'	—
	38"	5,950 lbs.	4,840 lbs.	5,240 lbs.	21'	—
8-Row Rigid	30"	7,000 lbs.	5,550 lbs.	6,050 lbs.	22'	—
8-Row Folding	36"	8,970 lbs.	6,525 lbs.	7,025 lbs.	16'6"	11'6"
	38"	8,970 lbs.	6,525 lbs.	7,025 lbs.	16'6"	11'6"
	40"	8,970 lbs.	6,835 lbs.	7,335 lbs.	16'6"	11'6"
12-Row Folding	30"	13,675 lbs.	11,300 lbs.	12,100 lbs.	15'6"	12'4"
	36"	13,875 lbs.	11,550 lbs.	12,300 lbs.	21'7"	12'3"
	38"	13,875 lbs.	11,550 lbs.	12,300 lbs.	21'3"	13'1"
	40"	13,975 lbs.	11,875 lbs.	12,675 lbs.	21'3"	13'10"

Note: Specifications are less markers and bedding gang gauge wheels

See your nearest Unverferth dealer today for complete details about the Ripper-Bedder, or check our website at [www.umequip.com](http://www.umequip.com).

Due to continuing improvements in the design and manufacture of Unverferth products, all specifications contained herein are subject to change without notice. For relevant patent marking, please visit [unverferth.com/patents](http://unverferth.com/patents).

**Unverferth**  
Manufacturing Company, Inc.

© 2019 Unverferth Manufacturing Co., Inc.  
Printed in U.S.A.

P.O. Box 357 | Kalida, OH 45853 | [unverferth.com](http://unverferth.com) | 419.532.3121

®™ Trademarks, registered or applied for, of Unverferth Manufacturing Co., Inc., Kalida, OH

Additional facilities in California, Georgia, Iowa, Nebraska, North Dakota, Oregon, Texas, Ontario and Saskatchewan, Canada



URB91517000M5