



# DIESEL Z



LIMITED WARRANTY

**5** YEAR | **1200** HOUR

FIRST 2 YEARS NO HOUR LIMIT

AVAILABLE DECK SIZES

Engine	Deck Sizes
25HP <sup>+</sup> - Perkins	60", 72" • 60" RD, 72" RD



**VX4<sup>®</sup> Deck**  
Fabricated 7 ga. steel deck engineered to move large amounts of grass at high speeds while maintaining cut-quality.



**13M<sup>™</sup> Suspension Seat**  
High-back seat with adjustable armrests and 3-inch travel range.



**Patented Belt Drive System**  
Helps provide long-life to the machine.

## DIESEL Z

ENGINE	
Manufacturer	Perkins
HP	25HP* (Per SAE J1995)
Displacement	1,130cc
Cooling	Liquid cooled, direct-drive, mechanical cooling fan
Air Cleaner	Remote canister
Engine Warranty	3 year limited
DRIVE SYSTEM	
Type	Dual hydrostatic
Pumps	Tandem 21cc Hydro-Gear® pumps
Wheel Motors	Parker® TG
Hydraulic Lines	Stainless steel Parker® Seal-Lok technology
Hydraulic Cooling	Oil cooler with 8" fan
Reservoir Capacity	1.3 gallons
Speed	Up to 11.5 mph
Parking Brakes	Integrated with steering levers
DECKS	
Cutting Width	Side discharge: 60", 72" • Rear-discharge: 60", 72"
Cutting Heights	1" - 5.5"
Deck Lift	Foot operated
Depth	5.5"
Blades	3
Blade Length	60" deck: 20.50" • 72" deck: 24.5"
Blade Tip Speed	60": 18,200 • 72": 18,800
Spindles	Ductile cast iron with steel shaft and sealed ball bearings
Drive	Electric PTO clutch
Construction	7 ga. welded steel
Spindle Mounts	Reinforced 7 ga. stamped disc
Impact/Trim Areas	Front of deck: 11 ga. formed bump bar • Side of deck: 1.5" x .375" steel bar
CONSTRUCTION	
Frame	1.5" x 3" steel tubing
Front Axle	Fabricated w/ sealed ball bearings
Front Caster Wheels	Tapered wheel bearings and debris cap
Front Caster Forks	Fabricated 1/2" steel
GENERAL	
Seat	I3M™ suspension seat
Fuel Capacity	14.4 gallons
Cupholder	Yes
Front Tire	13 x 6.5 - 6
Drive Tire	24 x 12 - 12
DIMENSIONS	
Weight	60": 1656 lbs • 60"RD: 1766 lbs • 72": 1711 lbs • 72"RD: 1816 lbs
Height	51" • 69" w/ ROPs
Length	60", 60"RD: 86.8" • 72", 72"RD: 90.4"
Width w/Chute Up	60", 60"RD: 66" • 72", 72"RD: 78"
Tire Width	56"
Trim Side	60": 3.9" • 60"RD: 3.6" • 72": 10.9" • 72"RD: 8.6"
PRODUCTIVITY**	
Acres Per Hour	60": 5.57 • 72": 6.68

Specifications are subject to change without notice.

### ACCESSORIES (Each sold separately)

- ▶ Semi pneumatic front tires
- ▶ Steering lever extension kit
- ▶ Single/dual anti-scalp wheels
- ▶ Flex Forks®
- ▶ Mulch kit
- ▶ Light kit
- ▶ Stripe kit
- ▶ Sand kit
- ▶ Beacon kit
- ▶ Flasher kit
- ▶ Electric deck lift
- ▶ Hitch kit
- ▶ Michelin® X® Tweel® Turf
- ▶ Michelin® X® Tweel® Turf Caster
- ▶ Fabric side catcher (3.5 bu)
- ▶ Aluminum side catcher (3.3 bu)

\* As rated by the engine manufacturer.  
 \*\* Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain.  
 Parker is a registered trademark owned by Parker Intangibles LLC. Hydro-Gear is a registered trademark owned by Hydro-Gear Limited Partnership.  
 Michelin, X and Tweel are registered trademarks owned by COMPAGNIE GÉNÉRALE DES ÉTABLISSEMENTS MICHELIN.