



SUPER S



AVAILABLE DECK SIZES

Engine	Deck Sizes
15HP* - Kawasaki® FS541	36"
19HP* - Kawasaki® FX600	36"
22HP* - Kawasaki® FX691	48"
27HP* - Kawasaki® FX850	52", 60"
29.5HP* - Kawasaki® FX850 EFI	52", 60"
26HP* - Vanguard® 810cc w/ Oil Guard	52"



SUPER S

Cut Height Adjustment
Hand operated lever and pin to adjust deck/cutting height.

Park Brake
Hand operated lever to set the park brake.

24" Rear Drive Tires
For superior traction. (48", 52", 60")

Wide Operator Platform
For mowing comfort and operator stability.

Pulley Covers
Toolless removable pulley covers for easy maintenance.



Adjustable Speed Controls
Allows you to go at your own pace for control. Also helps with training new operators.

Adjustable Foot Platform
Spring loaded suspension platform for comfort.



THE SUPER S STAND-ON MOWER

SUPER S

- ✓ **Compact Stance**
Ideal for tight spaces and for trailering from job-to-job
- ✓ **Service Friendly Design**
Designed to make maintenance and service fast and easy.
- ✓ **SmoothTrak™ Steering**
Precision control to help trim and maneuver easily around obstacles.
- ✓ **VX™ Deck**
Fabricated 7 ga. steel engineered for extreme vacuum performance and cut quality.
- ✓ **Deck Options**
36", 48", 52" and 60"



ACCESSORIES

(Each sold separately)

- ▶ Mulch kit
- ▶ Mesh side bagger (3 bushels)
- ▶ Aluminum side bagger (3.3 bushels)
- ▶ Fabric side bagger (3.5 bushels)
48", 52", 60" deck only
- ▶ Light kit
- ▶ Stripe kit
- ▶ Trash basket
36" only
- ▶ Cup holder
36" only



SUPER S

ENGINE	
Manufacturer	Kawasaki® FS, FT & FX series
HP	36" deck: 15HP* - FS541, 19HP* - FX600 48" deck: 22HP* - FX691 52", 60" deck: 27HP* - FX850, 29.5HP* - FX850 EFI 52" deck: 26HP* - Vanguard® 810cc w/ Oil Guard (Per SAE J1995)
Displacement	603cc - 852cc
Cooling	Air cooled
Air Cleaner	FX: Remote canister • FS: Oval
Engine Warranty	3 year limited
DRIVE SYSTEM	
Type	Dual hydrostatic
Pumps	36" deck: Hydro-Gear® 10cc • 48", 52", 60" deck: Hydro-Gear® 12cc
Wheel Motors	36" deck: Parker® TL • 48", 52", 60" deck: Parker® TL
Speed	36": Up to 8 mph. • 48", 52", 60": Up to 9 mph.
Parking Brakes	Hand operated drum brakes
DECKS	
Cutting Width	Side discharge: 36", 48", 52", 60"
Cutting Heights	1.5" - 5.5"
Deck Lift	Hand operated.
Depth	5.5"
Blades	36": 2 • 48", 52", 60": 3
Blade Length	36" deck: 17.86" • 48" deck: 16.50" 52" deck: 17.86" • 60" deck: 20.50"
Blade Tip Speed	36": 18,700 • 48": 18,500 • 52": 17,700 • 60": 18,400
Spindles	Ductile cast iron with steel shafts and sealed ball bearings
Drive	Electric PTO clutch
Construction	7 ga. Fabricated w/ 7 ga. wrappers
Spindle Mounts	36": 7ga. with 11 ga. doubler • 48", 52", 60": 7 ga. with 7 ga. doubler
Impact/Trim Areas	11 ga. formed channel with rolled edge
CONSTRUCTION	
Frame	36": 1.5" x 2" steel tubing • 48" 52" 60": 1.5" x 3" steel tubing
Engine Plate	7 ga. with 11 ga. jackshaft doubler
Operator Platform	7 ga. with embossed tread pattern
Front Axle	Fabricated with tapered roller bearings
Front Caster Wheels	Tapered wheel bearings and debris cap
Front Caster Forks	Fabricated 3/8" steel
Operator Pad	Bolstered operator pad
GENERAL	
Fuel Capacity	36": 6.5 gallons • 48", 52", 60": 7.3 gallons
Front Tire	36" 11 x 4 - 5 • 48", 52": 13 x 5 - 6 • 60": 13 x 6.5 - 6
Drive Tire	36": 20 x 8 - 10 • 48", 52": 24 x 9.5 - 12 • 60": 24 x 12 - 12
DIMENSIONS	
Weight	36": 907 lbs • 48": 1144 lbs • 52": 1153 - 1182 lbs • 60": 1207 - 1232 lbs
Height	47"
Length	36": 63.5" • 48", 52": 68" • 60": 70.75"
Width w/Chute Up	36": 39" • 48": 49.3" • 52": 52.8" • 60": 61.7"
Tire Width	36": 36.3" • 48", 52": 45.8" 60": 49"
Trim Side	36": 0" • 48": 1.5" • 52": 3.5" • 60": 5.6"
PRODUCTIVITY**	
Acres Per Hour	36": 2.33 • 48": 3.49 • 52": 3.79 • 60": 4.36

Specifications are subject to change without notice.

* As rated by the engine manufacturer.

** Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain.

Kawasaki is a registered trademark owned by KAWASAKI JUKOGYO KABUSHIKI KAISHA. Vanguard is a registered trademark owned by Briggs & Stratton Corporation.

Parker is a registered trademark owned by Parker Intangibles LLC. Hydro-Gear is a registered trademark owned by Hydro-Gear Limited Partnership.