

MT7 SERIES

LS Tractor




MT7101CPS / MT7101CSPS
PREMIUM UTILITY TRACTORS

5-YEAR LIMITED WARRANTY. SEE DEALER FOR DETAILS

RECOMMENDED IMPLEMENTS/ ATTACHMENTS



LOADER:
High Capacity With
An Abundance Of
Standard Features



LAND GRADER:
Heavy Steel
Construction, High
Strength, Designed
For Use In Demanding
Applications



ROTARY CUTTER:
Durable Heavy Steel
Design Providing
Quality And Strength



BOX BLADE:
Features A Heavy
Welded Steel
Design For Use In
Demanding Applications

FEATURES

- **5 Year Warranty***
- **Available In 100.6 HP**
- **Cab Versions**
- **Unballasted Weight Up To 7,714 lbs.**
- **2 Sets Of Rear Remotes Standard With Float And Detent Functionality**
- **40F x 40R (Incl. Creep) Power Shuttle Or 32F x 32R (Incl. Creep) Semi-Powershift With Power Shuttle Transmission**



High Capacity Loader
High Performing Lift
Capacity, Among The
Industry Leaders In Lift
Height (139.9 in.)



Goodyear LSW Tires
Enable Better Traction,
Less Field Compaction



Spacious Cab
Providing a Roomy
Climate Controlled
Working Environment



**Standard Factory Grille
Guard W/ Loader**
Full Length Grille Guard
Protects Body Panels And
Radiator



Durability and Capacity
Heavy-Duty Frame And Lift
Cylinders Enable Three-Point
Lift Capacity Up To
5,139 lbs.



Power Shuttle Transmission
Provides Efficiency And
Comfort In Demanding
Applications (Standard)



Right-Side Cab Access
Enables Operators To Access
Both Sides Of The Cab
(Door And Steps)



**Four Standard
Rear Worklights**
Provides Significant
Illumination During
Night Operation



Semi-Powershift
Provides Push-Button Control
In Demanding Commercial
Applications

MT7101CPS / MT7101CSPS



SPECIFICATIONS

CATEGORY	MT7101CPS	MT7101CSPS
ENGINE	4 Cylinder, CRDI, Water-cooled	
Type	F5G	
Model	Tier 4 Final	
Emission	100.6 (75)	
Engine HP (kW)	85.5	
PTO (HP)	2,200	
Rated Speed (rpm)	206.7	
Displacement (in ³ .)	30.4	
Fuel Tank Capacity (gal.)		
DRIVE TRAIN		
Transmission Type (Option)	Power Shuttle	Semi-Powershift with Power Shuttle
No. Of Speed	40 x 40	32 x 32
Forward Speed (mph)	0.1 - 22.6	
PTO		
Type	Independent / Ground Speed PTO	
Rear (rpm)	540 / 750 / 1,000	
HYDRAULIC SYSTEM		
Control System	Position / Draft	
Implement Pump (gpm)	15.7	
Steering Pump (gpm)	6.5	
Total Flow (gpm)	22.2	
Category (3pt Hitch)	CAT II	
Hitch Lift Capacity (lbs.)	8,378	
Remote Ports	3 Pairs (Front) 2 Pairs (Rear)	
DIMENSION		
Overall Length (Frame To Link, in.)	152.2	
Overall Width With Tires (in.)	78.7	
Wheelbase (in.)	90	
Height To Top (in.)	105.4	
Total Weight Without Ballast (lbs.)	7,714	
TIRE SIZE		
Front / Rear R14	FW: 340/70R28, RR: 460/75R38	
Front / Rear Ag	F: 13.6-24 R: 18.4-34	

FRONT END LOADER	LL8100
TRACTOR APPLICATION	MT7 SERIES
Bucket Size (in.)	83
Maximum Lift Height (in.)	139.9
Clearance With Attachment Dump (in.)	103.3
Reach At Maximum Height (in.)	23.4
Maximum Dump Angle (deg.)	57
Maximum Rollback Angle (deg.)	46
Digging Depth (in.)	4.6
Overall Height In Carry Position (in.)	68.8
Lift Capacity (At Pivot Pin) (lbs.)	5,139
Breakout Force (At Pivot Pin) (lbs.)	5,313
Approx. Weight (Loader W/O Bucket) (lbs.)	1,660

Additional Equipment Available

- Standard Air Suspension Seat With Swivel
- Standard Electric Engaged Independent PTO
- Standard Instructor Seat
- Standard Monitor Bracket
- Standard Interior Power Source
- Optional Third Rear Remote

**All Specs and features are subject to change, and pictures could include optional equipment etc.*



LS Tractor

LS Tractor USA | P: 252.984.0700 | F: 252.984.0701 | LSTractorUSA.com
(Corporate Address) 6900 Corporation Parkway, Battleboro, NC

