

GRANDSTAND[®]

STAND-ON MOWERS

SEE PAGE 2 FOR BATTERY
REVOLUTION SERIES OPTIONS

STAND UP TO ANY TERRAIN.

 **HORIZON360**
CONTRACTOR BUSINESS SOFTWARE

COMPATIBLE

BUMPY PATCHES AND CHALLENGING TERRAIN ARE ALL IN A DAY'S WORK—but feeling them doesn't need to be. GrandStand[®] combines the speed and comfort of a zero-turn rider with the on-and-off ease of a walk-behind for speed and maneuverability.

IMPROVE PRODUCTIVITY with easy access on and off the machine—up to 10.5 gallons of fuel capacity on 48", 52", 60" and 72" models—to mow longer with fewer stops.

GAIN SPEED AND PERFORMANCE with a new max forward ground speed of up to 12 mph and responsive solid drive linkage. *(Select models only.)*

SAVE MAINTENANCE AND TIME with no hydraulic hoses, no daily/weekly grease points and a new engine design that allows extra room for service access. The fuel tank can also be removed without draining for easy service access to the transmission and controls.



GrandStand® Series helps you save time, money and trailer space with multi-season flexibility and a foldable operator platform.

2.6–5.5

Maximum Acres/Hour

Based on 90% efficiency (MPH x width of cut). Actual productivity dependent upon conditions.



TRACTION AND HANDLING

A wide stance and optimal balance enhance hillside stability and control. Operators can shift weight as needed to further enhance performance.



CUSHIONED SUSPENSION

Flex-Ride operator platform suspension self-compensates for operators of all sizes, resulting in less fatigue and higher productivity throughout the day.



2-IN-1 VERSATILITY

Foldable operator platform instantly converts the machine to a walk-behind. It easily lowers back down when it's time to ride, saving time and trailer space.



POWERED BAGGER

Compact side-mounted soft twin bagger and vertically mounted blower allow maneuverability in tight spaces and maximum visibility.



HIGHER HORSEPOWER

Effortlessly tackle demanding jobs with an upgraded 35 hp* Kawasaki FX1000 999cc engine. (Models 72507 and 72512)

	72504		72518		72505		72519		72513		72509		72520		HDX 72506	
POWER SYSTEM	71504 CARB				71505 CARB								NEW			
Commercial Engines at 3600 RPM*	22 hp Kawasaki FX (726cc)		▶ 23 hp Kohler® Command PRO® EFI (747cc)		22 hp Kawasaki FX (726cc)		▶ 25 hp Kohler Command PRO EFI (747cc)				23.5 hp Kawasaki FX730V (726cc)		Briggs 28 HP (883cc)		31 hp Kawasaki FX921 (999cc)	
Starter							FX (726cc)								Electric	
Heavy-Duty Canister Air Cleaner							▶ Standard								▶ Standard	
Drive Tires							▶ 20" x 10.5" – 8" (50.8 x 26.7 – 20.3 cm)								▶ 24" x 9.5" – 12" Turf (61 x 24.1 – 30.5 cm)	
Caster Tires							11" x 4" – 5" Flat-Free Semi-Pneumatic (27.9 x 10.2 – 12.7 cm)								13" x 6.5" – 6" Flat-Free Semi-Pneumatic (33 x 16.5 – 15.2 cm)	
Fuel/Capacity							Gas/10.5-Gal (39.7 L)								Gas/10.5-Gal (39.7 L)	
Digital Hour Meter							Standard								Standard	
Hydraulic Drive System							▶ Unitized Pumps & Wheel Motors								▶ Unitized Pumps & Wheel Motors	
Pump							10cc/rev								13cc/rev	
Wheel Motor							10 cir								13cc/rev	
Maximum Forward Speed							▶ 10 mph (16.1 km/h)								▶ 12 mph (19.3 km/h)	
Throttle Control							Manual								▶ Electronic	
Clutch							Electromagnetic								Electromagnetic	
MOWING DECKS																
Deck Size	▶ 48" (121.9 cm)		48" (121.9 cm)		▶ 52" (132.1 cm)		52" (132.1 cm)		▶ 60" (152.4 cm)		60" (152.4 cm)		60" (152.4 cm)		52" (132.1 cm)	
Cutting Deck							7-Gauge TURBO FORCE™								7-Gauge TURBO FORCE™	
Bullnose Bumper							Standard								Standard	
Adjustable Discharge Baffle							Standard								Standard	
Rubber Discharge Chute							Standard								Standard	
Deck Lift Design							▶ Extension Spring								▶ Extension Spring	
Spindle Housings							9 3/8" (23.8 cm) Diameter Cast Aluminum								9 3/8" (23.8 cm) Diameter Cast Aluminum	
1" (2.5 cm) Heavy-Duty Spindle Shaft							Standard								Standard	
Spindle Bearings							Maintenance-Free								Maintenance-Free	
Cutting Height							▶ 1.5" – 5.0" (3.8 – 12.7 cm)								▶ 1.5" – 5.0" (3.8 – 12.7 cm)	
Blades							.204" (.5 cm) Heat-Treated Steel								.204" (.5 cm) Heat-Treated Steel	
Blade Tip Speed							18,500+ ft/min								18,500+ ft/min	
Belt Construction							Aramid Fiber V-Belt								Aramid Fiber V-Belt	
Anti-Scalp Rollers			▶ Optional						▶ Standard						Standard	
Carrier Frame Construction							3" x 1.5" x 12-Gauge (7.6 cm x 3.8 cm x 12-Gauge)								3" x 1.5" x 12-Gauge (7.6 cm x 3.8 cm x 12-Gauge)	
FEATURES																
Steering Controls							Twin Lever								Twin Lever	
Operator Platform							Foldable Operator Platform with Suspension								Foldable Operator Platform with Suspension	
WEIGHTS AND MEASUREMENTS																
Weight	890 lbs.	403.7 kg	881 lbs.	399.6 kg	898 lbs.	407.3 kg	895 lbs.	406 kg	941 lbs.	426.8 kg	941 lbs.	426.8 kg	941 lbs.	426.8 kg	1061 lbs.	481.3 kg
Height	48"	121.9 cm	48"	121.9 cm	48"	121.9 cm	48"	121.9 cm	48"	121.9 cm	48"	121.9 cm	48"	121.9 cm	50.25"	127.6 cm
Deck Clearance Width	49.5"	125.7 cm	49.5"	125.7 cm	53.5"	135.9 cm	53.5"	135.9 cm	61.5"	156.2 cm	61.5"	156.2 cm	61.5"	156.2 cm	N/A	N/A
Deflector Width	63.5"	161.3 cm	63.5"	161.3 cm	67.5"	171.5 cm	67.5"	171.5 cm	75.5"	191.8 cm	75.5"	191.8 cm	75.5"	191.8 cm	53.5"	135.9 cm
Length (Platform Up)	61"	154.9 cm	61"	154.9 cm	61"	154.9 cm	61"	154.9 cm	65"	165.1 cm	65"	165.1 cm	65"	165.1 cm	71"	180.3 cm
Length (Platform Down)	75"	190.5 cm	75"	190.5 cm	75"	190.5 cm	75"	190.5 cm	79"	200.7 cm	79"	200.7 cm	79"	200.7 cm	85.5"	217.2 cm

* The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.

▶ = Step Up Feature

	HDX 72510	HDX 72514	HDX 72517	HD+ 72507	HD+ 72512	HDM 74534	HDM 74532	HDM 74535								
POWER SYSTEM				NEW	NEW	79534 CARB	NEW	NEW								
Commercial Engines at 3600 RPM*	31 hp Kawasaki FX921 (999cc)	37 hp Briggs & Stratton® Vanguard® EFI w/Oil Guard (993cc)	37 hp Briggs & Stratton® Vanguard® EFI w/Oil Guard (993cc)		35 hp Kawasaki FX1000 (999 cc)	15 hp Kawasaki® FS (603cc)		18.5 hp Kawasaki FS600V (603 cc)								
Starter		Electric			Electric	Electric		Electric								
Heavy-Duty Canister Air Cleaner		▶ Standard			▶ Standard	N/A		▶ Standard								
Drive Tires		▶ 24" x 12" – 12" Turf (61 x 30.5 – 30.5 cm)			20 in. x 10.5 in. – 8 in. (50.8 cm x 26.7 cm – 20.3 cm)	18" x 8.5" – 8" (45.7 x 21.6 – 20.3 cm)		21 in. x 7 in. – 10 in. (53.3 cm x 17.7 cm – 25.4 cm)								
Caster Tires		13" x 6.5" – 6" Flat-Free Semi-Pneumatic (33 x 16.5 – 15.2 cm)			11" x 4" – 5" Flat-Free Semi-Pneumatic (27.9 x 10.2 – 12.7 cm)	11" x 4" – 5" Flat-Free Semi-Pneumatic (27.9 x 10.2 – 12.7 cm)		9 in. x 4.5 in. – 5 in. Semi-Pneumatic (22.8 cm x 11.4 cm – 12.7 cm)								
Fuel/Capacity		Gas/10.5-Gal (39.7 L)			Gas/10.5-Gal (39.7 L)	Gas/7.8-Gal (29.5 L)		Gas/5-Gal (18.9 L)								
Digital Hour Meter		Standard			Standard	Standard		Standard								
Hydraulic Drive System		▶ Unitized Pumps & Wheel Motors			▶ Unitized Pumps & Wheel Motors	Pumps & Wheel Motors		▶ Unitized Pumps & Wheel Motors								
Pump		13cc/rev			10 cc/rev	10cc/rev		13cc/rev								
Wheel Motor		13cc/rev			10 cc/rev	10 cir		13cc/rev								
Maximum Forward Speed		▶ 12 mph (19.3 km/h)			▶ 12 mph (19.3 km/h)	8 mph (12.9 km/h)		7.5 mph (12.0 km/h)								
Throttle Control		▶ Electronic			▶ Electronic	Manual		▶ Electronic								
Clutch		Electromagnetic			Electromagnetic	Electromagnetic		Electromagnetic								
MOWING DECKS																
Deck Size	60" (152.4 cm)	60" (152.4 cm)	▶ 72" (182.9 cm)	52" (132.1 cm)	60" (152.4 cm)	36" (91.4 cm)	32" (81.2cm)	36" (91.4 cm)								
Cutting Deck		7-Gauge TURBO FORCE®			7-Gauge TURBO FORCE®	7-Gauge TURBO FORCE®		7-Gauge TURBO FORCE®								
Bullnose Bumper		Standard			Standard	Standard		Standard								
Adjustable Discharge Baffle		Standard			Standard	Standard		Standard								
Rubber Discharge Chute		Standard			Standard	Standard		Standard								
Deck Lift Design		▶ Extension Spring			▶ Extension Spring	Compression Spring		▶ Extension Spring								
Spindle Housings		9 3/8" (23.8 cm) Diameter Cast Aluminum			9 in / 22.9 cm Diameter Cast Aluminum	Cast Iron		7.75 in/19.7cm Dia Cast Aluminum								
1" (2.5 cm) Heavy-Duty Spindle Shaft		Standard			Standard	Standard		Standard								
Spindle Bearings		Maintenance-Free			Maintenance-Free	Maintenance-Free		Maintenance-Free								
Cutting Height		▶ 1.5" – 5.0" (3.8 – 12.7 cm)			▶ 1.5" – 5.0" (3.8 – 12.7 cm)	1.0" – 5.0" (2.5 – 12.7 cm)		1.0" – 4.5" (2.54 – 11.4 cm)								
Blades		.204" (.5 cm) Heat-Treated Steel			.204" (.5 cm) Heat-Treated Steel	.25" (.6 cm) Heat-Treated Steel		.204" (.5 cm) Heat-Treated Steel								
Blade Tip Speed		18,500+ ft/min			18,500+ ft/min	18,500+ ft/min		18,500+ ft/min								
Belt Construction		Aramid Fiber V-Belt			Aramid Fiber V-Belt	Aramid Fiber V-Belt		Aramid Fiber V-Belt								
Anti-Scalp Rollers		Standard			Optional	Standard		N/A								
Carrier Frame Construction		3" x 1.5" x 12-Gauge (7.6 cm x 3.8 cm x 12-Gauge)			3" x 1.5" x 12-Gauge (7.6 cm x 3.8 cm x 12-Gauge)	3" x 1.5" x 12-Gauge (7.6 cm x 3.8 cm x 12-Gauge)		3" x 1.5" x 10-Gauge (7.6cm x 3.8cm x 10-Gauge)								
FEATURES																
Steering Controls		Twin Lever			Twin Lever			Twin Lever								
Operator Platform		Foldable Operator Platform with Suspension			Foldable Operator Platform with Suspension			Foldable Operator Platform with Suspension								
WEIGHTS AND MEASUREMENT																
Weight	1091 lbs.	494.9 kg	1100 lbs.	499.0 kg	1193 lbs.	541.1 kg	949 lb	430 kg	1004 lb	455 kg	833 lbs.	377.8 kg	702 lbs	318.4 kg	779 lbs	353.3 kg
Height	50.25"	127.6 cm	50.25"	127.6 cm	50.25"	127.6 cm	48"	122 cm	48"	122 cm	48"	121.9 cm	47.3"	120.1 cm	47.3"	120.1 cm
Deck Clearance Width	N/A	N/A	N/A	N/A	N/A	N/A	54"	137 cm	62"	158 cm	37.6"	95.5 cm	N/A	N/A	N/A	N/A
Deflector Width	61.5"	156.2 cm	61.5"	156.2 cm	73.75"	187.3 cm	68"	172 cm	76"	193 cm	51.6"	131.1 cm	44.9"	114 cm	48.0"	122 cm
Length (Platform Up)	73.5"	186.7 cm	61.5"	156.2 cm	73.75"	187.3 cm	61"	145 cm	65"	164 cm	61"	154.9 cm	58.1"	147.5 cm	58.1"	147.5 cm
Length (Platform Down)	88.0"	223.5 cm	75.25"	190.5 cm	87.75"	222.9 cm	75"	191 cm	79"	201 cm	74"	188 cm	N/A	N/A	N/A	N/A

* The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.

▶ = Step Up Feature