

2013 Sno Pro 500

MSRP \$9,999 CAD



AVAILABLE COLORS:

ENGINE

Туре	2-stroke
Displacement	499cc
Cooling	Liquid
Cylinders	Twin
Bore X Stroke	71 x 63 mm
Lubrication	Oil injection
Ignition	3D
Carburetion	38 mm throttle body batteryless EFI
Exhaust	Tuned pipe and muffler
Fuel Capacity	41.6 cm

SUSPENSION

Front Suspension	AWS VIII with Fox Zero Pro IFP
Front Travel	24.1 cm
Rear Suspension	Race slide-action suspension with coupling blocks, adjustable torsion springs and FOX (IFP) shocks 5.1 cm dia. rear shock
Rear Travel	34.3 cm

DIMENSIONS

Overall Length	297.2 cm
Overall Width	11.9 cm
Ski Stance	109.2 cm
Ski Type	Trail 15.2 cm
Runner Type	Single skag w/carbide
Track Type	HackSaw
Track Width	38.1 cm
Track Length	325.1 cm
Lug	2.5 cm
Pitch	6.4 cm

STANDARD FEATURES

Dual halogen headlight (4-bulb), low-height windshield, digital/analog gauge, hand/thumb warmer, tether switch, electric fuel gauge, low oil light, coolant overheat light

OPTIONAL FEATURES

Sport bumper, hand guards, premium shocks, storage bags, (mid, high) windshield

Cobra,[™] HackSaw[™] and RipSaw[™] are trademarks of Camoplast Inc. Diamond Direct Drive[™] is a trademark of Black Diamond, Inc. FOX® and FOX Float® AirShox[™] are registered trademarks of FOX Racing Shox. ACT,[™] Arctic Cat[®] Arctic Drive System,[™] Arctic Race Suspension,[™] AWS,[™] Bearcat[®] Cat,[™] Crossfire,[™] Diamond Direct Drive,[™] Exhaust Pipe Temperature Sensor,[™] F Series,[™] FasTrack[®] IRP,[™] Infinite Rider Positioning,[™] Power Claw,[™] ProClimb,[™] ProCross,[™] Share Our Passion,[™] Slide-Action Rear Suspension,[™] Sno Pro,[®] SpeedRack,[®] Twin Spar,[™] and Z1[™] are trademarks or registered trademarks of Arctic Cat Inc. Arctic Cat Sales Inc. is not a successor of Arctic Enterprises, Inc. ©2012 Arctic Cat Sales Inc.,^{®™} Trademarks of Arctic Cat Inc., 601 Brooks Avenue South, Thief River Falls, MN 56701.

Because of our ongoing commitment to product quality and innovation, Arctic Cat reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. See your dealer for details.

POWERTRAIN

Drive Clutch	Arctic 6 post (rpm sensing)
Driven Clutch	Team driven
Drive System	Chain / Sprocket
Brakes	Axial master cylinder hydraulic brake / disc on driven shaft