



L7

INDUSTRY'S HARDEST WORKING, SMOOTHEST RIDING UTV OF IT'S CLASS

(shown with optional accessories)



4WD · POWER STEERING (EPS) · VANGUARD 627CC



MADE IN USA

*Price above does not include setup fees, destination charges, installation charges or any other fees charged at the dealership.



THE BEST COMBINATION OF DURATION AND COVERAGE IN THE INDUSTRY

We build UTVs at American LandMaster with the intention of our customers never needing to use a warranty, but we know things can happen. The **Easy Life Warranty** from American LandMaster is a 12-month bumper-to-bumper limited warranty. Does limited sound confusing? It isn't. **As long as you care for your machine like you should, don't wreck it, or crush it, or let it be attacked by unruly farm animals, we're going to cover it.** Except for tires, brake pads, batteries, damage, neglect. That's the limit. [Visit AmericanLandMaster.com to learn more.](http://AmericanLandMaster.com)

POWER	23hp 627cc Commercial-Grade, V-Twin OHV-Technology, EFI Vanguard 4-stroke Gas Engine. Superior balance, low vibration, lower emissions, improved valve life, better fuel economy and higher HP/Weight
SEATING CAPACITY	2-Person*
SPEED	35mph +
FUEL CONSUMPTION	Up to 28 mpg**
RANGE	Up to 100 miles**
STARTING	12V keyed ignition - remote jump start terminals
BATTERY	12V / 315 cca utility class
SPARK PLUG	NGK C7HSA
FUEL CAPACITY	5.0 gal
ALTERNATOR	25 amp
TRANSMISSION	CVT automatic
TRANSAXLE	Gear drive Schafer/DANA oil-filled transaxle
DIFFERENTIAL	Cable Actuated Rear-Locking
DRIVE	Switch engaged on demand, 4 wheel drive
FRONT SUSPENSION	Double A-arms, adjustable coil over shock with up to 8" travel
REAR SUSPENSION	Independent trailing arm, with radius rod, adjustable camber & tow control, dual-rate coil over shock with up to 8" of travel
BRAKE SYSTEM	4 wheel disc, hydraulic brake
TIRES	25 x 8 - 12 (front) 25 x 10 - 12 (rear)
DIMENSIONS	110" L x 58" W x 76" H (110" with poly bed)
WHEEL BASE	73"
TURNING RADIUS	12' inside radius
GVRW	L-ROSS - 2,100 lbs. / HD-LROSS - 2,300 lbs.
CURB WEIGHT	1,200 lbs.
BED MATERIALS	Structural foam "Poly Bed" with stake pockets
BED DIMENSIONS	35.25" L x 41.5" W x 11" D
BED CAPACITY	Poly - 9 cu.ft. / Steel - 11 cu.ft. / L-ROSS - 500 lbs. / HD-LROSS - 700 lbs.
TOWING CAPACITY	1,500 lbs.
TOTAL PAYLOAD	L-ROSS - 900 lbs. / HD-LROSS - 1,100 lbs.
WARRANTY	3 year engine / All other 1 year limited
ADDITIONAL FEATURES	3pt lap/shoulder DOT certified belts for driver and passenger with driver indicator light, twin 12V auxiliary outlets for accessories, 12V/18W LED headlights, polyurethane powder paint, 2" front and rear receiver hitch, dump bed, bench seating, welded steel frame, Complete weather-sealed wiring connections. Wide selection of additional accessories available along with three bed options. Fuel gauge located underside of bed. In-dash, hour/volt meter standard

* 2 additional seats with optional seat bed.

** Estimates. Actual top speeds, fuel consumptions and vehicle ranges may vary due to driving conditions, terrain, climate and other extenuating circumstances.