



* Shown w/ optional Alum. Wheel Upgrade & Extruded Aluminum Floor

WIDTH/LENGTH	BASE PRODUCT CODE	MSRP
7x16	7X16OCHA35	
7x18	7X18OCHA35	
7x20	7X20OCHA35	
7x22	7X22OCHA35	
* 7x24	7X24OCHA52	

* Standard w/ 5,200# Axles & ST225/75R15, 6-Bolt Tires

HIGHLIGHTS

- 32" Beavertail (18' - 24')
- Triple Tube A-Frame Steel Reinforced Tongue
- Removable ATP Fenders
- Surface Mount LED Lighting
- Rub Rail
- Stake Pockets
- Front Mounted Ramps
- Tubing Bump Rail

	STANDARD FEATURES		POPULAR OPTIONS			
				MSRP		MSRP
STRUCTURAL						
Cross Members	2" x 3" Tube 16" OC	12" OC				
Frame	2" x 6" Tube					
Jack	2,000# Top-Wind A-Frame Jack w/ Foot	5,000# Jack w/ Foot			7,000# Drop-Leg Jack w/ Foot	
Rear Loading	12" x 82" Aluminum Ramps (Front Mounted)	Rear Slide-In Ramps ILO Front Mount				
Side Loading	N/A					
Tongue	2" x 6" Tube w/ Steel Reinforcement					
Top Rail	2" Tube Bump Rail					
RUNNING GEAR						
* Axles	3,500# E-Z Lube Torsion, 2 Electric Brakes (16'-22')	5,200# w/ 225 Tires (6-Bolt) (Standard on 24')				
Tires/Wheels	ST205/75R15 Nitrogen Filled Silver Mod Steel	ST205/75R15 Spare Tire	Alum-Steel		Removable Spare Mount (Stake Pocket Mount)	Aluminum Wheels Upgrade
FLOORS						
Beavertail	32" (18' - 24')	No Beavertail (Standard on 16')				
Floor	Dura Color Dimensional Pine	Extruded Aluminum				
COMPONENTS						
Coupler	2 ^{5/16"} A-Frame	Adjustable 2 ^{5/16"} Coupler			Adjustable Pintle	
Stake Pockets	Included w/ Rub Rail	Additional Stake Pockets				
Storage	Optional					
Tie Downs	4-5,000# D-Rings (Installed)	Additional 5,000# D-Rings (Installed)				

[View All Aluminum Options](#)