aoutlander Max XT

IGHLIGHTS

- Rotax[®] V-twin engine options
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS[™]) ٠
- 3,000-lb (1,361 kg) WARN[†] winch ٠ with roller fairlead
- Heavy-duty front and rear bumpers ٠
- 14-in. cast-aluminum wheels •
- 26-in. ITP⁺ Terracross radial tires ٠
- Painted plastics for premium look
- · Handlebar wind deflectors
- Convertible Rack System (CRS) • with LinQ[™] system
- Dynamic passenger comfort ergonomics
- Multiposition passenger handgrips

- Raised floorboards
- 5.7-gal (21.4 L) water-resistant rear compartment
- 625-W magneto



Brushed Aluminum / 650 / 850 / 1000R Pearl White & Black / 650 / 850 / 1000R Mossy Oak† Break-Up Country Camo† / 650 / 850

ENGINES	650	850	1000R
Туре	62 hp, Rotax 649.6 cc V-twin, liquid cooled	78 hp, Rotax 854 cc V-twin, liquid cooled	89 hp, Rotax 976 cc V-twin, liquid cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)		
Transmission	CVT, P / R / N / H / L, standard engine braking		
Drive Train	Selectable 2WD / 4WD with Visco-Lok [‡] QE auto-locking front differential		
Power Steering	Tri-Mode Dynamic Power Steering (DPS)		

SUSPENSIONS

Rear

Front Suspension	Double A-arm 9 in. (22.9 cm) travel	
Front Shocks	Oil	
Rear Suspension	Torsional Trailing arm Independent (TTI) 9.3 in. (23.6 cm) travel	
Rear Shocks	Oil	
BRAKES		
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers	

Single 214 mm ventilated disc brake with hydraulic twin-piston caliper

TIRES / WHEELS	
Front Tires	ITP Terracross 26 x 8 x 14 in. (66 x 20.3 x 35.6 cm)
Rear Tires	ITP Terracross 26 x 10 x 14 in. (66 x 25.4 x 35.6 cm)
Wheels	14-in. cast-aluminum

DIMENSIONS / CAPACITIES		
LxWxH	94 x 46 x 53 in. (238.8 x 116.8 x 135 cm)	
Wheelbase	59 in. (149.9 cm)	
Ground Clearance	11 in. (27.9 cm)	
Seat Height	34.5 in. (87.7 cm)	
Engine / Dry Weight*	650 / 795 lb (361 kg) 850 / 821 lb (372 kg) 1000R / 840 lb (381 kg)	
Rack Capacity	Front: 100 lb (45 kg) Rear: 200 lb (90 kg)	
Storage Capacity	Rear: 5.7 gal (21.4 L)	
Towing Capacity	1,300 lb (590 kg)	
Fuel Capacity	5.4 gal (20.5 L)	

FEATURES			
Gauge	Multifunction Digital: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
		Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
		Seat	Convertible Rack System (CRS)
Winch	3,000-lb (1,361 kg) WARN winch with roller fairlead	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)
Protection	Heavy-duty front & rear bumpers, handlebar wind deflectors		

WARRANTY	
Factory	6-months limited warranty
Extended	Up to 36 months B.E.S.T. coverage



©2016 Bombardier Recreational Products Inc (BRP). All rights reserved. TM, [®] and the BRP logo are registered trademarks of BRP or its affiliates. Products are distributed in the U.S.A. by BRP US Inc. [®]Base model dry weight shown. [®]Visco-Lok is a trademark of GKU Viscodrive GmbH. ^YAll other trademarks are the properly of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any polyligiton. Rife responsibly, BRP high vecommends that all AV drivers take a training course. For safety and training information, see your dealer or, in U.S.A. call the ATV Safety Institute at 1 (800) 887-2887. In Canada, call the Canadian Safety Council at 1 (613) 739-1535 ext 227. **ATVs can be hazardous to operate.** For your safety: the operator and passenger should wear a helmet, eye protection and other protective clubing. Always remember that ring and alcohol / drugs don't this. Avere ride on parties or your face on the ongate of the roads. Never earry passengers on any ATV not specifically designated for such use.



Can-AmOffroad.com