

MODEL LOW20G, 14K



THE N&N ADVANTAGE

For those times when it's important to stay close to the ground and you need to load equipment quickly and head off to new horizons. With its very low loading angle, and a hydraulic system at the front, the Lowland trailer is the perfect partner for transporting small excavation equipment.

STANDARD FEATURES

- 6" channel frame
- Cross members on 16" C/C
- 235-80R16 10 ply radial tires
- 14,000 lb power up, gravity down cylinder
- 4" galvanized drop axles
- Slipper spring suspension
- Adjustable $2\frac{5}{16}$ " coupler
- 25" deck height
- Full plate at rear for trailer access
- Winch mounting plate on front
- 4 welded D-rings
- Pocket side with flat bar

- LED lights
- Plank decking
- Aluminum toolbox on front
- 80" width between fenders
- 12,000 lb drop-leg jack
- Installed smart battery charger (1.5A)

SPECIFICATIONS

USABLE WIDTH	80 inches
USABLE LENGTH	242 inches
AXLES	2 x 7,000 lb (electric)
BRAKES	Electric
TIRES	235-80R16 10 ply radial
WEIGHT WHEN EMPTY	3,650 lb
LOAD CAPACITY	11,410 lb
TRAILER LENGTH	312 inches
TRAILER WIDTH	102 inches
DECKING	Hemlock
RAMP	-
FINISH	Hot dipped galvanized

